








































رد	ت	(ر ل)
1	<p>HAC-HFW1509MHP-A-LED-S2</p>   <p>5MP Full-color HDCVI Bullet Camera Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens <b>Built-in Mic</b> CVI/CVBS/AHD/TVI Switchable, Support OSD Menu 120 dB true WDR, HLC,HLC-Pro, BLC, 3D DNR, AGC, AWB 2 LEDs 50m Distance, Smart Light, IP67, DC12V</p>	 <p>33.350.000</p>
2	<p>HAC-HFW1509TMP-IL-A</p>   <p>5MP Smart Dual Illuminators Bullet Camera Max 25 fps@5MP (16:9 video output). 120 dB true WDR, 3D NR. Smart Dual Illuminators, 40 m illumination distance Min. Illumination, 0.001 lux@F1.0 (Color, 30 IRE), 0.0001 lux@F1.0 (B/W, 30 IRE) Super Adapt, Built-in MIC, BLC; HLC; WDR; HLC-Pro 3.6 mm fixed lens (2.8 mm optional). CVI/CVBS/AHD/TVI switchable, IP67, 12 VDC</p>	 <p>39.400.000</p>
3	<p>HAC-HFW1509TLM-A-LED</p>   <p>5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens <b>Built-in Mic</b> CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, BLC, 3D DNR, AGC, AWB 2 LEDs 40m Distance, Smart Light, IP67, DC12V</p>	 <p>31.800.000</p>
4	<p>HAC-HFW1509TLMP-LED</p>  <p>5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, BLC, 3D DNR, AGC, AWB 2 LEDs 40m Distance, Smart Light, IP67, DC12V</p>	 <p>29.950.000</p>
5	<p>HAC-HFW1509TP-LED</p>  <p>5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, HLC-Pro, BLC, 3D DNR, AGC, AWB 1 LED 20m Distance, Smart Light, IP67, DC12V</p>	 <p>29.500.000</p>
6	<p>HAC-HFW1509TP-A</p>  <p>5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) <b>Built-in mic</b> 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, HLC-Pro, BLC, 3D DNR, AGC, AWB 1 LED 20m Distance, Smart Light, IP67, DC12V</p>	 <p>30.150.000</p>
7	<p>DH-HAC-HFW1500RP-Z-IRE6</p>  <p>5MP Starlight HDCVI IR Bullet Camera, Image Sensor 1/2.7 inch CMOS Max 25 fps@5MP (16:9 video output) CVI/CVBS/AHD/TVI switchable 2.7 mm-12 mm motorized lens, 0.005 Lux/F1.6, 30IRE, 0 Lux IR on Illumination Distance 60 m , S/N Ratio &gt; 65 dB Pan/Tilt/Rotation Range Pan: 0°-360°, Tilt: 0°-90°, Rotation: 0°-360° Max. IR length 60 m, Smart IR, BLC/HLC/DWDR IP67, 12V DC</p>	 <p>40.150.000</p>






















رد	ت	رد
8	DH-HAC-HFW1500THP-I4 5MP HDCVI IR Bullet Camera, 1/2.7" Progressive Scan CMOS 20fps@5MP, 25/30fps@4MP (16:9 video output) 3.6mm fixed lens, Aperture: F1.85 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Support Electronic Defog, HD/SD switchable Max. IR length 40m, Smart IR, IP67, DC12V±30	 19.900.000
9	DH-HAC-HFW1500THP-I8 5MP HDCVI IR Bullet Camera, 1/2.7" Progressive Scan CMOS 20fps@5MP, 25/30fps@4MP (16:9 video output) 3.6mm fixed lens, Aperture: F1.85 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Support Electronic Defog, HD/SD switchable Max. IR length 80m, Smart IR, IP67, DC12V±30	 22.800.000
10	DH-HAC-HFW1500TP-0360B-S3 5MP Starlight HDCVI IR Bullet Camera Max 25 fps@5MP (16:9 video output) 3.6 mm fixed lens, Max. Aperture F1.6 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR CVI/CVBS/AHD/TVI switchable, Support OSD Menu Max. IR length 30 m, Smart IR, IP67, DC12V	 19.600.000
11	DH-HAC-HFW1500DP 5MP Starlight HDCVI IR Bullet Camera Max 25 fps@5MP (16:9 video output) 3.6 mm fixed lens, Max. Aperture F1.6/Min. Illumination 0.005 Lux DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR CVI/CVBS/AHD/TVI switchable, Support OSD Menu Max. IR length 80 m, Smart IR, IP67, DC12V	 27.500.000
12	DH-HAC-HFW1500CMP 5MP Starlight HDCVI IR Bullet Camera Max 25 fps@5MP (16:9 video output) 3.6 mm fixed lens, Max. Aperture F1.6/Min. Illumination 0.005 Lux DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR CVI/CVBS/AHD/TVI switchable, Support OSD Menu Max. IR length 30 m, Smart IR, IP67, DC12V	 19.600.000
13	HAC-B1A51 5MP HDCVI IR Bullet Camera, 1/2.7" 5 MegaPixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P (16:9 video output) 3.6mm, 2.8mm fixed lens, HD and SD output switchable DWDR, Day/Night(ICR), BLC, HLC, AGC, AWB, 2D-DNR, Support OSD Menu, Max. IR length 20m, Smart IR, IP67, DC12V, Casing Plastic	 15.000.000
14	DH-HAC-B2A51P 5MP HDCVI IR Bullet Camera, 1/2.7" 5 MegaPixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P (16:9 video output) 3.6mm fixed lens, HD and SD output switchable DWDR, Day/Night(ICR), BLC, HLC, AGC, AWB, 2D-DNR, Support OSD Menu, Max. IR length 20m, Smart IR IP67, DC12V, Casing Aluminium	 17.500.000
15	DH-HAC-B1A41P 4MP HDCVI IR Bullet Camera, 1/2.7" 4Megapixel CMOS 25/30fps@4MP,25/30fps@1080P, 3.6mm fixed lens HD and SD output switchable, Max. IR length 20m IP67, DC12V, Casing: Plastic	 12.650.000
16	DH-HAC-B2A41P 4MP HDCVI IR Bullet Camera, 1/2.7" 4Megapixel CMOS 25/30fps@4MP,25/30fps@1080P, 3.6mm fixed lens HD and SD output switchable, Max. IR length 20m IP67, DC12V, Casing: Aluminium	 15.450.000
17	HFW1239TLMIP-IL-A 2MP Smart Dual Illuminators Bullet Camera Progressive CMOS - Focal Length 3.6 mm Max. 30 fps@1080p 0.001 lux@F1.6 (Color, 30 IRE) - 0.0001 lux(B/W, 30 IRE) - 0 lux (Illuminator on) Smart Dual Illuminators - Built-in-mic CVI/CVBS/AHD/TVI Switchable, Support OSD Menu 130 dB true WDR, HLC, BLC, 3D DNR, AGC, AWB 2 LEDs 40m distance - 2 IR Lights 40m distance Smart IR & WL, IP67, DC12V	 25.000.000
18	HFW1239MHP-A-LED 2MP Full-color HDCVI Bullet Camera, 1/2.8" CMOS ,24/7 color imaging Max. 30 fps@1080p,3.6 mm fixed lens (6 mm optional) 50 m illumination distance , Super Adapt, 130 dB true WDR, 3D NR Focal Length 3.6 mm; 6 mm , Built-in mic ,CVI/CVBS/AHD/TVI switchable Min Illumination 0.001 Lux/F1.6, 30IRE, 0 Lux LED on , IP67, DC 12 V	 28.400.000























19	DH-HAC-HFW1239TLMP-A-LED		<p>2M Full-color Starlight HDCVI Bullet Camera 1/2.8 inch 2.16 MP CMOS Minimum Illumination:0.005Lux/F1.6 1080@25fps, 720@25/50fps 3.6mm fixed lens <b>Built-in mic</b> CVI/CVBS/AHD/TVI Switchable WDR (130 db) , BLC, HLC, 2DNR,AGC,AWB Electronic Defog 40m LED distance, IP67, DC12V</p>		22.700.000
20	DH-HAC-HFW1239TLMP-LED		<p>2M Full-color Starlight HDCVI Bullet Camera 1/2.8 inch 2.16 Mega Pixels Progressive CMOS 0.005Lux/F1.6, 30IRE, 0Lux white Light on Max. 30fps@1080P 3.6mm fixed lens, 16x Digital Zoom CVI/TVI/AHD/CVBS Switchable, Support OSD Menu WDR (130 db)/E-Defog/BLC/HLC/AWB/AGC/2D DNR 40m LED Distance Smart Light, IP67, DC12V</p>		22.350.000
21	HAC-HFW1239TP-LED		<p>2MP Full-color HDCVI Bullet Camera 2MP 1/2.8" Progressive CMOS Max 2MP@25/30fps 3.6mm fixed lens CVI/CVBS/AHD/TVI switchable, Support OSD Menu WDR(130db), BLC, HLC, AWB, AGC, 3D DNR Smart Light, 1 LED 20m Distance, IP67, DC12V</p>		21.450.000
22	DH-HAC-HFW1231RP-Z-A	 	<p>2MP Starlight HDCVI IR Bullet Camera 1/2.8" 2Megapixel CMOS (Starlight) Minimum Illumination:0.002Lux/F1.5 1080@25fps, 720@25/50fps 2.7-12mm motorized lens HD and SD output switchable,<b>Built in mic</b>, WDR(130dB), BLC, HLC, 3DNR, AGC,AWB 80m LED distance, Smart IR, IP67, DC12V</p>		36.650.000
23	DH-HAC-HFW1231RP-Z-IRE6		<p>2MP Starlight HDCVI IR Bullet Camera 1/2.8" 2Megapixel CMOS (Starlight) Minimum Illumination:0.002Lux/F1.5 1080@25fps, 720@25/50fps 2.7-12mm motorized lens HD and SD output switchable WDR(130dB), BLC, HLC, 3DNR, AGC,AWB 80m LED distance, Smart IR, IP67, DC12V</p>		35.750.000
24	DH-HAC-HFW1230RP-Z-IRE6		<p>2MP Starlight HDCVI IR Bullet Camera 1/2.8" 2Megapixel CMOS (Starlight) Minimum Illumination:0.005Lux/F1.8 1080@25fps, 720@25/50fps 2.7-12mm motorized lens HD and SD output switchable DWDR, BLC, HLC, 2DNR, AGC,AWB 60m LED distance, Smart IR, IP67, DC12V</p>		32.450.000
25	DH-HAC-HFW1230TP		<p>2MP Starlight HDCVI IR Bullet Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens (2.8mm, 6mm Optional) HD and SD output switchable, Support OSD Menu Starlight, DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V, Casing: Aluminium</p>		15.650.000
26	DH-HAC-HFW1230TP-A		<p>2MP Starlight HDCVI IR Bullet Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, <b>Built-in mic</b> DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V</p>		16.100.000
27	DH-HAC-HFW1230DP		<p>1/2.8" 2Megapixel CMOS (Starlight) 3.6mm Fixed lens, 25/30fps@1080P &amp; @720P DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, OSD Menu Max. IR length 80m, Smart IR, IP67, DC12V</p>		20.700.000

28	DH-HAC-HFW1220THP-I4	Value Starlight	2MP Value Starlight HDCVI IR Bullet Camera 1/2.7 inch CMOS 1080P@25fps, 720P@25fps, 720@50fps 3.6mm Fixed lens Value Starlight Minimum Illumination:0.008Lux/F1.85 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D DNR Smart IR, Eletronic Defog CVI/CVBS/AHD/TVI switchable Max. IR length 40m, Smart IR, IP67, DC12V		16.100.000
29	HAC-HFW1209TLMP-LED-0360B	Full-color	2MP Full-color HDCVI Bullet Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 3.6mm Fixed lens Min. Illumination 0.001 Lux/F1.6, 30IRE, 0 Lux LED on DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3D DNR CVI/CVBS/AHD/TVI switchable, OSD Menu Support 40m LED distance, IP67, DC12V		17.850.000
30	HAC-HFW1209CMP-LED-0360B	Starlight Full-color	2MP Full Color Starlight HDCVI Bullet CCTV Camera 1/2.8 inch 2.16 Mega Pixels Progressive CMOS Max 30fps@2MP 3.6mm fixed lens CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V		16.750.000
31	HAC-HFW1209CP-LED-0360B	Full-color	2MP Full-color HDCVI Bullet Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu DWDR/BLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V		13.550.000
32	HAC-HFW1200TLM-IL-A	DUAL LITE Full-color	<b>NEW</b> 2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera * In order to use the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000004.1.R.220323 or later version. 2 MP Progressive CMOS Sensor 3.6 mm Lens: H: 83°; V: 48°; D: 105° Max. 30 fps@1080p, CVI/CVBS/AHD/TVI switchable DWDR, BLC, HLC, AWB, AGC, Day/Night Auto(ICR)/Color/B/W, Smart Dual Light, Illumination Distance IR: 40 m (131.23 ft) Warm light: 40 m (131.23 ft) , Super Adapt, 3D DNR, <b>Built-in mic, 1 Audio in</b> Min. Illumination 0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on) 12 VDC, IP67, Metal+Plastic		17.600.000
33	DH-HAC-HFW1200RP-Z-IRE6	Starlight	2MP HDCVI IR Bullet Camera, 1/2.7 inch CMOS Max 30fps@1080P, Min Illumination 0.02Lux/F1.7, 30IRE, 0Lux IR on Motorized vari-focal 2.7 mm-12 mm, Fixed iris BLC/HLC/DWDR , Gain Control , Noise Reduction 2D NR , Smart IR Max. IR length 60m,IP67, DC12V Built-in mic(-A)		31.350.000
34	DH-HAC-HFW1200TLP		1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6 & 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 40m, Smart IR, IP67, DC12V		13.450.000
35	DH-HAC-HFW1200THP-A		2MP HDCVI IR Bullet Camera 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens (2.8mm, 6mm Optional), <b>Built-in mic</b> HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 80m, Smart IR, IP67, DC12V		15.400.000
36	DH-HAC-HFW1200THP-I4		2MP HDCVI IR Bullet Camera 1/2.7 inch CMOS 1080P@25fps, 720P@25fps, 720@50fps 3.6mm Fixed lens Minimum Illumination:0.02Lux/F1.9 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Smart IR, Eletronic Defog HD and SD output switchable Max. IR length 40m, Smart IR, IP67, DC12V		15.150.000

رد	ت	رد
37	DH-HAC-HFW1200DP-0360B-S5 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P DWDR, Day/Night(ICR), AWB, AGC, HLC, BLC, 2D-DNR HD and SD output switchable, 3.6mm fixed lens Max. IR LEDs length 80m, Smart IR, IP67, DC12V 2MP HDCVI IR Bullet Camera	 18.150.000
38	HAC-HFW1200CMP-0360B 1/2.7 inch Progressive CMOS Max 30fps@2MP, 3.6mm fixed lens CVI/TVI/AHD/CVBS output switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR Max. IR length 30m, Smart IR, IP67, DC12V 2MP HDCVI IR Bullet Camera	 14.300.000
39	HAC-HFW1200CMP-A 1/2.7 inch Progressive CMOS Max 30fps@2MP, 3.6mm fixed lens, <b>Built-in mic</b> CVI/TVI/AHD/CVBS output switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR Max. IR length 30m, Smart IR, IP67, DC12V	 15.400.000
40	HAC-HFW1200CM-IL-A <b>DUAL LITE</b> <b>Full-color</b> 2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera <b>* In order to use the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000004.1.R.220323 or later version.</b> 2 MP Progressive CMOS Sensor 3.6 mm: H: 83°; V: 48°; D: 105° Max. 30 fps@1080p, CVI/CVBS/AHD/TVI switchable DWDR, BLC, HLC, AWB, AGC, 3D DNR, Day/Night Auto(ICR)/Color/B/W, Smart Dual Light, Illumination Distance IR: 20m (65.62 ft) Warm light: 20m (65.62 ft), Super Adapt, Built-in mic, 1 Audio in Min. Illumination 0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on) 12 VDC, IP67, Metal	 16.850.000
41	DH-HAC-HFW1200SP 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR length 30m, Smart IR, IP67, DC12V	 14.400.000
42	DH-HAC-HFW1200TP 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 2.8mm/3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR length 25m, Smart IR, IP67, DC12V	 15.000.000
43	DH-HAC-HFW1200TP-A 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens, <b>Built-in mic</b> HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR length 30m, Smart IR, IP67, DC12V	 15.400.000
44	DH-HAC-HUM3201B <b>STARLIGHT</b> 1/2.8" 2Megapixel CMOS (Starlight), 25/30fps@1080P & @720P 2.8mm fixed lens HD and SD output switchable, Support OSD Menu WDR(120dB), Day/Night(ICR), AWB, AGC, BLC,HLC, 3DNR, DC12V	 18.950.000
45	DH-HAC-B2A21P <b>Cooper Series</b> 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium	 12.000.000
46	DH-HAC-B1A21P <b>Cooper Series</b> 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Plastic	 9.750.000
47	DH-HAC-HDW1509TP-IL-A <b>STARLIGHT</b> <b>Full-color</b> 5MP Smart Dual Illuminators Eyeball Camera Max 25 fps@5MP (16:9 video output). 120 dB true WDR, 3D NR Smart Dual Illuminators, 40 m illumination distance Super Adapt, Built-in MIC. 3.6 mm fixed lens (2.8 mm optional). CVI/CVBS/AHD/TVI switchable. IP67, 12 VDC.	 37.300.000
48	DH-HDW1509TP-A-LED <b>STARLIGHT</b> <b>Full-color</b> 5MP Full-color HDCVI Eyeball Camera Progressive CMOS - Focal Length 2.8 mm Min. Illumination 0.001 Lux/F1.0, 0 Lux warm light on illumination 2 LEDs Distance 40 m <b>Built-in mic</b> , CVI/CVBS/AHD/TVI switchable WDR 120db, BLC, HLC, HLC-Pro, AWB, AGC, 3DNR Privacy Masking, Smart Light, IP67, DC 12V	 31.800.000



49	DH-HAC-HDW1509TLQP-A-LED	 	5MP Full-color HDCVI Quick-to-install Eyeball Camera 25fps@5MP, 25/30fps@4MP/1080P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu 120dB WDR, 3D/2D NR, Day/Night(ICR), AWB, AGC, BLC, HLC 20m illumination distance, Smart IR, IP67, DC12V, <b>Built-in mic</b>		30.250.000
50	DH-HAC-HDW1509TLQP-LED		5MP Full-color HDCVI Quick-to-install Eyeball Camera 25fps@5MP, 25/30fps@4MP/1080P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu 120dB WDR, 3D/2D NR, Day/Night(ICR), AWB, AGC, BLC, HLC 20m illumination distance, Smart IR, IP67, DC12V		27.200.000
51	DH-HAC-HDW1500SLP		5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP/1080P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 20m, Smart IR, IP67, DC12V		15.750.000
52	DH-HAC-HDW1500TRQP-A-0280B-S3		5MP Starlight HDCVI Quick-to-install IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 25/30 fps@5MP, 25/30fps@4MP,1080P@25/30 fps, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR,, Built-in Mic Max. IR LEDs length 20m, Smart IR, IP50, DC12V		18.950.000
53	DH-HAC-HDW1500TRQP-0280B-S3		5MP Starlight HDCVI Quick-to-install IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 25/30 fps@5MP, 25/30fps@4MP,1080P@25/30 fps, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 20m, Smart IR, IP67, DC12V		16.950.000
54	HAC-HDW1500CLQ-IL-A	  	<b>NEW</b> 5MP Smart Dual Light HDCVI Fixed-focal Quick-to-install Eyeball Camera <b>* In order to use the 5MP 16:9 and the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000004.1.R.220323 or later version.</b> 5MP Progressive CMOS Sensor 2.8 mm: H: 106°; V: 56°; D: 125° Max 25 fps@5MP (16:9 video output), CVI/CVBS/AHD/TVI switchable DWDR, BLC, HLC, AWB, AGC, 2D DNR, Day/Night Auto(ICR)/Color/B/W, Smart Dual Light, Illumination Distance IR: 20m (65.62 ft) Warm light: 20m (65.62 ft), Super Adapt, Built-in mic Min. Illumination 0.05 lux@F1.6 (Color, 30 IRE) 0.005 lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on) 12VDC, IP67, Plastic, Quick-to-install		23.000.000
55	HAC-T2A51P		5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP & @1080P (16:9 video output) 3.6mm & 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Support OSD Menu Max. IR length 20m, IP67, DC12V, Casing: Aluminium		17.500.000
56	HAC-T1A51P		5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P (16:9 video output) 3.6mm and 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Support OSD Menu Max. IR length 20m, IP67, DC12V, Casing: Plastic		14.650.000
57	DH-HAC-T2A41P		1/2.7" 4Megapixel CMOS, 25/30fps@4MP,25/30fps@1080P 2.8mm fixed lens, HD and SD output switchable Max. IR length 20m, IP67, DC12V, Casing: Aluminium		15.400.000
58	DH-HAC-T1A41P		1/2.7" 4Megapixel CMOS, 25/30fps@4MP,25/30fps@1080P 2.8mm fixed lens, HD and SD output switchable Max. IR length 20m, DC12V, Casing: Plastic		12.650.000

59	DH-HAC-HDW1239TLP-A-LED	 	<p>2M Full-color Starlight HDCVI Eyeball Camera 1/2.8 inch 2.16 Mega Pixels CMOS Minimum Illumination:0.005Lux/F1.6 Full-color starlight 1080@25fps, 720@25fps, 720@50fps 3.6 mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Smart Light, Electronic Defog HCVI/CVBS/AHD/TVI switchable <b>Built-in Mic</b> 20m LED distance, IP67, DC12V</p>		20.900.000
60	DH-HAC-HDW1230MP		<p>2MP Starlight HDCVI IR Eyeball Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V</p>		13.750.000
61	HAC-HDW1209TLQP-A-LED-0280B	 	<p>2MP Full-color HDCVI Quick-to-install Eyeball Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 2.8mm fixed lens <b>Built-in Mic</b> CVI/CVBS/AHD/TVI Switchable, Support OSD Menu DWDR/BLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V</p>		16.000.000
62	HAC-HDW1209TLQP-LED-0280B	 	<p>2MP Full-color HDCVI Quick-to-install Eyeball Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 2.8mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu DWDR/BLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V</p>		13.900.000
63	DH-HAC-HDBW1200EP		<p>2MP HDCVI IR Dome Camera, 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 2.8mm Fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, IK10, DC12V</p>		15.100.000
64	DH-HAC-HDW1200LP		<p>2MP HDCVI IR Eyeball Camera, 1/2.7" 2Megapixel CMOS Max 30fps@1080P, 2.1mm fixed lens HD and SD output switchable, <b>Built in Mic</b>, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 3m, Smart IR, IP67, DC12V</p>		17.950.000
65	DH-HAC-HDW1200MP		<p>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens HD and SD output switchable, Support OSD Menu Day/Night(ICR), AWB, AGC, BLC, 2D-DNR Max. IR length 30m, Smart IR, IP67, DC12V</p>		12.900.000
66	DH-HAC-HDW1200EMP-A Metal Case		<p>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, <b>Built-in MIC</b> Day/Night(ICR), AWB, AGC, BLC, 2DNR, DWDR 3.6 &amp; 2.8mm fixed lens Max. IR LEDs length 50m, Smart IR, IP67, DC12V</p>		16.000.000
67	HAC-HDW1200TRQP-A-0280B	 	<p>2MP HDCVI Quick-to-install IR Eyeball Camera 1/2.7 inch Progressive CMOS Max 30fps@2MP 2.8mm/3.6mm fixed lens <b>Built in Mic</b> CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto switch by ICR Max. IR length 25m, Smart IR, IP50, DC12V</p>		13.450.000
68	DH-HAC-HDW1200TLP-A		<p>2MP HDCVI IR Eyeball Camera 1/2.7 inch CMOS Max 30fps@1080P 2.8mm Fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR <b>Built-in mic</b> Electronic Defog CVI/CVBS/AHD/TVI switchable Max. IR length 30m, Smart IR, IP67, DC12V</p>		14.200.000

NEW

2MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera  
 \* In order to use the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000004.1.R.220323 or later version.

69 HAC-HDW1200CLQ-IL-A



2 MP Progressive CMOS Sensor 2.8 mm: H: 102°; V: 60°; D: 129°  
 Max. 30 fps@1080p, CVI/CVBS/AHD/TVI switchable  
 DWDR, BLC, HLC, AWB, AGC, 3D DNR, Day/Night Auto(ICR)/Color/B/W, Smart Dual Light, Illumination Distance IR: 20m (65.62 ft) Warm light: 20m (65.62 ft), Super Adapt, Built-in mic, 1 Audio in  
 Min. Illumination 0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on)  
 12VDC, IP67, Plastic, Quick-to-install



15.000.000

70 DH-HAC-T2A21P

Cooper Series

1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P  
 2.8mm fixed lens  
 HD and SD output switchable, Support OSD Menu  
 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR  
 Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium  
 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P  
 2.8mm & 3.6 fixed lens



12.000.000

71 DH-HAC-T1A21P

Cooper Series

HD and SD output switchable, Support OSD Menu  
 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR  
 Max. IR length 20m, Smart IR, Casing: Plastic, DC12V  
 1/2.8" 2Megapixel Exmor R CMOS (Starlight)



9.500.000

72 DH-SD59225I-HC-S2

STARLIGHT

Max 25/30fps @1080P & 20/30/50/60fps @720P Resolution  
 4.8mm ~ 120mm 25x optical zoom  
 WDR (120db), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus  
 Max 400°/s pan speed, 360° endless pan rotation  
 Control over coaxial cable  
 1-channel BNC HDCVI/CVBS output (switchable)  
 Up to 300 presets, 5 auto scan, 8 tour, 5 pattern  
 Built-in 2/1 Alarm in/out, 1 Audio Input, RS485  
 IR Distance up to 150m, IP66, OSD



198.000.000

73 SD59230I-HC

STARLIGHT

2MP 30x Starlight IR PTZ HDCVI Camera, 1/2.8" Exmor R CMOS  
 Max. 25/30fps @1080P(1920x1080) & 50/60fps @720P Resolution  
 4.5mm~135mm 30x optical zoom  
 WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus  
 Max 400°/s pan speed, 360° endless pan rotation  
 HD and SD switchable  
 Up to 300 presets, 5 auto scan, 8 tour, 5 pattern  
 Audio(in/out) 1 / 1 , Built-in 2/1 Alarm in/out  
 IR Distance up to 150m, IP66, OSD



231.000.000

74 DH-SD49225I-HC-LA

STARLIGHT

2MP 25x Starlight IR PTZ HDCVI Camera, 1/2.8" STARVIS CMOS  
 Max. 25/30fps @1080P(1920x1080) & 50/60fps @720P Resolution  
 4.8mm~120mm 25x optical zoom  
 WDR(120dB), Day/Night(ICR), Ultra DNR, HLC, BLC, Auto iris, Auto focus  
 Max 400°/s pan speed, 360° endless pan rotation  
 Up to 300 presets, 5 auto scan, 8 tour, 5 pattern  
 HD and SD switchable, 2/1 Alarm In/Out  
 1CH Audio In, RS485, IR Distance up to 100m, IP66, OSD



185.000.000

75 DH-XVR1A04

Cooper Series

4CH Penta-brid 1080N/720P Real-Time Cooper Recorder  
 H.264 video compression, 4CH: 1/4 Playback  
 Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+1 IP up to 2 MP(20 Mbps)]  
 1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 8 TB  
 HDMI , VGA ,simultaneous video Output  
 2\*USB 2.0, 10/100 Mbps LAN Interface, P2P Support




21.750.000

Wiz Sense AI

76 XVR1B04-I

Cooper Series

4 Channel Penta-brid 1080N/720p Real-time WizSense Ai XVR  
 H.265+/H.265/H.264+/H.264 dual-stream video compression  
 Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+1 IP up to 2MP(20 Mbps),  
 4CH: 1/4 Playback  
 HDMI , VGA ,simultaneous video Output  
 1 SATA port, up to 6 TB capacity  
 2\*USB 2.0, 10/100 Mbps LAN Interface, P2P Support



26.300.000

77 DH-XVR1A08

Cooper Series

8CH Penta-brid 1080N/720P noneReal-Time Cooper Recorder  
 H.264 video compression, 8CH:1/4/9 Playback  
 Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+2 IP up to 5 MP(40 Mbps)]  
 1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 8 TB  
 HDMI , VGA ,simultaneous video Output, 2\*USB 2.0  
 10/100 Mbps LAN Interface, P2P Support



26.750.000



78	XVR1B08-I		<p>8 Channel Penta-brid 1080N/720p Real-time WizSense Ai XVR H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+2 IP up to 6MP(40 Mbps), 4CH: 1/4/9 Playback HDMI , VGA ,simultanous video Output 1 SATA port, up to 6 TB capacity 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification</p>		32.000.000
		Cooper Series			
79	XVR1B08H-I		<p>8 Channels 5M-N/1080p Cooper 1U 1HDD Digital Video Recorder Supports Full-channel AI-Coding , H.265+/H.265 dual-stream Pentabrid (IP+CVI+AHD+TVI+CVBS) - Max 12 channels IP camera inputs Up to 8 channels SMD Plus Human/Vehicle Classification Encoding Capacity : 5M-N@(10 fps); 4M-N/1080p@(15 fps); 1080N@(25/30 fps) 1/4/8/9 Playback , 1 SATA port, up to 16 TB capacity 2*USB 2.0, Audio In/Out : 1/1 , 10/100 Mbps LAN Interface, P2P Support</p>		55.000.000
		Cooper Series			
80	XVR5104HS-I3		<p>New GUI V4.0 Support - 4 Channel Penta-brid 5M-N/1080p None Real-Time WizSense Ai XVR 5M-N; 4M-N; 1080p; 1080N; 720p; 960H; D1; CIF H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 6MP(32 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4ch 1 SATA Port up to 6 TB capacity 2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification, IoT Support</p>		44.250.000
81	XVR5104HS-4KL-I3		<p>New GUI V4.0 Support - 4 Channel Penta-brid 4K WizSense Ai XVR 4K@7fps, 6MP@10fps, 5MP@12fps, 4MP@15fps, 4MN/1080p/720p@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 4+4 IP up to 8MP(64 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4ch 1 SATA Port up to 10 TB capacity 2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification, IoT Support</p>		64.800.000
82	XVR5108HS-4KL(V.2)		<p>New GUI V4.0 Support - 8CH Penta-brid 4K Recorder HDCVI 4K, AHD,5mp, HDTV1 5MP 8+4ch support H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 8MP Tripwire, Intrusion, Face Detection, Smart Search 1/1 Audio In/Out, 1 SATA Port , Up to 8TB 1*HDMI, 1*VGA ,simultanous video Output 2*USB 2.0, 1*10/100 Mbps LAN Interface , P2P Support</p>		92.400.000
83	XVR5108HS-I3		<p>New GUI V4.0 Support - 8 Channel Penta-brid 5M-N/1080p None Real-Time WizSense Ai XVR 5M-N; 4M-N; 1080p; 1080N; 720p; 960H; D1; CIF H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M 8+4 IP up to 6MP(64 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9ch 1 SATA Port up to 10 TB capacity 2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 8ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification. IoT Support</p>		66.650.000

<p>84 XVR5108HS-4KL-I2</p> <p><b>Wiz Sense</b> <b>AI</b></p> <p><b>4K</b></p>	<p>New GUI V4.0 Support - 8 Channel Penta-brid 4K-N/5MP WizSense Ai XVR  4K@7fps, 6MP@10fps, 5MP@12fps, 4K-N/4MP@15fps, 4MN/1080p/720p@25/30fps  H.265+/H.265/H.264+/H.264 dual-stream video compression  Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 8+8 IP up to 8MP(128 Mbps)  HDMI/VGA Simultaneous Video Output, 1ch Audio I/O  Playback 1/4/9ch  1 SATA Port up to 10 TB capacity  1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support  2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to  20,000 Face Library, 8ch SMD Plus, Human/Vehicle Classification, IoT Support</p>	 <p>107.800.000</p>
<p>85 XVR5108HS-4KL-I3</p> <p><b>Wiz Sense</b> <b>AI</b></p>	<p>New GUI V4.0 Support - 8 Channels Penta-brid 4K-N/5MP  Encode Capacity All channel 4K@(7 fps); 6MP@ (10 fps); 5MP@ (12 fps); 4K-N/4 MP/3  MP@ (15 fps); 4M-N/1080P @ (25/30fps);  AI Coding/H.265+/H.265 dual-stream video compression  Supports HDCVI/AHD/TVI/CVBS  Up to 16 channels of IPC access / 128 Mbps  Supports Full-channel AI Coding  Perimeter Protection : 8 channels, 10 IVS for each channel / 2 channels (up to 12 face  images/s) / Face Recognition : 2 channel up to 10 face databases / Full-channel SMD  Plus  Audio Input : 1, RCA (external) 8, BNC (coaxial) / Audio Output 1, RCA  HDD Interface 1 SATA Port, up to 16TB  RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000  DC12V, 2A / Power Consumption Lower than 10 W / Operating Temperature  -10 °C to +55 °C</p>	 <p>107.800.000</p>
<p>86 DH-XVR1B16</p> <p><b>Cooper Series</b></p>	<p>16CH Penta-brid 1080N/720P None Real-Time Cooper Recorder  H.265+/H.265 dual-stream video compression  1st channel 1080N/720P@25fps, others 1080N/720P@15fps  16CH: 1/4/9/16 Playback  Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+2 IP up to 6 MP(64 Mbps)]  1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 6 TB  HDMI , VGA ,simultaneous video Output  2 USB 2 , 10/100 Mbps LAN Interface, P2P Support</p>	 <p>52.800.000</p>
<p>87 XVR1B16-I</p> <p><b>Wiz Sense</b> <b>AI</b></p> <p><b>Cooper Series</b></p>	<p>8 Channel Penta-brid 1080N/720p Real-time WizSense Ai XVR  H.265+/H.265/H.264+/H.264 dual-stream video compression  Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+2 IP up to 6MP(64 Mbps)  4CH: 1/4/9/16 Playback  HDMI/VGA Simultaneous Video Output  1 SATA port, up to 6 TB capacity  2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support  8ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification</p>	 <p>64.750.000</p>
<p>88 XVR5116H-I2</p> <p><b>Wiz Sense</b> <b>AI</b></p>	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P WizSense Ai XVR  5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps  H.265+/H.265/H.264+/H.264 dual-stream video compression  Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+4 IP up to 6MP(128 Mbps)  HDMI/VGA Simultaneous Video Output, 1ch Audio I/O  Playback 1/4/9/16ch  1 SATA Port up to 10 TB capacity  1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support  2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to  10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>	 <p>111.100.000</p>
<p>89 XVR5116HS-S2(V.2)</p>	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P XVR  5MN, 4M-N, 1080P, 1080N, 720P, 960H, D1, HD1, BCIF, CIF, QCIF  H.264+/H.264 dual-stream video compression  Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+8 IP up to 5MP(96 Mbps)  HDMI/VGA Simultaneous Video Output, 1ch Audio I/O  Playback 1/4/9/16ch  1 SATA Port, up to 8TB capacity  1 USB 2.0 , 1 USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support  Tripwire, Intrusion, Face Detection</p>	 <p>95.400.000</p>

<p>90 XVR5116HS-I3</p> 	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P          Encode Capacity All channel 5M-N (10 fps); 4M-N/1080p (15fps)          AI Coding/H.265+/H.265 dual-stream video compression          Supports HDCVI/AHD/TVI/CVBS/IP video inputs          Max 24 channels IP camera, up to 6MP; Max 128Mbps incoming bandwidth          Supports Full-channel AI Coding / 16 channel SMD / 2 channel face recognition          Audio Input : 1, RCA (external) 16, BNC (coaxial) / Audio Output 1, RCA          HDD Interface 1 SATA Port, up to 16TB for a single HDD          RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000          DC12V, 2A / Power Consumption Lower than 12 W / Operating Temperature          -10 °C to +55 °C</p>	 <p>111.100.000</p>
<p>91 XVR5216AN-S2(V.2)</p>	<p>New GUI V4.0 Support - 16CH Penta-brid 5MN/4M-N/1080P Non-real Time ,          1080N/720P Real-Time Recorder, 5MN/4M-N/1080P@15fps , 1080N/720P@25fps          H.264+/H.264 dual-stream video compression          1/4/9/16CH Playback, Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 MP(96          Mbps)]          Support Smart Search and Intelligent Video System          1/1 Audio In/Out, 2 SATA Port , Up to 16 TB          HDMI , VGA , simultaneous video Output, RS485 for PTZ support          2 USB Ports (1 USB 2.0 , 1 USB 3.0)          10/100/1000 Mbps LAN Interface, P2P Support</p>	 <p>123.800.000</p>
<p>92 XVR5216AN-I2</p> 	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P WizSense Ai XVR          5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps          H.265+/H.265/H.264+/H.264 dual-stream video compression          Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+4 IP up to 6MP(128 Mbps)          HDMI/VGA Simultaneous Video Output, 1ch Audio I/O          Playback 1/4/9/16ch          2 SATA Port up to 10 TB capacity each port(20TB Total)          1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support          2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to          10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>	 <p>142.500.000</p>
<p>93 XVR5216AN-I3</p> 	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P          Encode Capacity All channel 5M-N (10 fps); 4M-N/1080p (15fps)          AI Coding/H.265+/H.265 dual-stream video compression          Supports HDCVI/AHD/TVI/CVBS          16+8 channels, each IP Channel up to 6MP          Supports Full-channel AI Coding          Perimeter Protection : 2 channel, 10 IVS for each channel / Face Detection : 6          attributes , 2 channels each channel up to 12 faces / Face Recognition : 2 channel up to          10 face databases / Full-channel SMD Plus          Audio Input : 1, RCA (external) 16, BNC (coaxial) / Audio Output 1, RCA          HDD Interface 2 SATA Port, up to 16TB for a single HDD          RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000          DC12V, 2A / Power Consumption Lower than 12 W / Operating Temperature          -10 °C to +55 °C</p>	 <p>142.500.000</p>
<p>94 XVR5216AN-4KL-I2</p> 	<p>New GUI V4.0 Support - 16 Channel Penta-brid 4KN/5MP WizSense Ai XVR          4K@7fps, 6MP@10fps, 5MN@12fps, 4KN/4MP@15fps, 4MN/2MP/1MP@25/30fps          H.265+/H.265/H.264+/H.264 dual-stream video compression          Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+16 IP up to 8MP(128 Mbps)          HDMI/VGA Simultaneous Video Output, 1ch Audio I/O          Playback 1/4/9/16ch          2 SATA Port up to 10 TB capacity each port(20TB Total)          1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support          2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to          20,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>	 <p>215.800.000</p>

<p>95 DH-XVR5216AN-4KL</p> 	<p>New GUI V4.0 Support - 16 Channel Embedded Processor 16+8 Channel, each channel up to 8M HDCV 4K, 4MP, 1080P@25/30fps, 720P@50/60fps, 720P@25/ Record rate Main stream: 4K(1~7fps);4MP(1~15fps);1080P (1~25/30f) H.264+/H.26 dual-stream video compression Internal HDD 2 SATA Ports, up to 8TB capacity for each IP Camera Input 8+4/16+8 Channel, each channel up to 8 Audio In/Out 1/1, RC - 2 USB Ports (1 USB 2.0 , 1 USB 3), 1*RS485, 1*1000 Mbps</p>	 <p>186.000.000</p>
<p>96 DH-XVR5216AN-4KL-I3</p> 	<p>New GUI V4.0 Support - 16 Channels Penta-brid 4K-N/5MP Encode Capacity All channel 4K@(7fps); 6MP@(10fps); 5MP@(12fps); 4K-N/4MP/3MP@(15fps); 4M-N/1080P(25/30fps); AI Coding; H.265+; H.265; H.264+; H.264 Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 32 channels IP camera inputs, each channel up to 8MP Supports Full-channel AI Coding Perimeter Protection : Advanced Model: 2 channels , General Model: 8 channels ; Face Detection : 2 channels ;Face Recognition : 2 channels , Up to 10 face databases , SMD Plus : 16 channels Audio Input :1-channel RCA , 16-channel BNC 16 / Audio Output 1, RCA HDD Interface 2 SATA Port, up to 16TB for a single HDD RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000 12 VDC, 5A / Power Consumption Lower than 15 W(without HDD) / Operating Temperature-10 °C to +55 °C</p>	 <p>215.800.000</p>
<p>97 DH-XVR5232AN-S2(V.2)</p>	<p>New GUI V4.0 Support - 32CH Penta-brid 1080P Recorder 4M-N/1080P@15fps, 1080N/720P@25fps H.264+/H.264 dual-stream video compression 16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 5 MP(128 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out, 2 SATA Port , Up to 16 TB 1*HDMI, 1*VGA ,simultaneous video Output RS485 for PTZ support, 2*USB(1 USB2.0 , 1 USB3.0) 1*10/100/1000 Mbps LAN Interface, P2P Support</p>	 <p>199.100.000</p>
<p>98 XVR5232AN-I2</p> 	<p>New GUI V4.0 Support - 32 Channel Penta-brid 5M-N/1080P WizSense Ai XVR 5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 32ch IP up to 6MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 2 SATA Port up to 10 TB capacity each port(20TB Total) 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>	 <p>230.500.000</p>
<p>99 XVR5232AN-I3</p> 	<p>New GUI V4.0 Support - 32 Channels Penta-brid 5M-N/1080P Encode Capacity All channels 5M-N@(10fps); 4M-N/1080P@(15fps) AI Coding/H.265+/H.265 dual-stream video compression Supports HDCVI/AHD/TVI/CVBS 32 IP channels, up to 6MP / bandwidth: 128 Mbps Supports 16-channel AI Coding Perimeter Protection : Up to 4 channels 10 IVS for each channel / Face Detection :2 channels (up to 12 face images/s) / Face Recognition : Up to 2 channels, Up to 10 face databases /16 channels SMD Plus) Audio Input : 1, RCA (external) 32, BNC (coaxial) / Audio Output 1, RCA HDD Interface 2 SATA Port, up to 16TB for a single HDD RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000 DC12V, 5A / Power Consumption Lower than 17 W / Operating Temperature -10 °C to +55 °C</p>	 <p>230.500.000</p>

100 XVR5432L-I3

WizSense

AI

32 Channels Penta-brid 5M-N/1080P 4HDDs WizSense Digital Video Recorder  
 H.265+/H.265 dual-stream video compression.  
 Supports 16-channel AI-Coding.  
 Supports HDCVI/AHD/TVI/CVBS/IP video inputs.  
 Max 32 channels IP camera, each channel up to 8MP; 128 Mbps bandwidth.  
 Up to 8 channels video stream (analog channel) perimeter protection.  
 Up to 16 channels video stream (analog channel) SMD plus.  
 Up to 2 channels video stream (analog channel) human face recognition.  
 Perimeter Protection, Face Detection, Face Recognition : Up to 10 face databases with  
 10,000 face images, SMD Plus  
 Multi-screen Display 1/4/8/9/16/25/36  
 IoT & POS functionalities.



379.500.000

101 DH-XVR4232AN-I

WizSense

32 Channels Penta-brid 1080N/720P 1U 2HDDs WizSense Digital Video Recorder  
 Video Compression AI Coding; H.265+; H.265; H.264+; H.264  
 Supports 8-channel AI-Coding.  
 Supports HDCVI/AHD/TVI/CVBS/IP video inputs.  
 Max 16 channels IP camera inputs, each channel up to 6MP; Max 128  
 Mbps incoming bandwidth. Multi-screen Display 1/4/8/9/16/25/36  
 Audio Input 1-channel RCA (external) 32-channel BNC (coaxial audio)  
 Two-way Talk, HDD Interface 2 SATA ports, up to 16 TB  
 Up to 16 channels video stream (analog channel) SMD Plus.  
 Long transmission distance over coax cable.



154.000.000