















رقم	مدل	مشخصات فني	تصوير	قيمت
IP Camera - IR				
1	SM-IP8414M-W 	1/2.8" SONY CMOS Sensor 8MP(20FPS)/3.6 mm fixed Lens/3Stream/H.265+/H.264+ True WDR 120dB /50m IR/0.1 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, defog, Smart IR POE/12VDC/1CH audio input/SD Card Max 256GB /ONVIF/IP67 Metal SMART Functions	 WDR	Hyperlink 108,750,000
2	SM-IP4512HM-W	1/3" CMOS Sensor 4MP(25FPS)/2.8 mm fixed Lens/3Streams/H265+/H264+ True WDR 120DB /30m IR/0.005 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH audio input; 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67(Metal) SMART Functions	 WDR	Hyperlink 43,750,000
3	SM-IP2412HM-WS	1/2.8" CMOS Sensor 2MP(25FPS)/3.6 mm fixed Lens/3Streams/H265+/H264+ True WDR 120dB /Starlight /30m IR/0.005 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH audio input/SD Card Max 256GB/ ONVIF/IP67 Metal SMART Functions	 WDR Starlight	Hyperlink 40,750,000
4	SM-IP2512HM-WS	1/2.8" CMOS Sensor 2MP(25FPS)/2.8 mm fixed Lens/3Streams/H265+/H264+ True WDR 120dB /Starlight /30m IR/0.005 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH audio input and 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67 Metal SMART Functions	 WDR Starlight	Hyperlink 40,750,000
5	SM-IPTZ-4MP-40X/MSFD	1/2.8" progressive scan CMOS Sensor, BSI and NIR++, dual gain, 4MP(25FPS)/ 4.5 ~ 180 mm Motorized Lens/40x Optical Zoom/350m Smart IR/H.265+,H.264+ True WDR 120dB/Starlight 1 Ch input, 1 Ch output Audio/1 Ch input , 1 Ch output Alarm/SD Card Max 256GB/IP66, IK10 Metal/Outdoor/ DC24V 2.5A , PoE+ SMART Functions/ Auto Tracking/ Supports face detection/ target counting	 WDR Starlight Scan Tracking	Hyperlink 5inch 585,000,000
6	SM-IPTZ-4MP-4X/MWSFR	1/2.7" progressive scan CMOS with BSI and NIR+ technology Sensor 4MP(25FPS)/ 2.8-12mm Motorized Lens/4x Optical Zoom/50m IR/H.265+,H.264+ True WDR 120dB/Starlight 1 Ch input, 1 Ch output Audio/built-in Mics & Speaker (8m for voice recording, 30m for audible warnings) / 1 Ch input , 1 Ch output Alarm/SD Card Max 256GB/IP66, IK10 Metal/Outdoor/ DC12V 2A, PoE+ SMART Functions/ Auto Tracking/ Supports face detection and comparison/ Active Deterrence (30m White LED)	 Face Recognition WDR Starlight Scan Tracking	Hyperlink 3inch 186,000,000
7	SM-IPTZ-4MP-4X/MWS	1/2.7" progressive scan CMOS with BSI and NIR+ technology Sensor 4MP(25FPS)/ 2.8-12mm Motorized Lens/4x Optical Zoom/50m IR/H.265+,H.264+ True WDR 120dB/Starlight 1 Ch input, 1 Ch output Audio/built-in Mics & Speaker (8m for voice recording, 30m for audible warnings) / 1 Ch input , 1 Ch output Alarm/SD Card Max 256GB/IP66, IK10 Metal/Outdoor/ DC12V 2A, PoE+ SMART Functions/ Auto Tracking/ Active Deterrence (30m White LED)	 WDR Starlight Scan Tracking	Hyperlink 3inch 160,000,000



8	SM-IP TZ-2MP-15X/MS	1/2.8" progressive scan CMOS, BSI, NIR++/ 2MP(25FPS) 5 ~ 75 mm Motorized Lens/15x Optical Zoom/200m SMART IR/H.265+,H.264+/DWDR /Starlight SD Card Max 256GB/IP66, IK10 Metal /DC12V 3A, ,PoE SMART Functions/ Auto Tracking	 	Hyperlink 227,500,000
---	----------------------------	--	--	--



Light Explorer IP Camera - Color View



9	SM-IP2414CV2-W	1/2.8" CMOS Sensor 2MP(25FPS)/ 3.6mm & 2.8 mm fixed Lens/3Streams/H265+/ H264+/ True WDR 120dB/30- 40m white light view distance/0.002 lux ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/1CH audio input; 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67 Metal SMART Functions	 	Hyperlink 53,750,000
---	-----------------------	--	---	---



10	SM-IP2512CV2-W	1/2.8" CMOS Sensor 2MP(25FPS)/ 2.8 mm fixed Lens/3Streams/H265+/ H264+/ True WDR 120dB/20- 30m white light view distance/0.002 lux ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/1CH audio input; 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67 Metal SMART Functions	 	Hyperlink 47,500,000
----	-----------------------	--	--	---



IP Camera - Dual Light









































11	NEW SM-IPN8512DM-W	1/2.8" SONY CMOS Sensor 8MP(20FPS)/2.8mm fixed Lens/3Streams/H265+/H264+/ True WDR 120dB/0.02 lux/ ICR , Auto day/night switch 30m White light view distance; 30m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC, Defog, ANR, Cloud upgrade, Dual-system backup POE/12VDC/1CH audio input/1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67(Metal) SMART Functions-Support SMD (human / Motor Vehicle)	 	Hyperlink 113,500,000
----	-------------------------------------	---	---	--



















12	NEW SM-IPN6416DM-ZWS	1/2.5" CMOS Sensor 6MP(20FPS)/2.8 -12mm Motorized Lens/3Streams/H265+/H264+/ True WDR 120dB/Starlight/0.008 lux/ ICR , Auto day/night switch 40m White light view distance; 50m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC, ANR, Cloud upgrade POE/12VDC/1CH audio input/1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67(Metal) SMART Functions-Support SMD (human / Motor Vehicle)	 	Hyperlink 121,000,000
----	---------------------------------------	--	--	--

13	SM-IPN6412DM-WS	1/2.5" CMOS Sensor 6MP(20FPS)/3.6mm fixed Lens/3Streams/H265+/H264+/ True WDR 120dB/Starlight/0.008 Lux/ ICR , Auto day/night switch 30m White light view distance; 30m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC, ANR, Cloud upgrade POE/12VDC/1CH audio input/1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67(Metal) SMART Functions-Support SMD (human / Motor Vehicle)	 	Hyperlink 75,000,000
----	------------------------	--	--	---

14	SM-IPN6512DM-WS	1/2.5" CMOS Sensor 6MP(20FPS)/2.8mm fixed Lens/3Streams/H265+/H264+/ True WDR 120dB/Starlight/0.008 Lux/ ICR , Auto day/night switch 30m White light view distance; 30m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC, ANR, Cloud upgrade POE/12VDC/1CH audio input/1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67(Metal) SMART Functions-Support SMD (human / Motor Vehicle)	 	Hyperlink 75,000,000
----	------------------------	--	--	---

15	SM-IPN4410DL	1/3" CMOS Sensor 4MP(25FPS)/3.6mm fixed Lens/2Streams/H265+/H264+/ DWDR /0.09 Lux/ ICR , Auto day/night switch 20m White light view distance; 30m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/1CH built-in MIC/ONVIF/IP67(Metal&Plastic) SMART Functions-Support SMD (available for human)	 	Hyperlink 38,500,000
----	---------------------	--	--	---

16	SM-IPN4510DL	1/3" CMOS Sensor 4MP(25FPS)/2.8mm fixed Lens/2Streams/ H265+/H264+ DWDR /0.09 Lux/ ICR , Auto day/night switch 20m White light view distance; 30m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/ 1CH built-in MIC/ONVIF/IP67 (Metal&Plastic) SMART Functions-Support SMD (available for human)	   	Hyperlink 38,500,000
17	SM-IPN2416DM-VFWS	1/2.8" CMOS Sensor 2MP(25FPS)/2.8 -12mm Varifocal Lens/3Streams/ H265+/H264+ True WDR 120dB/Starlight/0.006 Lux/ ICR , Auto day/night switch 40m White light view distance; 50m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC, ANR, cloud upgrade POE/12VDC/ 1CH audio input/1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67 (Metal) SMART Functions-Support SMD (human / Motor Vehicle)	     	Hyperlink 62,500,000
18	SM-IPN2516DM-VFWS	1/2.8" CMOS Sensor 2MP(25FPS)/2.8 -12mm Varifocal Lens/3Streams/ H265+/H264+ True WDR 120dB/Starlight/0.006 Lux/ ICR , Auto day/night switch 40m White light view distance; 50m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC, ANR, cloud upgrade POE/12VDC/ 1CH audio input/1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67 (Metal) SMART Functions-Support SMD (human / Motor Vehicle)	     	Hyperlink 62,500,000
19	NEW SM-IPN2412DL	1/3" CMOS Sensor 2MP(25FPS)/3.6mm fixed Lens/2Streams/ H265+/H264+ DWDR/0.02 lux/ ICR , Auto day/night switch 20m White light view distance; 30m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/ 1CH built-in MIC/ONVIF/IP67 (Metal) SMART Functions-Support SMD (available for human)	   	Hyperlink 34,750,000
20	SM-IPN2410DL	1/3" CMOS Sensor 2MP(25FPS)/3.6mm fixed Lens/2Streams/ H265+/H264+ DWDR/0.02 Lux/ ICR , Auto day/night switch 20m White light view distance; 30m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/ 1CH built-in MIC/ONVIF/IP67 (Metal&Plastic) SMART Functions-Support SMD (available for human)	   	Hyperlink 32,000,000
21	NEW SM-IPN2512DL	1/3" CMOS Sensor 2MP(25FPS)/2.8mm fixed Lens/2Streams/ H265+/H264+ DWDR /0.02 lux/ ICR , Auto day/night switch 20m White light view distance; 30m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/ 1CH built-in MIC/ONVIF/IP67 (Metal) SMART Functions-Support SMD (available for human)	   	Hyperlink 34,750,000
22	SM-IPN2510DL	1/3" CMOS Sensor 2MP(25FPS)/2.8mm fixed Lens/2Streams/ H265+/H264+ DWDR /0.02 Lux/ ICR , Auto day/night switch 20m White light view distance; 30m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/ 1CH built-in MIC/ONVIF/IP67 (Metal&Plastic) SMART Functions-Support SMD (available for human)	   	Hyperlink 32,000,000
23	SM-IPS2410DL	1/3" CMOS Sensor 2MP(25FPS)/3.6mm fixed Lens/2Streams/ H265+/H264+ DWDR/0.0462 Lux/ ICR , Auto day/night switch Dual light Camera (line Crossing-Intrusion) 20m White light view distance; 20m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC, Defog POE/ 1CH built-in MIC/ONVIF/IP67 (Metal&Plastic) SMART Functions	  	Hyperlink 23,250,000
24	SM-IPS2510DL	1/3" CMOS Sensor 2MP(25FPS)/2.8mm fixed Lens/2Streams/ H265+/H264+ DWDR/0.0462 Lux/ ICR , Auto day/night switch Dual light Camera (line Crossing-Intrusion) 20m White light view distance; 20m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC, Defog POE/ 1CH built-in MIC/ONVIF/IP67 (Metal&Plastic) SMART Functions	  	Hyperlink 23,250,000
NVR				
25	SM-NLS4016	4CH input & Record 6MP @25fps /H.265S ,H.265+ Bandwidth(Input 40Mbps/Output 40Mbps) 4CH IPC Audio/Alarm input/ SATA3.0 x 1, max 10T / HDMI-VGA/USB2.0*2/ P2P/ ONVIF/DHCP/DDNS/ RJ45 100Mbps x 1 SMART Function/Supports face detection/Video Metadata/Perimeter Protection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	Hyperlink 36,250,000

26	SM-NLS4016-4PE	<p>4CH input & Record 6MP@25fps - 4*100M RJ45 PoE ports H.265S ,H.265+ -Bandwidth(Input 40Mbps/Output 40Mbps) 4CH IPC Audio input/SATA3.0 x 1, max 10T / HDMI-VGA/USB2.0*2/P2P/ ONVIF/DHCP/DDNS/ RJ45 100Mbps x 1 SMART Function/Supports face detection/Video Metadata/Perimeter Protection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	 VCA 	Hyperlink 56,000,000
27	SM-NLS8016	<p>8CH input & Record 6MP@25fps /H.265S ,H.265+ / Bandwidth(Input 64Mbps/Output 64Mbps) 8CH IPC Audio/Alarm input/SATA3.0 x 1, max 10T / HDMI-VGA/USB2.0*2/P2P/ ONVIF/DHCP/DDNS/ RJ45 100Mbps x 1 SMART Function/Supports face detection/Video Metadata/Perimeter Protection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	 VCA 	Hyperlink 42,000,000
28	SM-NLS1616	<p>16CH input & Record 6MP@25fps /H.265S ,H.265+ / Bandwidth(Input 64Mbps/Output 64Mbps) 16CH IPC Audio/Alarm input/SATA3.0 x 1, max 10T / HDMI-VGA/USB2.0*2/P2P/ ONVIF/DHCP/DDNS/ RJ45 100Mbps x 1 SMART Function/Supports face detection/Video Metadata/Perimeter Protection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	 VCA 	Hyperlink 47,500,000
29	SM-N2M818	<p>NEW 8CH input & Record 8MP(25FPS)/H.265S ,H.265+ / Bandwidth (Input80Mbps/Output 80Mbps) 8CH IPC Audio/Alarm input/SATA3.0 x 1, max 10T / HDMI 4K-VGA/ 2 RCA AUDIO IN & OUT / USB2.0*2 /P2P/ONVIF/DHCP/DDNS RJ45 10-100-1000M SMART Function/ Supports face detection/Video Metadata/ Perimeter Protection/ Support fisheye (Web Client and mobile APP) قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	 VCA 	Hyperlink 74,500,000
30	SM-N2M1618	<p>16CH input & Record 8MP(25FPS)/H.265S ,H.265+ / Bandwidth (Input160Mbps/Output 160Mbps) 16CH IPC Audio/Alarm input/SATA3.0 x 1, max 10T / HDMI 4K-VGA/ 2 RCA AUDIO IN & OUT / USB2.0*2 /P2P/ONVIF/DHCP/DDNS/ RJ45 10-100-1000M SMART Function/Supports face detection/Video Metadata/Perimeter Protection/Support fisheye (Web Client and mobile APP) قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	 VCA 	Hyperlink 78,500,000
31	SM-N2M1628	<p>16CH input & Record 8MP(25FPS)/H.265S ,H.265+ / Bandwidth (Input160Mbps/Output 160Mbps) 16CH IPC Audio/Alarm input/4 CH local alarm input- 1Ch Output/SATA3.0 x 2, max 10T per HDD/HDMI 4K-VGA 2 RCA AUDIO IN & OUT/RS485*2/ USB2.0*2 /P2P/ONVIF/DHCP/DDNS/ RJ45 10-100-1000M SMART Function/Supports face detection/Video Metadata/Perimeter Protection/Support fisheye (Web Client and mobile APP) قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	 VCA 	Hyperlink 99,500,000
32	SM-N2H32212-AI	<p>NEW 32CH input & Record 12MP(20FPS)/ H.265S/H.265+/H264/ Bandwidth(Input 320Mbps/Output 256Mbps) 32CH IPC Audio input/8Ch local Alarm input - 4Ch Output/2HDD*10TB HDMI*2(4K & 1080P)-VGA/2 RCA AUDIO IN & OUT/RS485*2/ USB2.0*2 & USB3.0*1/P2P/ONVIF/DHCP/DDNS RJ45 10-100-1000M * 2 AI Function-Supports face detection and comparison (32CH - AI by IPC / 2CH (2MP) - AI by Device) / License plate recognition/ Video Metadata/Support fisheye (NVR/ Web Client and mobile APP) قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	 Deep Learning Algorithm  VCA  Face Recognition   License plate recognition  Metadata	Hyperlink 187,500,000

کلیه محصولات لیست با گارانتی شرکت سیماران می باشند