



































































































مدل	مشخصات فنی	تصویر	قیمت (ریال)
1 AC-DH1050-E	1/2.5" CMOS Sensor, 5.0Megapixel 3.6mm Fixed Lens 2608 (H) × 1952(V) Resolution DWRD, 3DNR, AWB, BLC 40~45m IR Length, 24 SMD LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		12,450,000
2 AC-DH1020-SL	1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm Fixed Lens 1920 (H) × 1080 (V) Resolution DWRD, 3DNR, AWB, BLC 40~45m IR Length, 24 SMD LED OSD Menu by UTC (output 4-in-1) IP66, Metal Case		10,450,000
3 AC-DH2220-EL	1/2.9" CMOS Sensor, 2.0Megapixel 3.6mm Fixed Lens 1920 (H) × 1080 (V) Resolution DWRD, 3DNR, AWB, BLC 40~50m IR Length, EXIR LED OSD Menu by UTC (output 4-in-1)		7,450,000
4 AC-DH2220-SL	1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm Fixed Lens 1920 (H) × 1080 (V) Resolution DWRD, 3DNR, AWB, BLC 40~50m IR Length, EXIR LED OSD Menu by UTC (output 4-in-1)		7,500,000
5 AC-DH2220-SLA	 HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm Fixed Lens 1920 (H) × 1080 (V) Resolution DWRD, 3DNR, AWB, BLC 40~50m IR Length, EXIR LED Built in MIC OSD Menu by UTC (output 4-in-1)		9,050,000
6 AC-DH2220-DSCA/28	  HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0Megapixel 2.8mm Fixed Lens 1920(H) × 1080(V) Resolution DWRD, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 2 Dual LED OSD Menu by UTC(output 4-in-1) Built in MIC - Support Audio in TVI & CVI Mode (Compatible With Dahua Recorder)		11,900,000
7 AC-DH2220-DSA/28	  HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0Megapixel 2.8mm Fixed Lens 1920 (H) × 1080 (V) Resolution DWRD, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 2 Dual LED Built in MIC OSD Menu by UTC (output 4-in-1)		11,900,000
8 AC-DH2220-DSA/36	  HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm Fixed Lens 1920 (H) × 1080 (V) Resolution DWRD, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 2 Dual LED Built in MIC OSD Menu by UTC (output 4-in-1)		11,900,000
9 AC-DH2320-EL	1/2.9" CMOS Sensor, 2.0Megapixel 3.6mm Fixed Lens 1920 (H) × 1080 (V) Resolution DWRD, 3DNR, AWB, BLC 30m IR Length, 24 LED OSD Menu by UTC (output 4-in-1) IP66, Metal Case		9,650,000
10 AC-DH2320-WS	 1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed Lens 1920(H) × 1080(V) Resolution DWRD, 3DNR, AWB, BLC 25~30m Warmlight Length, 2 Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		12,050,000

مدل	مشخصات فنی	تصویر	قیمت (ریال)
11 AC-DH2420-WS 	1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed Lens 1920(H) × 1080(V) Resolution DWRD, 3DNR, AWB, BLC 30m Warmlight Length, 2 Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal-Plastic Case		11,350,000
12 AC-DH2520-DSA 	HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0Megapixel 2.8mm F1.2 Starlight Fixed Lens 1920(H) × 1080(V) Resolution DWRD, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 2 Dual LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Ball		13,600,000
13 AC-DH2550-DSA 	HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0Megapixel 3.6mm F1.2 Starlight Fixed Lens 2560(H) × 1920(V) Resolution DWRD, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 2 Dual LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Ball		16,300,000
14 AC-DH2620-WSA 	HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0Megapixel 2.8mm F1.2 Starlight Fixed Lens 1920(H) × 1080(V) Resolution DWRD, 3DNR, AWB, BLC 40m Warmlight, 6 Power LED OSD Menu by UTC(output 4-in-1) Built in MIC		11,900,000
15 AC-DH2620-WSCA 	HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0Megapixel 2.8mm F1.2 Starlight Fixed Lens 1920(H) × 1080(V) Resolution DWRD, 3DNR, AWB, BLC 40m Warmlight, 6 Power LED OSD Menu by UTC(output 4-in-1) Built in MIC - Support Audio in TVI & CVI Mode (Compatible With Dahua Recorder)		11,900,000
16 AC-DH2650-WSA 	HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0Megapixel 2.8mm F1.2 Starlight Fixed Lens 2560(H) × 1920(V) Resolution DWRD, 3DNR, AWB, BLC 40m Warmlight, 6 Power LED OSD Menu by UTC(output 4-in-1) Built in MIC		14,640,000
17 AC-DH2850-DSA 	HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0Megapixel 2.8mm F1.2 Starlight Fixed Lens 2560(H) × 1920(V) Resolution DWRD, 3DNR, AWB, BLC 40m Warmlight - 50m IR Length, 4 Dual LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Ball		16,750,000
18 AC-DH2920-DSCA 	HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0Megapixel 2.8mm F1.2 Starlight Fixed Lens 1920(H) × 1080(V) Resolution DWRD, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length - 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC - Support Audio in TVI & CVI Mode (Compatible With Dahua Recorder) IP67, Metal Ball, Easy Installation		14,200,000
19 AC-DH2920-DSA 	HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0Megapixel 2.8mm F1.2 Starlight Fixed Lens 1920(H) × 1080(V) Resolution DWRD, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length - 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP67, Metal Ball, Easy Installation		14,200,000
20 AC-DH2950-DSA 	HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0Megapixel 2.8mm F1.2 Starlight Fixed Lens 2560(H) × 1920(V) Resolution DWRD, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length - 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP67, Metal Ball, Easy Installation		17,250,000

مدل	مشخصات فنی	تصویر	قیمت (ریال)
21 AC-DH2920-WSCA	 <p>HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0Megapixel 2.8mm F1.2 Starlight Fixed Lens 1920(H) × 1080(V) Resolution DWDR, 3DNR, AWB, BLC 30m Warmlight - 3 EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC, Support Audio In TVI &amp; CVI Mode (Compatibe With Dahua Recorder) IP67, Metal Ball, Easy Installation</p>	 	13,450,000
22 AC-DH2950-WSA	 <p>HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0Megapixel 2.8mm F1.2 Starlight Fixed Lens 2560(H) × 1920(V) Resolution DWDR, 3DNR, AWB, BLC 30m Warmlight - 3 EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP67, Metal Ball, Easy Installation</p>	 	16,600,000
23 AC-BH4620-SL	<p>1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm 3.0MegaPixel Fixed Lens 1920 (H) × 1080 (V) Resolution DWDR, 3DNR, AWB, BLC 30m IR Length, SMD LED OSD Menu by UTC (output 4-in-1) IP66, Plastic Case</p>	 	8,400,000
24 AC-BH4920-SL	<p>1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm 3.0MegaPixel Fixed Lens 1920 (H) × 1080 (V) Resolution DWDR, 3DNR, AWB, BLC 35m IR Length, 6 Mini Array OSD Menu by UTC (output 4-in-1) IP66, Metal Case</p>		9,700,000
25 AC-BH6920-WS	 <p>1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed Lens 1920(H) × 1080(V) Resolution DWDR, 3DNR, AWB, BLC 40m Warmlight - 4 EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case</p>		13,200,000
26 AC-BH6950-WSA	  <p>HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0Megapixel 3.6mm F1.2 Starlight Fixed Lens 2560(H) × 1920(V) Resolution DWDR, 3DNR, AWB, BLC 40m Warmlight - 4 EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case</p>		17,000,000
27 AC-BH6920-DS	 <p>1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed Lens 1920(H) × 1080(V) Resolution DWDR, 3DNR, AWB, BLC 40m Warmlight- 60m IR Length - 4 Dual EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case</p>		13,850,000
28 AC-BH6950-DSA	  <p>HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0Megapixel 3.6mm F1.2 Starlight Fixed Lens 2560(H) × 1920(V) Resolution DWDR, 3DNR, AWB, BLC 40m Warmlight - 60m IR Length - 4 Dual EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case</p>		17,600,000
29 AC-BH6950-DS	 <p>HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0Megapixel 3.6mm F1.2 Starlight Fixed Lens 2560(H) × 1920(V) Resolution DWDR, 3DNR, AWB, BLC 40m Warmlight - 60m IR Length - 4 Dual EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case</p>		17,150,000
30 AC-BH5920-WS	 <p>1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed Lens 1920(H) × 1080(V) Resolution DWDR, 3DNR, AWB, BLC 30m Warmlight Length - 3 EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case</p>		12,450,000

مدل	مشخصات فنی	تصویر	قیمت (ریال)
31 AC-BH5950-WSA	 <p>HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0Megapixel 3.6mm F1.2 Starlight Fixed Lens 2560(H) × 1920(V) Resolution DWDR, 3DNR, AWB, BLC 30m Warmlight Length - 3 EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case</p>		16,200,000
32 AC-BH5950-DSA	 <p>HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0Megapixel 3.6mm F1.2 Starlight Fixed Lens 2560(H) × 1920(V) Resolution DWDR, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case</p>		16,850,000
33 AC-BH5950-DS	 <p>HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0Megapixel 3.6mm F1.2 Starlight Fixed Lens 2560(H) × 1920(V) Resolution DWDR, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case</p>		16,350,000
34 AC-BH5820-DS	 <p>1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed Lens 1920(H) × 1080(V) Resolution DWDR, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case</p>		13,200,000
35 AC-BH5850-DSA	 <p>HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0Megapixel 3.6mm F1.2 Starlight Fixed Lens 2560(H) × 1920(V) Resolution DWDR, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case</p>		17,000,000
36 AC-BH5850-WSA	 <p>HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0Megapixel 3.6mm F1.2 Starlight Fixed Lens 2560(H) × 1920(V) Resolution DWDR, 3DNR, AWB, BLC 30m Warmlight, 3 EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case</p>		16,350,000
37 AC-BH5820-WS/28	 <p>1/2.9" Starlight CMOS Sensor, 2.0Megapixel 2.8mm F1.2 Starlight Fixed lens 1920(H) × 1080(V) Resolution DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 3 EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case</p>	 	13,200,000
38 AC-BH5820-WS	 <p>1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed lens 1920(H) × 1080(V) Resolution DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 3 EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case</p>		13,200,000
39 AC-BH5850-WS	 <p>1/2.5" Starlight CMOS Sensor, 5.0Megapixel 3.6mm F1.2 Starlight Fixed lens 3072(H) × 1728(V) Resolution, 16:9 DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 3 EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case</p>		15,200,000
40 AC-BH5320-SL	 <p>1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed lens 1920(H) × 1080(V) Resolution DWDR, 3DNR, AWB, BLC 35m IR Length, EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case</p>		9,450,000

مدل	مشخصات فنی	تصویر	قیمت (ریال)
41 STARLIGHT AC-BH5420-S	1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed lens 1920(H) × 1080(V) Resolution DWRD, 3DNR, AWB, BLC 30~35m IR Length, EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		10,400,000
42 STARLIGHT AC-BH5450-S	1/2.5" Starlight CMOS Sensor, 5.0Megapixel 3.6mm F1.2 Starlight Fixed lens 3072(H) × 1728(V) Resolution, 16:9 DWRD, 3DNR, AWB, BLC 30~35m IR Length, EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		13,350,000
43 COLOR AC-BH5520-WS	1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed lens 1920(H) × 1080(V) Resolution DWRD, 3DNR, AWB, BLC 25~30m Warmlight Length, EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		12,550,000
44 COLOR AC-BH5550-WS	1/2.5" Starlight CMOS Sensor, 5.0Megapixel 3.6mm F1.2 Starlight Fixed lens 3072(H) × 1728(V) Resolution, 16:9 DWRD, 3DNR, AWB, BLC 25~30m Warmlight Length, EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		15,100,000
45 STARLIGHT AC-BH5520-S	1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed lens 1920(H) × 1080(V) Resolution DWRD, 3DNR, AWB, BLC 40m IR Length, EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		10,750,000
46 AC-BH5520-EL	1/2.9" CMOS Sensor, 2.0Megapixel 3.6mm Fixed lens 1920 (H) × 1080 (V) Resolution DWRD, 3DNR, AWB, BLC 40m IR Length, EXIR LED OSD Menu by UTC (output 4-in-1) IP66, Metal Case		10,100,000
47 AC-BH5550-E	1/2.5" CMOS Sensor, 5.0Megapixel 3.6mm Fixed lens 2608 (H) × 1952(V) Resolution DWRD, 3DNR, AWB, BLC 40m IR Length, EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		13,400,000
48 COLOR AC-BH5620-WS	1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed lens 1920(H) × 1080(V) Resolution DWRD, 3DNR, AWB, BLC 30m Warmlight Length, 4 Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		12,050,000
49 COLOR AC-BH5650-WS	1/2.5" Starlight CMOS Sensor, 5.0Megapixel 3.6mm F1.2 Starlight Fixed lens 3072(H) × 1728(V) Resolution, 16:9 DWRD, 3DNR, AWB, BLC 30m Warmlight Length, 4 Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		14,600,000
50 COLOR AC-BH7220-WS	1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed lens 1920(H) × 1080(V) Resolution DWRD, 3DNR, AWB, BLC 50m Warmlight Length, 4 High Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		15,200,000

مدل	مشخصات فنی	تصویر	قیمت (ریال)
51 AC-BH7250-WS	<p>1/2.8" Starlight CMOS Sensor, 5.0Megapixel 3.6mm F1.2 Starlight Fixed lens 2560(H) × 1920(V) Resolution DWDR, 3DNR, AWB, BLC 50m Warmlight Length, 4 High Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case</p>		17,750,000
52 AC-BH7220-S	<p>1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed lens 1920(H) × 1080(V) Resolution DWDR, 3DNR, AWB, BLC 70~80m IR Length, High Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case</p>		12,950,000
53 AC-BH7250-S	<p>1/2.5" Starlight CMOS Sensor, 5.0Megapixel 3.6mm F1.2 Starlight Fixed lens 3072(H) × 1728(V) Resolution, 16:9 DWDR, 3DNR, AWB, BLC 70~80m IR Length, High Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case</p>		16,250,000
54 AC-BH7450-DS	<p>1/2.8" Starlight CMOS Sensor, 5.0Megapixel 3.6mm F1.2 Starlight Fixed lens 2560(H) × 1920(V) Resolution DWDR, 3DNR, AWB, BLC 50m Warmlight- 60m IR Length - 4 Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case</p>		18,850,000
55 AC-BH7420-S	<p>1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed lens 1920(H) × 1080(V) Resolution DWDR, 3DNR, AWB, BLC 70~80m IR Length, High Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case</p>		15,350,000
56 AC-BH7450-S	<p>1/2.5" Starlight CMOS Sensor, 5.0Megapixel 3.6mm F1.2 Starlight Fixed lens 3072(H) × 1728(V) Resolution, 16:9 DWDR, 3DNR, AWB, BLC 70~80m IR Length, High Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case</p>		17,000,000
57 FARA AI ALARM BOX	<p>3 Output Relay Box 1 Output With 12VDC 1 RJ45 Web Management Interface Compatible With Z Series XVR 12VDC Input (Without Adaptor)</p> <p>این محصول به وسیله کابل شبکه به رکوردرهای سری زد متصل شده و با تعریف و پیاده سازی سناریوهای مختلف از طریق رکوردر و منوی خود محصول می توان از قابلیت های تشخیص انسان و خودروی دوربین و رکوردر در جهت فعال سازی خروجی محصول استفاده نمود تا خروجی تجهیزات از قبیل آژیر، تلفن کننده، فرمان به دزدگیر و سایر تجهیزات فرمان پذیر را فعال کرد و از دوربین ها به عنوان دتکتور محیطی با هوش مصنوعی و دقت بسیار بالا استفاده نمود</p>	<p><b>NEW</b></p> 	1,520,000
58 AAD-7104XF-A1	<p>4CH AHD H.265 5MP-Lite XVR 4CH AHD Camera(HD Mode), 16CH 5MP IP Camera (IP Mode) Preview Capacity: 4*(5MP-Lite@20/4MP-Lite@25/1080P@25)fps Code Capacity: 4*(5MP-Lite@12/4MP-Lite@17/1080P@18/1080P-Lite@25)fps 4CH Playback Support AOC (Audio Over Coaxial For All Channel) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Output 1 SATA HDD Up to 8TB 1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod Mobile APP &amp; CMS PC Software, Internal cloud Server</p>		27,250,000
59 AAD-5104ZF-A1	<p>4CH H.265 1080P-Lite XVR Preview Capacity: 4*(1080P-Lite@25)fps Code Capacity: 4*(1080P-Lite@24)fps 2CH Playback Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod FARA VIEW App - Adaptive Iran &amp; International Servers</p>		24,850,000


مدل	مشخصات فنی	تصویر	قیمت (ریال)
60	<p><b>SMD</b> </p> <p>4CH H.265 5MP-Lite XVR 4CH Camera + 1CH IP Camera Preview Capacity: 4*(5MP-Lite@20)fps Code Capacity: 4*(5MP-Lite@12/4MP-Lite@17/1080P@15/1080P-Lite@25)fps 4CH Playback Support SMD (Human/Vehicle Classification For 4CH) Support 1CH Face Detection (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p>		29,900,000
61	<p><b>SMD</b> </p> <p>4CH H.265 5MP-Lite XVR 4CH Camera + 1CH IP Camera Preview Capacity: 4*(5MP-Lite@20)fps Code Capacity: 4*(5MP-Lite@12/4MP-Lite@17/1080P@15/1080P-Lite@25)fps 4CH Playback Support SMD (Human/Vehicle Classification For 4CH) Support Face Detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI 1080P &amp; VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p>		29,900,000
62	<p><b>SMD</b> </p> <p>4CH H.265 Real 5MP XVR 4CH Camera (Analog &amp; IP) Preview Capacity: 4*(5MP@12)fps Code Capacity: 4*(5MP@12/4MP@15/1080P@25)fps 4CH Playback Support SMD (Human/Vehicle Classification For 4CH) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI 4K &amp; VGA Video Simultaneous Output - Analog Video Output (BNC) 1 SATA HDD Up to 10TB 4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p>		42,450,000
63	<p><b>SMD</b> </p> <p>4CH H.265 Real 5MP XVR 4CH Camera (Analog &amp; IP) Preview Capacity: 4*(5MP@12)fps Code Capacity: 4*(5MP@12/4MP@15/1080P@25)fps 4CH Playback Support SMD (Human/Vehicle Classification For 4CH) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI 4K &amp; VGA Video Simultaneous Output - Analog Video Output (BNC) 1 SATA HDD Up to 10TB 4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p>		42,450,000
64	<p><b>SMD</b>  <b>HISILICON</b> NEW AI Chipset</p> <p>4CH H.265 4K-Lite &amp; Real 5MP XVR 4CH Camera + 2CH IP Camera Preview Capacity: 4*(8MP-Lite@15/5MP@12)fps Code Capacity: 4*(8MP-Lite@15/5MP@12/4MP@16/1080P@25)fps 4CH Playback (2CH@15fps + 2CH@1fps) Support SMD (Human/Vehicle Classification For 4CH) Support Face Detection Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI 4K &amp; VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p>		43,850,000
65	<p>4CH AHD H.265 5MP-Lite XVR 4CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode) Preview Capacity:4*(5MP-Lite@20/4MP-Lite@25/1080P@25)fps Code Capacity: 4*(5MP-Lite@8/4MP-Lite@15/1080P@18/1080P-Lite@25)fps 4CH Playback Support real-time Face Detection, Face list, Face playback Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Output 1 SATA HDD Up to 8TB 1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support , IOS-Andriod Mobile APP &amp; CMS PC Software</p>		29,900,000
66	<p></p> <p>8CH AHD H.265 5MP-Lite XVR 8CH AHD Camera(HD Mode), 16CH 5MP IP Camera (IP Mode) Preview Capacity: 8*(5MP-Lite@20/4MP-Lite@25/1080P-Lite@25)fps Code Capacity: 8*(5MP-Lite@5/4MP-Lite@8/1080P-Lite@15)fps 8CH Playback Support AOC (Audio Over Coaxial For All Channel) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Output 1 SATA HDD Up to 8TB 1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod Mobile APP &amp; CMS PC Software, Internal cloud Server</p>		34,200,000



مدل	مشخصات فنی	تصویر	قیمت (ریال)
67	<p><b>SMD</b></p> <p>8CH H.265 5MP-Lite XVR 8CH Camera + 2CH IP Camera Preview Capacity: 8*(5MP-Lite@12)fps Code Capacity: 8*(5MP-Lite@6/4MP-Lite@8/1080P-Lite@16)fps 8CH Playback Support SMD (Human/Vehicle Classification For 8CH) Support 1CH Face Detection (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran &amp; International Servers</p>		39,000,000
68	<p><b>SMD</b></p> <p>8CH H.265 5MP-Lite XVR 8CH Camera + 2CH IP Camera Preview Capacity: 8*(5MP-Lite@12)fps Code Capacity: 8*(5MP-Lite@6/4MP-Lite@8/1080P-Lite@16)fps 8CH Playback Support SMD (Human/Vehicle Classification For 8CH) Support 1CH Face Detection (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran &amp; International Servers</p>		39,000,000
69	<p><b>SMD</b></p> <p>8CH H.265 5MP-Lite XVR 8CH Camera + 2CH IP Camera Preview Capacity: 8*(5MP-Lite@12)fps Code Capacity: 8*(5MP-Lite@12/1080P-Lite@25)fps 8CH Playback Support SMD (Human/Vehicle Classification For 8CH) Support 1CH Face Detection Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran &amp; International Servers</p> <p><b>New Ultra Model</b></p>	<p><b>NEW</b></p> 	39,000,000
70	<p><b>SMD</b></p> <p>8CH H.265 4K-Lite &amp; Real 5MP XVR 8CH Camera (Analog &amp; IP) Preview Capacity: 8*(4K-Lite@15/5MP@12)fps Code Capacity: 8*(4K-Lite@9/5MP@8/4MP@10/1080P@20)fps 8CH Playback Support SMD (Human/Vehicle Classification For 8CH) Support 1CH Face Detection (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI 4K &amp; VGA Video Simultaneous Output - Analog Video Output (BNC) 2 SATA HDD Up to 10TB For each port (Change Adaptor to 12V/5A) 4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p>		62,250,000
71	<p><b>SMD</b></p> <p>8CH H.265 4K-Lite &amp; Real 5MP XVR 8CH Camera (Analog &amp; IP) Preview Capacity: 8*(4K-Lite@15/5MP@12)fps Code Capacity: 8*(4K-Lite@9/5MP@8/4MP@10/1080P@20)fps 8CH Playback Support SMD (Human/Vehicle Classification For 8CH) Support 1CH Face Detection (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI 4K &amp; VGA Video Simultaneous Output - Analog Video Output (BNC) 1 SATA HDD Up to 10TB (Change Adaptor to 12V/5A) 4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p>		62,250,000
72	<p><b>SMD</b> <b>HISILICON</b> <b>NEW AI Chipset</b></p> <p>8CH H.265 4K-Lite &amp; Real 5MP XVR 8CH Camera + 4CH IP Camera Preview Capacity: 8*(4K-Lite@15/5MP@12)fps Code Capacity: 8*(4K-Lite@9/5MP@8/1080P@20)fps 8CH Playback Support SMD (Human/Vehicle Classification For 8CH) Support Face Detection Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI 4K &amp; VGA Video Simultaneous Output - Analog Video Output (BNC) 1 SATA HDD Up to 10TB 4/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p>	<p><b>NEW</b></p> 	62,250,000
73	<p>8CH AHD H.265 5MP-Lite XVR 8CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode) Preview Capacity:8*(5MP-Lite@12/4MP-Lite@15/1080P-Lite@25)fps Code Capacity:8*(5MP-Lite@6/4MP-Lite@8/1080P@8/1080P-Lite@15)fps 8CH Playback:4ch main stream/8ch sub-stream Support real-time Face Detection, Face list, Face playback Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Output 1 SATA HDD Up to 6TB 1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod Mobile APP &amp; CMS PC Software</p>		39,450,000



مدل	مشخصات فنی	تصویر	قیمت (ریال)
74	<p>8CH AHD H.265 5MP-Lite XVR 8CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode) Preview Capacity:8*(5MP-Lite@12/4MP-Lite@15/1080P-Lite@25)fps Code Capacity:8*(5MP-Lite@6/4MP-Lite@8/1080P@8/1080P-Lite@15)fps 8CH Playback:4ch main stream/8ch sub-stream Support real-time Face Detection, Face list, Face playback Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Output 1 SATA HDD Up to 6TB 1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod Mobile APP &amp; CMS PC Software</p>		40,000,000
75	<p>16CH H.265 5MP-Lite XVR 16CH Camera + 4CH IP Camera Preview Capacity:16*(5MP-Lite@12)fps Code Capacity:16*(5MP-Lite@6/4MP-Lite@8/1080P-Lite@16)fps 16CH Playback Support SMD (Human/Vehicle Classification For 16CH) Support 1CH Face Detection (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC in TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Simultaneous Output 2 SATA HDD Up to 10TB for each port 1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran &amp; International Servers</p>		67,700,000
76	<p>16CH H.265 5MP-Lite XVR 16CH Camera + 4CH IP Camera Preview Capacity:16*(5MP-Lite@12)fps Code Capacity:16*(5MP-Lite@6/4MP-Lite@8/1080P-Lite@16)fps 16CH Playback Support SMD (Human/Vehicle Classification For 16CH) Support 1CH Face Detection (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC in TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran &amp; International Servers</p>		66,800,000
77	<p><b>SMD</b> <b>HISILICON</b> <b>NEW AI Chipset</b></p> <p>8CH H.265 5MP-Lite XVR 8CH Camera + 4CH IP Camera Preview Capacity: 8*(5MP-Lite@20)fps Code Capacity: 8*(5MP-Lite@12/1080P@15)fps 8CH Playback (4CH@12fps + 4CH@11fps) Support SMD (Human/Vehicle Classification For 8CH) Support 1CH Face Detection Support AOC in TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 4/1 CH Audio In/Out, 2*USB - 1*10/100 Mbps LAN Interface P2P support, Onvif, IOS-Andriod FARA VIEW App - Adaptive Iran &amp; International Servers</p>		44,200,000
78	<p><b>SMD</b> <b>HISILICON</b> <b>NEW AI Chipset</b></p> <p>16CH H.265 4K-Lite &amp; Real 5MP XVR 16CH Camera + 4CH IP Camera Preview Capacity: 16*(4K-Lite@15/5MP@12)fps Code Capacity: 16*(4K-Lite@9/5MP@8/1080P@20)fps 16CH Playback Support SMD (Human/Vehicle Classification For 16CH) Support 1CH Face Detection Support AOC in TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI 4K &amp; VGA Video Simultaneous Output - Analog Video Output (BNC) 1 SATA HDD Up to 10TB 4/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran &amp; International Servers</p>		94,300,000
79	<p><b>SMD</b> <b>HISILICON</b> <b>NEW AI Chipset</b></p> <p>32CH H.265 4K-Lite &amp; Real 5MP XVR 32CH Camera (Analog &amp; IP) Preview Capacity: 32*(4K-Lite@15/5MP@12)fps Code Capacity: 32*(4K-Lite@7/5MP@6/1080P@15)fps 16CH Playback Support SMD (Human/Vehicle Classification For 16CH) Support Face Detection Support AOC in TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI 4K &amp; VGA Video Simultaneous Output - Analog Video Output (BNC) 2 SATA HDD Each Up to 10TB 4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran &amp; International Servers</p>		206,850,000
80	<p>16CH AHD H.265 5MP-Lite XVR 16CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode) Preview Capacity:16*(5MP-Lite@12/4MP-Lite@15/1080P-Lite@25)fps Code Capacity:16*(5MP-Lite@6/4MP-Lite@8/1080P@8/1080P-Lite@15)fps 16CH Playback Support real-time Face Detection, Face list and Face playback Pentabrid (Analog,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Output 2 SATA HDD Up to 6TB for each port 4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod Mobile APP &amp; CMS PC Software</p>		67,700,000

مدل	مشخصات فنی	تصویر	قیمت (ریال)
81 AAD-9216X-A2	<p><b>AI</b></p> <p>16CH AHD H.265 8MP-Lite XVR            16CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode)            Preview Capacity:16*(8MP-Lite@15/5MP@12/5MP-Lite@20/1080P@25)fps            Code Capacity:16*(8MP-Lite@8/5MP@6/5MP-Lite@12/1080P@15)fps            16CH Playback</p> <p>Support real-time Face Detection, Face list and Face playback            AI Functions: Intrusion , Line crossing            Support Phone push on Mobile app, Pentabrid (Analoge,AHD,CVI,TVI,IP)            HDMI &amp; VGA Video Output, 2 SATA HDD Up to 6TB for each port            2/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface            P2P support, IOS-Andriod Mobile APP &amp; CMS PC Software, Wireless Mouse</p>		<b>92,900,000</b>

