


































مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
1 HAC-HFW1509MHP-A-LED-S2	5MP Full-color HDCVI Bullet Camera Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens Built-in Mic CVI/CVBS/AHD/TVI Switchable, Support OSD Menu 120 dB true WDR, HLC, HLC-Pro, BLC, 3D DNR, AGC, AWB 2 LEDs 50m Distance, Smart Light, IP67, DC12V		40,350,000
2 HAC-HFW1509TMP-IL-A	5MP Smart Dual Illuminators Bullet Camera Max 25 fps@5MP (16:9 video output). 120 dB true WDR, 3D NR. Smart Dual Illuminators, 40 m illumination distance Min. Illumination, 0.001 lux@F1.0 (Color, 30 IRE), 0.0001 lux@F1.0 (B/W, 30 IRE) Super Adapt, Built-in MIC, BLC; HLC; WDR; HLC-Pro 3.6 mm fixed lens (2.8 mm optional). CVI/CVBS/AHD/TVI switchable, IP67, 12 VDC		47,750,000
3 HAC-HFW1509TLM-A-LED	5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens Built-in Mic CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, BLC, 3D DNR, AGC, AWB 2 LEDs 40m Distance, Smart Light, IP67, DC12V		38,550,000
4 HAC-HFW1509TLM-LED-S2	5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, BLC, 3D DNR, AGC, AWB 2 LEDs 40m Distance, Smart Light, IP67, DC12V		36,250,000
5 HAC-HFW1509TP-LED	5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, HLC-Pro, BLC, 3D DNR, AGC, AWB 1 LED 20m Distance, Smart Light, IP67, DC12V		35,650,000
6 HAC-HFW1509TP-A	5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) Built-in mic 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, HLC-Pro, BLC, 3D DNR, AGC, AWB 1 LED 20m Distance, Smart Light, IP67, DC12V		36,500,000
7 DH-HAC-HFW1500RP-Z-IRE6-S2	5MP Starlight HDCVI IR Bullet Camera, Image Sensor 1/2.7 inch CMOS Max 25 fps@5MP (16:9 video output) CVI/CVBS/AHD/TVI switchable 2.7 mm-12 mm motorized lens, 0.005 Lux/F1.6, 30IRE, 0 Lux IR on Illumination Distance 60 m , S/N Ratio > 65 dB Pan/Tilt/Rotation Range Pan: 0°-360°, Tilt: 0°-90°, Rotation: 0°-360° Max. IR length 60 m, Smart IR, BLC/HLC/DWDR IP67, 12V DC		48,550,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
8	<p>HFW1500TLM-IL-A-S2</p> <p>5MP Smart Dual Light HDCVI Fixed-focal Bullet Camera Max 25 fps@5MP (16:9 video output) 3.6 mm fixed lens, 0.05 lux@F1.6 (Color, 30 IRE), 0.005 lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on), 40 m illumination distance Smart Dual Light, Super Adapt, Auto ICR, BLC, HLC, DWDR, AWB, AGC, 2D NR, <b>Built-in MIC</b> IP67, 12 VDC, Metal + Plastic Case</p>		31,300,000
	 		
9	<p>DH-HAC-HFW1500THP-I4</p> <p>5MP HDCVI IR Bullet Camera, 1/2.7" Progressive Scan CMOS 20fps@5MP, 25/30fps@4MP (16:9 video output) 3.6mm fixed lens, Aperture: F1.85 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Support Electronic Defog, HD/SD switchable Max. IR length 40m, Smart IR, IP67, DC12V±30</p>		24,050,000
10	<p>DH-HAC-HFW1500THP-I8</p> <p>5MP HDCVI IR Bullet Camera, 1/2.7" Progressive Scan CMOS 20fps@5MP, 25/30fps@4MP (16:9 video output) 3.6mm fixed lens, Aperture: F1.85 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Support Electronic Defog, HD/SD switchable Max. IR length 80m, Smart IR, IP67, DC12V±30</p>		27,550,000
11	<p>DH-HAC-HFW1500TP-0360B-S3</p> <p>5MP Starlight HDCVI IR Bullet Camera Max 25 fps@5MP (16:9 video output) 3.6 mm fixed lens, Max. Aperture F1.6 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR CVI/CVBS/AHD/TVI switchable, Support OSD Menu Max. IR length 30 m, Smart IR, IP67, DC12V</p>		23,700,000
			
12	<p>DH-HAC-HFW1500DP</p> <p>5MP Starlight HDCVI IR Bullet Camera Max 25 fps@5MP (16:9 video output) 3.6 mm fixed lens, Max. Aperture F1.6/Min. Illumination 0.005 Lux DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR CVI/CVBS/AHD/TVI switchable, Support OSD Menu Max. IR length 80 m, Smart IR, IP67, DC12V</p>		33,250,000
			
13	<p>DH-HAC-HFW1500CMP</p> <p>5MP Starlight HDCVI IR Bullet Camera Max 25 fps@5MP (16:9 video output) 3.6 mm fixed lens, Max. Aperture F1.6/Min. Illumination 0.005 Lux DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR CVI/CVBS/AHD/TVI switchable, Support OSD Menu Max. IR length 30 m, Smart IR, IP67, DC12V</p>		23,700,000
			
14	<p>DH-HAC-B2A51P-U-IL-S2</p> <p><b>NEW</b></p> <p>5MP Smart Dual Light HDCVI Fixed-focal Bullet Camera 5 MP Progressive CMOS, HD/SD Output Max 25 fps@5MP (16:9 video output), 3.6 mm: H: 92°; V: 48°; D: 109° Min. Illumination 0.02 lux@F2.0 (Color, 30 IRE) 0.002 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on), IR: 30m, Warm Light: 20m Smart Dual Light, DWDR, BLC, HLC, 2D DNR, AWB, AGC IP67, 12 VDC ± 30%, Metal Case</p>		23,800,000
			
15	<p>HAC-B1A51</p> <p>5MP HDCVI IR Bullet Camera, 1/2.7" 5 MegaPixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P (16:9 video output) 3.6mm, 2.8mm fixed lens, HD and SD output switchable DWDR, Day/Night(ICR), BLC, HLC, AGC, AWB, 2D-DNR, Support OSD Menu, Max. IR length 20m, Smart IR, IP67, DC12V, Casing Plastic</p>		18,150,000
			
16	<p>DH-HAC-B2A51P</p> <p>5MP HDCVI IR Bullet Camera, 1/2.7" 5 MegaPixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P (16:9 video output) 3.6mm fixed lens, HD and SD output switchable DWDR, Day/Night(ICR), BLC, HLC, AGC, AWB, 2D-DNR, Support OSD Menu, Max. IR length 20m, Smart IR IP67, DC12V, Casing Aluminium</p>		21,200,000
			
17	<p>DH-HAC-B1A41P</p> <p>4MP HDCVI IR Bullet Camera, 1/2.7" 4Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 3.6mm fixed lens HD and SD output switchable, Max. IR length 20m IP67, DC12V, Casing: Plastic</p>		15,300,000
			
18	<p>DH-HAC-B2A41P</p> <p>4MP HDCVI IR Bullet Camera, 1/2.7" 4Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 3.6mm fixed lens HD and SD output switchable, Max. IR length 20m IP67, DC12V, Casing: Aluminium</p>		18,750,000
			

توجه: دستگاه های جدید XVR به جز دستگاه های ستاره دار، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
19	HFW1239TLMP-IL-A Full-Color Microphone icon	2MP Smart Dual Illuminators Bullet Camera Progressive CMOS - Focal Length 3.6 mm Max. 30 fps@1080p 0.001 lux@F1.6 (Color, 30 IRE) - 0.0001 lux(B/W, 30 IRE) - 0 lux (Illuminator on) Smart Dual Illuminators - <b>Built-in-mic</b> CVI/CVBS/AHD/TVI Switchable, Support OSD Menu 130 dB true WDR, HLC, BLC, 3D DNR, AGC, AWB 2 LEDs 40m distance - 2 IR Lights 40m distance Smart IR & WL, IP67, DC12V	 30,250,000
20	HFW1239MHP-A-LED Full-Color Microphone icon	2MP Full-color HDCVI Bullet Camera, 1/2.8" CMOS ,24/7 color imaging Max. 30 fps@1080p,3.6 mm fixed lens (6 mm optional) 50 m illumination distance , Super Adapt, 130 dB true WDR, 3D NR Focal Length 3.6 mm; 6 mm , Built-in mic ,CVI/CVBS/AHD/TVI switchable Min Illumination 0.001 Lux/F1.6, 30IRE, 0 Lux LED on , IP67, DC 12 V	 34,350,000
21	DH-HAC-HFW1239TLMP-A-LED STARLIGHT Full-Color Microphone icon	2M Full-color Starlight HDCVI Bullet Camera 1/2.8 inch 2.16 MP CMOS Minimum Illumination:0.005Lux/F1.6 1080@25fps, 720@25/50fps 3.6mm fixed lens <b>Built-in mic</b> CVI/CVBS/AHD/TVI Switchable WDR (130 db) , BLC, HLC, 2DNR,AGC,AWB Electronic Defog 40m LED distance, IP67, DC12V	 27,450,000
22	DH-HAC-HFW1239TLMP-LED STARLIGHT Full-Color	2M Full-color Starlight HDCVI Bullet Camera 1/2.8 inch 2.16 Mega Pixels Progressive CMOS 0.005Lux/F1.6, 30IRE, 0Lux white Light on Max. 30fps@1080P 3.6mm fixed lens, 16x Digital Zoom CVI/TVI/AHD/CVBS Switchable, Support OSD Menu WDR (130 db)/E-Defog/BLC/HLC/AWB/AGC/2D DNR 40m LED Distance Smart Light, IP67, DC12V	 27,050,000
23	HAC-HFW1239TP-LED STARLIGHT Full-Color	2MP Full-color HDCVI Bullet Camera 2MP 1/2.8" Progressive CMOS Max 2MP@25/30fps 3.6mm fixed lens CVI/CVBS/AHD/TVI switchable, Support OSD Menu WDR(130db), BLC, HLC, AWB, AGC, 3D DNR Smart Light, 1 LED 20m Distance, IP67, DC12V	 26,000,000
24	DH-HAC-HFW1231RP-Z-A STARLIGHT Microphone icon	2MP Starlight HDCVI IR Bullet Camera 1/2.8" 2Megapixel CMOS (Starlight) Minimum Illumination:0.002Lux/F1.5 1080@25fps, 720@25/50fps 2.7-12mm motorized lens HD and SD output switchable, <b>Built in mic</b> , WDR(130dB), BLC, HLC, 3DNR, AGC,AWB 80m LED distance, Smart IR, IP67, DC12V	 44,300,000
25	DH-HAC-HFW1231RP-Z-IRE6 STARLIGHT	2MP Starlight HDCVI IR Bullet Camera 1/2.8" 2Megapixel CMOS (Starlight) Minimum Illumination:0.002Lux/F1.5 1080@25fps, 720@25/50fps 2.7-12mm motorized lens HD and SD output switchable WDR(130dB), BLC, HLC, 3DNR, AGC,AWB 80m LED distance, Smart IR, IP67, DC12V	 43,250,000
26	DH-HAC-HFW1230RP-Z-IRE6 STARLIGHT	2MP Starlight HDCVI IR Bullet Camera 1/2.8" 2Megapixel CMOS (Starlight) Minimum Illumination:0.005Lux/F1.8 1080@25fps, 720@25/50fps 2.7-12mm motorized lens HD and SD output switchable DWDR, BLC, HLC, 2DNR, AGC,AWB 60m LED distance, Smart IR, IP67, DC12V	 39,250,000
27	DH-HAC-HFW1230TP STARLIGHT	2MP Starlight HDCVI IR Bullet Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens (2.8mm, 6mm Optional) HD and SD output switchable, Support OSD Menu Starlight, DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V, Casing: Aluminium	 19,000,000

توجه: دستگاه های جدید XVR به جز دستگاه های ستاره دار، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.


























مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
28 DH-HAC-HFW1230TP-A 	2MP Starlight HDCVI IR Bullet Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, <b>Built-in mic</b> DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V		19,450,000
29 DH-HAC-HFW1230DP 	1/2.8" 2Megapixel CMOS (Starlight) 3.6mm Fixed lens, 25/30fps@1080P & @720P DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, OSD Menu Max. IR length 80m, Smart IR, IP67, DC12V		25,050,000
30 DH-HAC-HFW1220THP-I4 	2MP Value Starlight HDCVI IR Bullet Camera 1/2.7 inch CMOS 1080P@25fps, 720P@25fps, 720@50fps 3.6mm Fixed lens Value Starlight Minimum Illumination:0.008Lux/F1.85 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D DNR Smart IR, Electronic Defog CVI/CVBS/AHD/TVI switchable Max. IR length 40m, Smart IR, IP67, DC12V		19,450,000
31 HAC-HFW1209TLMP-LED-0360B 	2MP Full-color HDCVI Bullet Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 3.6mm Fixed lens Min. Illumination 0.001 Lux/F1.6, 30IRE, 0 Lux LED on DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3D DNR CVI/CVBS/AHD/TVI switchable, OSD Menu Support 40m LED distance, IP67, DC12V		21,600,000
32 HAC-HFW1209CMP-LED-0360B-S2  	2MP Full Color Starlight HDCVI Bullet CCTV Camera 1/2.8 inch 2.16 Mega Pixels Progressive CMOS Max 30fps@2MP 3.6mm fixed lens CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V		20,250,000
33 HAC-HFW1209CP-LED-0360B 	2MP Full-color HDCVI Bullet Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu DWDR/BLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V		16,450,000
34 HAC-HFW1200TLM-IL-A-S6   	2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera <b>* In order to use the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000004.1.R.220323 or later version.</b> 2 MP Progressive CMOS Sensor 3.6 mm Lens: H: 83°; V: 48°; D: 105° Max. 30 fps@1080p, CVI/CVBS/AHD/TVI switchable DWDR, BLC, HLC, AWB, AGC, Day/Night Auto(ICR)/Color/B/W, Smart Dual Light, Illumination Distance IR: 40 m (131.23 ft) Warm light: 40 m (131.23 ft) , Super Adapt, 3D DNR, <b>Built-in mic, 1 Audio in</b> Min. Illumination 0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on) 12 VDC, IP67, Metal+Plastic		21,300,000
35 DH-HAC-HFW1200RP-Z-IRE6 	2MP HDCVI IR Bullet Camera, 1/2.7 inch CMOS Max 30fps@1080P, Min Illumination 0.02Lux/F1.7, 30IRE, 0Lux IR on Motorized vari-focal 2.7 mm-12 mm, Fixed iris BLC/HLC/DWDR , Gain Control , Noise Reduction 2D NR , Smart IR Max. IR length 60m,IP67, DC12V Built-in mic(-A)		37,900,000
36 DH-HAC-HFW1200TLP	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P <b>3.6 &amp; 2.8mm</b> fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 40m, Smart IR, IP67, DC12V		16,300,000
37 DH-HAC-HFW1200THP-A 	2MP HDCVI IR Bullet Camera 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens (2.8mm, 6mm Optional), <b>Built-in mic</b> HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 80m, Smart IR, IP67, DC12V		18,650,000

توجه: دستگاه های جدید XVR به جز دستگاه های ستاره دار، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.






















مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
38	DH-HAC-HFW1200THP-I4 2MP HDCVI IR Bullet Camera 1/2.7 inch CMOS 1080P@25fps, 720P@25fps, 720@50fps 3.6mm Fixed lens Minimum Illumination:0.02Lux/F1.9 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Smart IR, Eletronic Defog HD and SD output switchable Max. IR length 40m, Smart IR, IP67, DC12V		18,300,000
39	DH-HAC-HFW1200DP-0360B-S5 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P DWDR, Day/Night(ICR), AWB, AGC, HLC, BLC, 2D-DNR HD and SD output switchable, 3.6mm fixed lens Max. IR LEDs length 80m, Smart IR, IP67, DC12V		22,000,000
40	HAC-HFW1200CMP-0360B 2MP HDCVI IR Bullet Camera 1/2.7 inch Progressive CMOS Max 30fps@2MP, 3.6mm fixed lens CVI/TVI/AHD/CVBS output switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR Max. IR length 30m, Smart IR, IP67, DC12V		17,350,000
41	HAC-HFW1200CMP-A 2MP HDCVI IR Bullet Camera 1/2.7 inch Progressive CMOS Max 30fps@2MP, 3.6mm fixed lens, <b>Built-in mic</b> CVI/TVI/AHD/CVBS output switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR Max. IR length 30m, Smart IR, IP67, DC12V		18,650,000
42	HAC-HFW1200CM-IL-A-S6 2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera <b>* In order to use the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000004.1.R.220323 or later version.</b> 2 MP Progressive CMOS Sensor 3.6 mm: H: 83°; V: 48°; D: 105° Max. 30 fps@1080p, CVI/CVBS/AHD/TVI switchable DWDR, BLC, HLC, AWB, AGC, 3D DNR, Day/Night Auto(ICR)/Color/B/W, Smart Dual Light, Illumination Distance IR: 20m (65.62 ft) Warm light: 20m (65.62 ft), Super Adapt, Built-in mic, 1 Audio in Min. Illumination 0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on) 12 VDC, IP67, Metal		20,400,000
43	DH-HAC-HFW1200SP 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR length 30m, Smart IR, IP67, DC12V		17,450,000
44	DH-HAC-HFW1200TP 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 2.8mm/3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR length 25m, Smart IR, IP67, DC12V		18,150,000
45	DH-HAC-HFW1200TP-A 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens, <b>Built-in mic</b> HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR length 30m, Smart IR, IP67, DC12V		18,650,000
46	DH-HAC-HUM3201B 1/2.8" 2Megapixel CMOS ( <b>Starlight</b> ), 25/30fps@1080P & @720P 2.8mm fixed lens HD and SD output switchable, Support OSD Menu WDR(120dB), Day/Night(ICR), AWB, AGC, BLC,HLC, 3DNR, DC12V		22,900,000
47	DH-HAC-B2A21P-U 2MP IR HDCVI Fixed-focal Bullet Camera 2 MP Progressive CMOS Sensor Max. 30 fps@1080p, 3.6 mm fixed lens CVI/CVBS/AHD/TVI switchable IR 30m, 0.02 lux@F2.0 (Color, 30 IRE), HFoV 80° DWDR, AGC, AWB, 2D DNR, Smart IR IP67, Metal Case		14,750,000
48	DH-HAC-B2A21P 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium		14,500,000
49	DH-HAC-B1A21P 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Plastic		11,800,000

توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.











مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
50	<p>DH-HAC-HDW1509TP-IL-A</p>   <p>5MP Smart Dual Illuminators Eyeball Camera Max 25 fps@5MP (16:9 video output). 120 dB true WDR, 3D NR Smart Dual Illuminators, 40 m illumination distance Super Adapt, Built-in MIC. 3.6 mm fixed lens (2.8 mm optional). CVI/CVBS/AHD/TVI switchable. IP67, 12 VDC.</p>		45,100,000
51	<p>DH-HDW1509TP-A-LED</p>   <p>5MP Full-color HDCVI Eyeball Camera Progressive CMOS - Focal Length 2.8 mm Min. Illumination 0.001 Lux/F1.0, 0 Lux warm light on Illumination 2 LEDs Distance 40 m <b>Built-in mic</b>, CVI/CVBS/AHD/TVI switchable WDR 120db, BLC, HLC, HLC-Pro, AWB, AGC, 3DNR Privacy Masking, Smart Light, IP67, DC 12V</p>		38,550,000
52	<p>DH-HAC-HDW1509TLQP-A-LED-S2</p>   <p>5MP Full-color HDCVI Quick-to-install Eyeball Camera 25fps@5MP, 25/30fps@4MP/1080P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu 120dB WDR, 3D/2D NR, Day/Night(ICR), AWB, AGC, BLC, HLC 20m illumination distance, Smart IR, IP67, DC12V, <b>Built-in mic</b></p>		36,600,000
53	<p>DH-HAC-HDW1509TLQP-LED</p>  <p>5MP Full-color HDCVI Quick-to-install Eyeball Camera 25fps@5MP, 25/30fps@4MP/1080P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu 120dB WDR, 3D/2D NR, Day/Night(ICR), AWB, AGC, BLC, HLC 20m illumination distance, Smart IR, IP67, DC12V</p>		32,900,000
54	<p>DH-HAC-HDW1500SLP</p> <p>5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP/1080P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 20m, Smart IR, IP67, DC12V</p>		19,100,000
55	<p>DH-HAC-HDW1500TRQP-A-0280B-S2-S3</p>  <p>5MP Starlight HDCVI Quick-to-install IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 25/30 fps@5MP, 25/30fps@4MP, 1080P@25/30 fps, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR,, <b>Built-in Mic</b> Max. IR LEDs length 20m, Smart IR, IP50, DC12V</p>		22,900,000
56	<p>DH-HAC-HDW1500TRQP-0280B-S3</p> <p>5MP Starlight HDCVI Quick-to-install IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 25/30 fps@5MP, 25/30fps@4MP, 1080P@25/30 fps, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 20m, Smart IR, IP67, DC12V</p>		20,500,000
57	<p>HAC-HDW1500CLQ-IL-A-S2</p>    <p>5MP Smart Dual Light HDCVI Fixed-focal Quick-to-install Eyeball Camera <b>* In order to use the 5MP 16:9 and the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000004.1.R.220323 or later version.</b> 5MP Progressive CMOS Sensor 2.8 mm: H: 106°; V: 56°; D: 125° Max 25 fps@5MP (16:9 video output), CVI/CVBS/AHD/TVI switchable DWDR, BLC, HLC, AWB, AGC, 2D DNR, Day/Night Auto(ICR)/Color/B/W, Smart Dual Light, Illumination Distance IR: 20m (65.62 ft) Warm light: 20m (65.62 ft), Super Adapt, Built-in mic Min. Illumination 0.05 lux@F1.6 (Color, 30 IRE) 0.005 lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on) 12VDC, IP67, Plastic, Quick-to-install</p>		27,750,000
58	<p>HAC-T2A51-U-IL-A</p>    <p>5MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera 25 fps@5MP (16:9 video output), 2.8mm Lens H: 106°; V: 56°; D: 125° Day/Night Auto(ICR), DWDR, BLCm HLCm AWB, AGC, 2D DNR, Smart Dual Light 30m Min. Illumination 0.02 lux@F2.0 (Color, 30 IRE) 0.002 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on) IP67, Built-in Mic, Quick-to-install, CVI/CVBS/AHD/TVI switchable, Casing Metal</p>		24,900,000
59	<p>HAC-T2A51P</p>  <p>5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP &amp; @1080P (16:9 video output) 3.6mm &amp; 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Support OSD Menu Max. IR length 20m, IP67, DC12V, Casing: Aluminium</p>		21,200,000

توجه: دستگاه های جدید XVR به جز دستگاه های ستاره دار، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
60 HAC-T1A51P <b>Cooper Series</b>	5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P (16:9 video output) 3.6mm and 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Support OSD Menu Max. IR length 20m, IP67, DC12V, Casing: Plastic		17,750,000
61 DH-HAC-T2A41P <b>Cooper Series</b>	1/2.7" 4Megapixel CMOS, 25/30fps@4MP, 25/30fps@1080P 2.8mm fixed lens, HD and SD output switchable Max. IR length 20m, IP67, DC12V, Casing: Aluminium		18,650,000
62 DH-HAC-T1A41P <b>Cooper Series</b>	1/2.7" 4Megapixel CMOS, 25/30fps@4MP, 25/30fps@1080P 2.8mm fixed lens, HD and SD output switchable Max. IR length 20m, DC12V, Casing: Plastic		15,300,000
63 DH-HAC-HDW1239TLP-A-LED  <b>STARLIGHT Full-color</b> 	2M Full-color Starlight HDCVI Eyeball Camera 1/2.8 inch 2.16 Mega Pixels CMOS Minimum Illumination:0.005Lux/F1.6 Full-color starlight 1080@25fps, 720@25fps, 720@50fps 3.6 mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Smart Light, Electronic Defog HCVI/CVBS/AHD/TVI switchable <b>Built-in Mic</b> 20m LED distance, IP67, DC12V		25,300,000
64 DH-HAC-HDW1230MP <b>STARLIGHT</b>	2MP Starlight HDCVI IR Eyeball Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V		16,700,000
65 HAC-HDW1209TLQP-A-LED-0280B  <b>Full-color</b> 	2MP Full-color HDCVI Quick-to-install Eyeball Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 2.8mm fixed lens <b>Built-in Mic</b> CVI/CVBS/AHD/TVI Switchable, Support OSD Menu DWDR/BLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V		19,350,000
66 HAC-HDW1209TLQP-LED-0280B  <b>Full-color</b>	2MP Full-color HDCVI Quick-to-install Eyeball Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 2.8mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu DWDR/BLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V		16,800,000
67 DH-HAC-HDBW1200EP	2MP HDCVI IR Dome Camera, 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 2.8mm Fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, IK10, DC12V		18,300,000
68 DH-HAC-HDW1200LP 	2MP HDCVI IR Eyeball Camera, 1/2.7" 2Megapixel CMOS Max 30fps@1080P, 2.1mm fixed lens HD and SD output switchable, <b>Built in Mic</b> , Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 3m, Smart IR, IP67, DC12V		21,750,000
69 DH-HAC-HDW1200MP	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens HD and SD output switchable, Support OSD Menu Day/Night(ICR), AWB, AGC, BLC, 2D-DNR Max. IR length 30m, Smart IR, IP67, DC12V		15,650,000
70 DH-HAC-HDW1200EMP-A <b>Metal Case</b> 	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, <b>Built-in MIC</b> Day/Night(ICR), AWB, AGC, BLC, 2DNR, DWDR 3.6 & 2.8mm fixed lens Max. IR LEDs length 50m, Smart IR, IP67, DC12V		19,350,000
71 HAC-HDW1200TRQP-A-0280B-S6  	2MP HDCVI Quick-to-install IR Eyeball Camera 1/2.7 inch Progressive CMOS Max 30fps@2MP 2.8mm/3.6mm fixed lens <b>Built in Mic</b> CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto switch by ICR Max. IR length 25m, Smart IR, IP50, DC12V		16,300,000

**توجه:** دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
72 DH-HAC-HDW1200TLP-A	<p>2MP HDCVI IR Eyeball Camera 1/2.7 inch CMOS Max 30fps@1080P 2.8mm Fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR <b>Built-in mic</b> Electronic Defog CVI/CVBS/AHD/TVI switchable Max. IR length 30m, Smart IR, IP67, DC12V</p>		17,150,000
73 HAC-HDW1200CLQ-IL-A-S6	<p>2MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera <b>* In order to use the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000004.1.R.220323 or later version.</b> 2 MP Progressive CMOS Sensor 2.8 mm: H: 102°; V: 60°; D: 129° Max. 30 fps@1080p, CVI/CVBS/AHD/TVI switchable DWDR, BLC, HLC, AWB, AGC, 3D DNR, Day/Night Auto(ICR)/Color/B/W, Smart Dual Light, Illumination Distance IR: 20m (65.62 ft) Warm light: 20m (65.62 ft), Super Adapt, Built-in mic, 1 Audio in Min. Illumination 0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on) 12VDC, IP67, Plastic, Quick-to-install</p>		18,150,000
74 DH-HAC-T2A21P-U-A	<p><b>NEW</b></p> <p>2MP IR HDCVI Fixed-focal Eyeball Camera Max. 30 fps@1080p, 2.8 mm: H: 100°; V: 54°; D: 117° 2 MP Progressive CMOS, HD/SD switchable Min. Illumination 0.02 lux@F2.0 (Color, 30 IRE) 0.002 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on) <b>Built-in Mic</b>, Smart IR 30m, DWDR, BLC, 2D DNR, AWB, AGC IP67, 12 VDC, Metal Case</p> <p>Cooper Series</p>		16,400,000
75 DH-HAC-T1A21P-U	<p>2MP IR HDCVI Fixed-focal Eyeball Camera Max. 30 fps@1080p, 2MP Progressive CMOS Sensor, 2.8mm Fixed Lens CVI/CVBS/AHD/TVI switchable IR 25m, 0.02 lux@F2.0 (Color, 30 IRE) DWDR, AGC, AWB, 2D DNR, Smart IR, Day/Night ICR Quick-to-install eyeball</p> <p>Cooper Series</p>		12,000,000
76 DH-HAC-T2A21P	<p>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium</p> <p>Cooper Series</p>		14,500,000
77 DH-HAC-T1A21P	<p>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P <b>2.8mm &amp; 3.6 fixed lens</b> HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, Casing: Plastic, DC12V</p> <p>Cooper Series</p>		11,500,000
78 HAC-PT1509A-A-LED	<p><b>NEW</b></p> <p>5MP Full-color HDCVI Fixed-focal PT Camera 25 fps@5MP (16:9 video output), 2.8 mm: H: 111°; V: 57°; D: 131° Min. Illumination 0.001 lux@F1.0 (Color, 30IRE) 0 lux (Illuminator on) Pan &amp; Tilt, Smart Area Lighting, 40 m illumination, 24/7 color imaging, Super Adapt, Built-in Mic, Quick-to-install, 4x Digital Zoom WDR 120db, BLC, HLC, HLC Pro, AWB, AGC, 3D DNR, E-Defog, Smart Light IP66, 12 VDC, Plastic</p> <p>Full-color</p>		54,700,000
79 DH-SD59225I-HC-S2	<p>1/2.8" 2Megapixel Exmor R CMOS (<b>Starlight</b>) Max 25/30fps @1080P &amp; 20/30/50/60fps @720P Resolution 4.8mm ~ 120mm 25x optical zoom WDR (120db), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation Control over coaxial cable 1-channel BNC HDCVI/CVBS output (switchable) Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Built-in 2/1 Alarm in/out, 1 Audio Input, RS485 IR Distance up to 150m, IP66, OSD</p> <p>STARLIGHT</p>		239,100,000

توجه: دستگاه های جدید XVR به جز دستگاه های ستاره دار، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.









مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
80	SD59230I-HC  2MP 30x Starlight IR PTZ HDCVI Camera, 1/2.8" Exmor R CMOS Max. 25/30fps @1080P(1920x1080) & 50/60fps @720P Resolution 4.5mm~135mm 30x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation HD and SD switchable Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Audio(in/out) 1 / 1 , Built-in 2/1 Alarm in/out IR Distance up to 150m, IP66,OSD		278,950,000
81	DH-SD49225I-HC-LA  2MP 25x Starlight IR PTZ HDCVI Camera, 1/2.8" STARVIS CMOS Max. 25/30fps @1080P(1920x1080) & 50/60fps @720P Resolution 4.8mm~120mm 25x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, HLC, BLC, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern HD and SD switchable, 2/1 Alarm In/Out 1CH Audio In, RS485, IR Distance up to 100m, IP66,OSD		223,400,000
82	DH-XVR1A04  4CH Penta-brid 1080N/720P Real-Time Cooper Recorder H.264 video compression, 4CH: 1/4 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+1 IP up to 2 MP(20 Mbps)] 1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 8 TB HDMI , VGA ,simultaneous video Output 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support		26,350,000
83	XVR1B04-I  4 Channel Penta-brid 1080N/720p Real-time WizSense Ai XVR H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+1 IP up to 2MP(20 Mbps), 4CH: 1/4 Playback HDMI , VGA ,simultaneous video Output 1 SATA port, up to 6 TB capacity 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support SMD Plus, Full channel AI-Coding, Human/Vehicle Classification		31,800,000
84	DH-XVR1A08  8CH Penta-brid 1080N/720P noneReal-Time Cooper Recorder H.264 video compression, 8CH:1/4/9 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+2 IP up to 5 MP(40 Mbps)] 1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 8 TB HDMI , VGA ,simultaneous video Output, 2*USB 2.0 10/100 Mbps LAN Interface, P2P Support		32,350,000
85	XVR1B08-I  8 Channel Penta-brid 1080N/720p Real-time WizSense Ai XVR H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+2 IP up to 6MP(40 Mbps), 4CH: 1/4/9 Playback HDMI , VGA ,simultaneous video Output 1 SATA port, up to 6 TB capacity 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification		38,650,000
86	XVR1B08H-I  8 Channels 5M-N/1080p Cooper 1U 1HDD Digital Video Recorder Supports Full-channel AI-Coding , H.265+/H.265 dual-stream Pentabrid (IP+CVI+AHD+TVI+CVBS) - Max 12 channels IP camera inputs Up to 8 channels SMD Plus Human/Vehicle Classification Encoding Capacity : 5M-N@(10 fps); 4M-N/1080p@(15 fps); 1080N@(25/30 fps) 1/4/8/9 Playback , 1 SATA port, up to 16 TB capacity 2*USB 2.0, Audio In/Out : 1/1 , 10/100 Mbps LAN Interface, P2P Support		66,450,000
87	XVR5104HS-I3(V3.0)  New GUI V4.0 Support - 4 Channel Penta-brid 5M-N/1080p None Real-Time WizSense Ai XVR 5M-N; 4M-N; 1080p; 1080N; 720p; 960H; D1; CIF H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 6MP(32 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4ch 1 SATA Port up to 6 TB capacity 2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification, IoT Support		53,500,000





توجه: دستگاه های جدید XVR به جز دستگاه های ستاره دار، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
88	<p>XVR5104HS-4KL-I3(V3.0)</p> <p><b>4K</b></p> <p><b>Wiz Sense AI</b></p> <p>New GUI V4.0 Support - 4 Channel Penta-brid 4K WizSense Ai XVR            4K@7fps, 6MP@10fps, 5MP@12fps, 4MP@15fps, 4MN/1080p/720p@25/30fps            H.265+/H.265/H.264+/H.264 dual-stream video compression            Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 4+4 IP up to 8MP(64 Mbps)            HDMI/VGA Simultaneous Video Output, 1ch Audio I/O            Playback 1/4ch            1 SATA Port up to 10 TB capacity            2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support            1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification, IoT Support</p>		78,350,000
89	<p>XVR5108HS-4KL(V.2)</p> <p><b>AI</b></p> <p>New GUI V4.0 Support - 8CH Penta-brid 4K Recorder            HDCVI 4K, AHD,5mp, HDTV 5MP 8+4ch support            H.264+/H.264 dual-stream video compression            Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 8MP            Tripwire, Intrusion, Face Detection, Smart Search            1/1 Audio In/Out, 1 SATA Port , Up to 8TB            1*HDMI, 1*VGA ,simultaneous video Output            2*USB 2.0, 1*10/100 Mbps LAN Interface , P2P Support</p>		111,550,000
90	<p>XVR5108HS-I3(V3.0)</p> <p><b>Wiz Sense AI</b></p> <p>New GUI V4.0 Support - 8 Channel Penta-brid 5M-N/1080p None Real-Time WizSense Ai XVR            5M-N; 4M-N; 1080p; 1080N; 720p; 960H; D1; CIF            H.265+/H.265/H.264+/H.264 dual-stream video compression            Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M 8+4 IP up to 6MP(64 Mbps)            HDMI/VGA Simultaneous Video Output, 1ch Audio I/O            Playback 1/4/9ch            1 SATA Port up to 10 TB capacity            2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support            1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 8ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification, IoT Support</p>		77,050,000
91	<p>XVR5108HS-4KL-I2</p> <p><b>4K</b></p> <p><b>Wiz Sense AI</b></p> <p>New GUI V4.0 Support - 8 Channel Penta-brid 4K-N/5MP WizSense Ai XVR            4K@7fps, 6MP@10fps, 5MP@12fps, 4K-N/4MP@15fps, 4MN/1080p/720p@25/30fps            H.265+/H.265/H.264+/H.264 dual-stream video compression            Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 8+8 IP up to 8MP(128 Mbps)            HDMI/VGA Simultaneous Video Output, 1ch Audio I/O            Playback 1/4/9ch            1 SATA Port up to 10 TB capacity            1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support            2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 20,000 Face Library, 8ch SMD Plus, Human/Vehicle Classification, IoT Support</p>		130,200,000
92	<p>XVR5108HS-4KL-I3(V2.0)</p> <p><b>Wiz Sense AI</b></p> <p>New GUI V4.0 Support - 8 Channels Penta-brid 4K-N/5MP            Encode Capacity All channel 4K@(7 fps); 6MP@ (10 fps); 5MP@ (12 fps); 4K-N/4 MP/3 MP@ (15 fps); 4M-N/1080P @ (25/30fps);            AI Coding/H.265+/H.265 dual-stream video compression            Supports HDCVI/AHD/TVI/CVBS            Up to 16 channels of IPC access / 128 Mbps            Supports Full-channel AI Coding            Perimeter Protection : 8 channels, 10 IVS for each channel / 2 channels (up to 12 face images/s) / Face Recognition : 2 channel up to 10 face databases / Full-channel SMD Plus            Audio Input : 1, RCA (external) 8, BNC (coaxial) / Audio Output 1, RCA            HDD Interface 1 SATA Port, up to 16TB            RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000            DC12V, 2A / Power Consumption Lower than 10 W / Operating Temperature -10 °C to +55 °C</p>		130,200,000
93	<p>DH-XVR1B16</p> <p><b>Cooper Series</b></p> <p>16CH Penta-brid 1080N/720P None Real-Time Cooper Recorder            H.265+/H.265 dual-stream video compression            1st channel 1080N/720P@25fps, others 1080N/720P@15fps            16CH: 1/4/9/16 Playback            Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+2 IP up to 6 MP(64 Mbps)]            1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 6 TB            HDMI , VGA ,simultaneous video Output            2 USB 2 , 10/100 Mbps LAN Interface, P2P Support</p>		63,850,000





توجه: دستگاه های جدید XVR به جز دستگاه های ستاره دار، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
94	<p>8 Channel Penta-brid 1080N/720p Real-time WizSense Ai XVR H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+2 IP up to 6MP(64 Mbps) 4CH: 1/4/9/16 Playback HDMI/VGA Simultaneous Video Output 1 SATA port, up to 6 TB capacity 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support 8ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification</p>		78,200,000
95	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P WizSense Ai XVR 5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+4 IP up to 6MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 1 SATA Port up to 10 TB capacity 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>		134,250,000
96	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P XVR 5MN, 4M-N, 1080P, 1080N, 720P, 960H, D1, HD1, BCIF, CIF, QCIF H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+8 IP up to 5MP(96 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 1 SATA Port, up to 8TB capacity 1 USB 2.0 , 1 USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support Tripwire, Intrusion, Face Detection</p>		115,250,000
97	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P Encode Capacity All channel 5M-N (10 fps); 4M-N/1080p (15fps) AI Coding/H.265+/H.265 dual-stream video compression Supports HDCVI/AHD/TVI/CVBS/IP video inputs Max 24 channels IP camera, up to 6MP; Max 128Mbps incoming bandwidth Supports Full-channel AI Coding / 16 channel SMD / 2 channel face recognition Audio Input : 1, RCA (external) 16, BNC (coaxial) / Audio Output 1, RCA HDD Interface 1 SATA Port, up to 16TB for a single HDD RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000 DC12V, 2A / Power Consumption Lower than 12 W / Operating Temperature -10 °C to +55 °C</p>		134,250,000
98	<p>New GUI V4.0 Support - 16CH Penta-brid 5MN/4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder, 5MN/4M-N/1080P@15fps , 1080N/720P@25fps H.264+/H.264 dual-stream video compression 1/4/9/16CH Playback, Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 MP(96 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out, 2 SATA Port , Up to 16 TB HDMI , VGA ,simultanous video Output, RS485 for PTZ support 2 USB Ports (1 USB 2.0 , 1 USB 3.0) 10/100/1000 Mbps LAN Interface, P2P Support</p>		149,500,000
99	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P WizSense Ai XVR 5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+4 IP up to 6MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 2 SATA Port up to 10 TB capacity each port(20TB Total) 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>		172,200,000

توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
100 XVR5216AN-I3	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P  Encode Capacity All channel 5M-N (10 fps); 4M-N/1080p (15fps)  AI Coding/H.265+/H.265 dual-stream video compression  Supports HDCVI/AHD/TVI/CVBS  16+8 channels,each IP Channel up to 6MP  Supports Full-channel AI Coding  Perimeter Protection : 2 channel, 10 IVS for each channel / Face Detection : 6 attributes ,  2 channels each channel up to 12 faces / Face Recognition : 2 channel up to 10 face  databases / Full-channel SMD Plus  Audio Input : 1, RCA (external) 16, BNC (coaxial) / Audio Output 1, RCA  HDD Interface 2 SATA Port, up to 16TB for a single HDD  RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000  DC12V, 2A / Power Consumption Lower than 12 W / Operating Temperature  -10 °C to +55 °C</p>		172,200,000
101 XVR5216AN-4KL-I2	<p>New GUI V4.0 Support - 16 Channel Penta-brid 4K/5MP WizSense Ai XVR  4K@7fps, 6MP@10fps, 5MN@12fps, 4KN/4MP@15fps, 4MN/2MP/1MP@25/30fps  H.265+/H.265/H.264+/H.264 dual-stream video compression  Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+16 IP up to 8MP(128 Mbps)  HDMI/VGA Simultaneous Video Output, 1ch Audio I/O  Playback 1/4/9/16ch  2 SATA Port up to 10 TB capacity each port(20TB Total)  1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support  2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to  20,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>		260,600,000
102 DH-XVR5216AN-4KL	<p>New GUI V4.0 Support - 16 Channel Embedded Processor  16+8 Channel, each channel up to 8M  HDCV 4K, 4MP, 1080P@25/30fps, 720P@50/60fps, 720P@25/  Record rate Main stream: 4K(1~7fps);4MP(1~15fps);1080P (1~25/30f)  H.264+/H.26 dual-stream video compression  Internal HDD 2 SATA Ports, up to 8TB capacity for each  IP Camera Input 8+4/16+8 Channel, each channel up to 8  Audio In/Out 1/1, RC - 2 USB Ports (1 USB 2.0 , 1 USB 3), 1*RS485, 1*1000 Mbps</p>		224,600,000
103 DH-XVR5216AN-4KL-I3(V2.0)	<p>New GUI V4.0 Support - 16 Channels Penta-brid 4K-N/5MP  Encode Capacity All channel 4K@(7fps); 6MP@(10fps); 5MP@(12fps); 4K-  N/4MP/3MP@(15fps); 4M-N/1080P(25/30fps);  AI Coding; H.265+; H.265; H.264+; H.264  Supports HDCVI/AHD/TVI/CVBS/IP video inputs.  Max 32 channels IP camera inputs, each channel up to 8MP  Supports Full-channel AI Coding  Perimeter Protection : Advanced Model: 2 channels , General Model: 8 channels ; Face  Detection : 2 channels ;Face Recognition : 2 channels , Up to 10 face databases , SMD  Plus : 16 channels  Audio Input :1-channel RCA , 16-channel BNC 16 / Audio Output 1, RCA  HDD Interface 2 SATA Port, up to 16TB for a single HDD  RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000  12 VDC, 5A / Power Consumption Lower than 15 W(without HDD) / Operating  Temperature-10 °C to +55 °C</p>		260,600,000
104 DH-XVR5232AN-S2(V.2)	<p>New GUI V4.0 Support - 32CH Penta-brid 1080P Recorder  4M-N/1080P@15fps, 1080N/720P@25fps  H.264+/H.264 dual-stream video compression  16CH Playback  Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 5 MP(128 Mbps)]  Support Smart Search and Intelligent Video System  1/1 Audio In/Out, 2 SATA Port , Up to 16 TB  1*HDMI, 1*VGA ,simultaneous video Output  RS485 for PTZ support, 2*USB(1 USB2.0 , 1 USB3.0)  1*10/100/1000 Mbps LAN Interface, P2P Support</p>		240,500,000

توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
105 XVR5232AN-I2	<p>New GUI V4.0 Support - 32 Channel Penta-brid 5M-N/1080P WizSense Ai XVR 5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 32ch IP up to 6MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 2 SATA Port up to 10 TB capacity each port(20TB Total) 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>		278,450,000
106 XVR5232AN-I3(V2.0)	<p>New GUI V4.0 Support - 32 Channels Penta-brid 5M-N/1080P Encode Capacity All channels 5M-N@(10fps); 4M-N/1080P@(15fps) AI Coding/H.265+/H.265 dual-stream video compression Supports HDCVI/AHD/TVI/CVBS 32 IP channels, up to 6MP / bandwidth: 128 Mbps Supports 16-channel AI Coding Perimeter Protection : Up to 4 channels 10 IVS for each channel / Face Detection : 2 channels (up to 12 face images/s) / Face Recognition : Up to 2 channels, Up to 10 face databases /16 channels SMD Plus) Audio Input : 1, RCA (external) 32, BNC (coaxial) / Audio Output 1, RCA HDD Interface 2 SATA Port, up to 16TB for a single HDD RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000 DC12V, 5A / Power Consumption Lower than 17 W / Operating Temperature -10 °C to +55 °C</p>		278,450,000
107 XVR5432L-I3	<p>32 Channels Penta-brid 5M-N/1080P 4HDDs WizSense Digital Video Recorder H.265+/H.265 dual-stream video compression. Supports 16-channel AI-Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 32 channels IP camera, each channel up to 8MP; 128 Mbps bandwidth. Up to 8 channels video stream (analog channel) perimeter protection. Up to 16 channels video stream (analog channel) SMD plus. Up to 2 channels video stream (analog channel) human face recognition. Perimeter Protection, Face Detection, Face Recognition : Up to 10 face databases with 10,000 face images, SMD Plus Multi-screen Display 1/4/8/9/16/25/36 IoT &amp; POS functionalities.</p>		458,300,000
108 DH-XVR4232AN-I	<p>32 Channels Penta-brid 1080N/720P 1U 2HDDs WizSense Digital Video Recorder Video Compression AI Coding; H.265+; H.265; H.264+; H.264 Supports 8-channel AI-Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 16 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth. Multi-screen Display 1/4/8/9/16/25/36 Audio Input 1-channel RCA (external)32-channel BNC (coaxial audio) Two-way Talk, HDD Interface 2 SATA ports, up to 16 TB Up to 16 channels video stream (analog channel) SMD Plus. Long transmission distance over coax cable.</p>		186,000,000

**توجه:** دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.