

Hi-tech products price list

| Product image | Model | Description | Price |
|---|--------------|---|------------------|
|  | HIB-5514 | <ul style="list-style-type: none"> • 5 MP • 3.6 mm -5 MP/YTOT • 5053 GALAXY CORE-HS • 25 fps@5M • 25m IR lenght • DWDR • ONVIF • Metal • 12V-2A | 1,850,000 |
|   | HIB-4455-WA | <ul style="list-style-type: none"> • 4 MP • 3.6 mm -5 MP/YTOT • 4083 GALAXY CORE-HS • 25 fps@4M • 25m warm light lenght • DWDR • ONVIF, Internal MIC,POE • Metal • 12V-2A | 1,895,000 |
|   | HIB-4420-WA | <ul style="list-style-type: none"> • 4 MP • 3.6 mm -5 MP/YTOT • 4083 GALAXY CORE-HS • 25 fps@4M • 25m warm light lenght • DWDR • ONVIF, Internal MIC,POE • Metal • 12V-2A | 1,750,000 |
|   | HIB-4448-WAN | <ul style="list-style-type: none"> • 4 MP • 3.6 mm -5 MP/YTOT • 4083 GALAXY CORE-HS • 25 fps@4M • 25m warm light lenght • DWDR • ONVIF, Internal MIC • Metal • 12V-2A | 1,595,000 |

Full-color

Full-color

Full-color



HIB-4438-WA



- 4 MP
- **3.6 mm -5 MP/YTOT**
- 4083 GALAXY CORE-HS
- 25 fps@4M
- 25m warm light lenght
- DWDR
- ONVIF, **Internal MIC,POE**
- Metal
- 12V-2A

1,790,000



HIB-5255-WA



- 5 MP
- **3.6 mm -5 MP/YTOT**
- Chip: Mstar
- 25 fps@5M
- 25m warm light lenght
- ONVIF/ **Internal MIC/POE**
- Metal
- 12V-2A

2,095,000



HIB-5548-WA-2.8



- 5 MP
- **2.8 mm -5 MP/YTOT**
- 5053 GALAXY CORE-HS
- 25 fps@5M
- 25m warm light lenght
- DWDR
- ONVIF/ **Internal MIC /POE**
- Metal
- 12V-2A

2,085,000



HIB-5538-WA-2.8



- 5 MP
- **2.8 mm -5 MP/YTOT**
- 5053 GALAXY CORE-HS
- 25 fps@5M
- 25m warm light lenght
- DWDR
- ONVIF/ **Internal MIC /POE**
- Metal
- 12V-2A

2,085,000



HIB-5555-WA



- 5 MP
- **3.6 mm -5 MP/YTOT**
- 5053 GALAXY CORE-HS
- 25 fps@5M
- 25m warm light lenght
- DWDR
- ONVIF/ **Internal MIC /POE**
- Metal
- 12V-2A

2,120,000



HIB-5575-WA



- 5 MP
- **3.6 mm -5 MP/YTOT**
- 5053 GALAXY CORE-HS
- 25 fps@5M
- 25m warm light lenth
- DWDR
- ONVIF/ **Internal MIC /POE**
- Metal
- **Big Case**
- 12V-2A

2,600,000



HIB-5455-WA



- 5 MP
- **3.6 mm -5 MP/YTOT**
- Hisilicon
- 25 fps@5M
- 25m warm light lenth
- DWDR
- ONVIF/ **Internal MIC /POE**
- Metal
- 12V-2A

1,995,000



HIB-5648-WA



- 5 MP
- **3.6 mm -5 MP/YTOT**
- Chip: Mstar
- 25 fps@5M
- 25m warm light lenth
- **WDR-120db**
- ONVIF/ **Internal MIC/POE**
- Metal
- 12V-2A

Unavalible



HIB-5760-WA



- 5 MP
- **3.6 mm -5 MP/YTOT**
- Chip: Mstar
- 25 fps@5M
- 35m warm light lenth
- DWDR
- ONVIF / **Internal MIC /POE**
- Metal
- **Big Case**
- 12V-2A

2,690,000



HT-5566

- 5 MP
- **2.8-12 mm** -5 MP/YTOT
- 5053 GALAXY CORE-HS
- 25 fps@5M
- 35m IR Lenght
- DWDR
- ONVIF/POE
- Metal
- **Big Case**
- 12V-2A

3,195,000



HIB-5575-ZWA



- 5 MP
- **2.7-13.5 mm (Motorized)** 5 MP
- 5053 GALAXY CORE - HS
- 25 fps@5M
- 35m warm light lenght
- DWDR
- ONVIF / **Internal MIC**
- Metal
- **Big Case**
- 12V-2A

Unavalible



HIB-5375-ZWA



- 5 MP
- **5-50 mm (Motorized)** 5 MP
- **335 SONY**
- 25 fps@5M
- 35m warm light lenght
- **WDR(120db)**
- ONVIF / **Internal MIC**
- Metal
- **Big Case**
- 12V-2A

5,550,000

+
اسپيليتر
poe



5,760,000



HIB-5355-WA



- 5 MP
- **3.6 mm** -5 MP/ **Starlight**
- **335 SONY**
- 25 fps@5M
- 25m warm light lenght
- **HDR(120db)**
- ONVIF / **Internal MIC/POE**
- Metal
- 12V-2A

3,145,000





HIB-5375-WA



- 5 MP
- **3.6 mm** -5 MP/ **Starlight**
- **335 SONY**
- 25 fps@5M
- 35m warm light lenght
- **HDR(120db)**
- ONVIF / **Internal MIC/POE**
- Metal
- **Big Case**
- 12V-2A

3,550,000

| | | | |
|---|--|--|------------------|
|  |   HIB-5360-WA  | <ul style="list-style-type: none"> • 5 MP • 3.6 mm -5 MP/ Starlight • 335 SONY • 25 fps@5M • 35m warm light lenth • WDR(120db) • ONVIF / Internal MIC/POE • Metal • Big Case • 12V-2A | 3,595,000 |
|  |   HIB-8455-WA  | <ul style="list-style-type: none"> • 8 MP • 3.6 mm -8 MP/YTOT • Hisilicon • 25 fps@5M • 25m warm light lenth • DWDR • ONVIF/ Internal MIC /POE • Metal • 12V-2A | 2,950,000 |
|  |  HIB-8848-WA  | <ul style="list-style-type: none"> • 8 MP • 3.6 mm - 8MP/ Starlight • IMX415 SONY • 20 fps@4K • 35m warm light lenth • WDR(120db) • ONVIF/ Internal MIC/POE • Metal • 12V-2A | 4,850,000 |
|  |  HID-4405-WAN  | <ul style="list-style-type: none"> • 4 MP • 3.6 mm -5 MP/YTOT • 4083 GALAXY CORE-HS • 25 fps@4M • 25m warm light lenth • DWDR • ONVIF, Internal MIC • Plastic • 12V-2A | 1,395,000 |
|  |  HID-4405-WAN-2.8  | <ul style="list-style-type: none"> • 4 MP • 2.8 mm -5 MP/YTOT • 4083 GALAXY CORE-HS • 25 fps@4M • 25m warm light lenth • DWDR • ONVIF, Internal MIC • Plastic • 12V-2A | 1,430,000 |

| | | | | |
|--|--|------------------------|--|------------------|
| | | HID-4608-WA-2.8 | <ul style="list-style-type: none"> • 4 MP • 2.8 mm -5 MP/YTOT • 4083 GALAXY CORE-HS • 25 fps@4M • 25m warm light lenght • DWDR • ONVIF, Internal MIC, POE • Metal+Plastic • 12V-2A | 1,950,000 |
| | | HID-4403-WAN | <ul style="list-style-type: none"> • 4 MP • 3.6 mm -5 MP/YTOT • 4083 GALAXY CORE-HS • 25 fps@4M • 25m warm light lenght • DWDR • ONVIF, Internal MIC • Metal • 12V-2A | 1,595,000 |
| | | HID-4407-WAN | <ul style="list-style-type: none"> • 4 MP • 3.6 mm -5 MP/YTOT • 4083 GALAXY CORE-HS • 25 fps@4M • 25m warm light lenght • DWDR • ONVIF, Internal MIC • Metal • 12V-2A | 1,595,000 |
| | | HID-5208-WA-2.8 | <ul style="list-style-type: none"> • 5 MP • 2.8 mm -5 MP/YTOT • Chip: Mstar • 25 fps@5M • 25m warm light lenght • ONVIF, Internal MIC, POE • Metal+Plastic • 12V-2A | 2,095,000 |
| | | HID-5507-WA | <ul style="list-style-type: none"> • 5 MP • 3.6 mm -5 MP/YTOT • 5053 GALAXY CORE-HS • 25 fps@5M • 25m warm light lenght • DWDR • ONVIF, Internal MIC, POE • Metal • 12V-2A | 2,055,000 |

| | | | | | |
|--|--|------------------------|--|---|-------------------|
| | | HID-5507-WA-2.8 | | <ul style="list-style-type: none"> • 5 MP • 2.8 mm -5 MP/YTOT • 5053 GALAXY CORE-HS • 25 fps@5M • 25m warm light lenth • DWDR • ONVIF , Internal MIC, POE • Metal • 12V-2A | 2,075,000 |
| | | HID-5508-WA-2.8 | | <ul style="list-style-type: none"> • 5 MP • 2.8 mm -5 MP/YTOT • 5053 GALAXY CORE-HS • 25 fps@5M • 25m warm light lenth • DWDR • ONVIF , Internal MIC, POE • Metal+Plastic • 12V-2A | 2,120,000 |
| | | HID-5505-WAN | | <ul style="list-style-type: none"> • 5 MP • 3.6 mm -5 MP/YTOT • 5053 GALAXY CORE-HS • 25 fps@5M • 25m warm light lenth • DWDR • ONVIF/ Internal MIC • Plastic • 12V-2A | 1,695,000 |
| | | HID-5408-WA-2.8 | | <ul style="list-style-type: none"> • 5 MP • 2.8 mm -5 MP/YTOT • Hisilicon • 25 fps@5M • 25m warm light lenth • DWDR • ONVIF/ Internal MIC /POE • Metal • 12V-2A | 1,995,000 |
| | | HID-5607-WA-2.8 | | <ul style="list-style-type: none"> • 5 MP • 2.8 mm -5 MP/YTOT • Chip: Mstar • 25 fps@5M • 25m warm light lenth • WDR-120db • ONVIF , Internal MIC, POE • Metal • 12V-2A | Unavalible |

| | | | | | | |
|--|------------------------|-------------------------------|-----------------------|---|--|-------------------------|
| | | <p>HID-5307-WA-2.8</p> | | <ul style="list-style-type: none"> • 5 MP • 2.8 mm -5 MP/ Starlight • 335 SONY • 25 fps@5M • 25m warm light lenght • DWDR • ONVIF / Internal MIC /POE • Metal • 12V-2A | <p>3,095,000</p> | |
| | | <p>HID-5308-WA-2.8</p> | | | <ul style="list-style-type: none"> • 5 MP • 2.8 mm -5 MP/ Starlight • 335 SONY • 25 fps@5M • 25m warm light lenght • HDR (120 db) • ONVIF / Internal MIC /POE • Metal + Plastic • 12V-2A | <p>3,145,000</p> |
| | | <p>HID-8408-WA-2.8</p> | | | <ul style="list-style-type: none"> • 8 MP • 2.8 mm -5 MP/YTOT • Hisilicon • 25 fps@5M • 25m warm light lenght • DWDR • ONVIF/ Internal MIC /POE • Metal • 12V-2A | <p>2,950,000</p> |
| | <p>HNR-8916</p> | | <p>P6SLITE</p> | <ul style="list-style-type: none"> • Bandwidth:80 mb/s • Perview : 16*4K • Recording: 4K/5M/4M/1080P • H265/H264 • Hard drive 14T (1 Port) • P6SLITE • Support AI Function • ONVIF | <p>3,150,000</p> | |