


ردیف	مدل	شرح	توضیحات	عکس	قیمت مصرف کننده (ریال)
1	CP-E25A	2MP wifi Ezycamera	2MP Wi-Fi PT Camera - 10 Mtr. •1/4.5" 2MP CMOS Image Sensor (0.5644 cm) •3.6mm Lens Wi-Fi Support •H.264 Video Compression Support SD Card •128GB IR Distance of 10 Mtr. •Works with Alexa Works with Google Assistant		50,569,660
2	CP-E41A	4MP wifi Ezycamera	4MP Wi-Fi PT Camera - 15 Mtr. •1/2.8" 4MP CMOS Image Sensor (0.9071cm) •4mm Lens •H.265 Video Compression Wi-Fi Support •Max. 20fps@4MP •128GB, IR Distance of 15Mtr. •Works with Alexa Works with Google Assistant		63,212,074
3	CP-URC-DC24PL2-V3	2.4MP IR Dome Camera - 20Mtr	2.4MP IR Dome Camera - 20Mtr. •1/2.7" 2.4MP CMOS Image Sensor (0.9407 cm) •Max 25/30fps@2.4MP •DWDR, Day/Night (ICR), 2D-DNR, AWB, AGC, BLC, HLC •3.6mm fixed lens (2.8mm, 6mm optional) IR •Range of 20 Mtrs. •OSD Menu, control over coaxial cable, 2D-DNR HD, SD and Two Analog format Output switchable		29,009,827
4	CP-URC-TC24PL2-V3	2.4MP Bullet Camera - 20Mtr	2.4MP IR Bullet Camera - 20Mtr. • 1/2.7" 2.4MP CMOS Image Sensor (0.9407 cm) • Max 25/30fps@2.4MP • DWDR, Day/Night (ICR), 2D-DNR, AWB, AGC, BLC, HLC • 3.6mm fixed lens • IR Range of 20 Mtrs., IP67 • OSD Menu, control over coaxial cable, 2D-DNR • HD, SD and Two Analog format Output switchable		25,569,284
5	CP-LSC-T24ML3	2.4MP IR Bullet Camera - 30Mtr.	2.4MP Bullet Camera-30Mtr •1/3" CMOS Sensor , •AHD/TVI/CVI: 2M@30fps/25fps , Smart IR up to 30m , •Metal Body , IP67 , •DWDR, Day/Night (ICR), 3D-NR, AWB, AGC • 3.6mm fixed lens		30,215,372
6	CP-LSC-D24L3C-GP	2.4MP Full Color Guard+ Dome Camera - 30 Mtr	2.4MP Full Color Guard+ Dome Camera- 30Mtr •AHD/TVI/CVI: 2M@30fps/25fps,default TVI mode •1/3" CMOS Sensor •2M:1920*1080 •3.6mm fixed lens, 30m IR •DWDR, 3DNR, AGC auto control •IP67 •Metal housing •Mobile Software: sMOB CMS Software: SVMS Pro		35,588,398
7	CP-VAC-T20FL4	2MP Full HD IR Bullet Camera - 40Mtr	2MP Full HD Bullet Camera-40Mtr •1/2.9" , 2MP HQIS Pro Image Sensor •25 / 30 FPS @ 2MP •DWDR / Day & Night (ICR) , 2DNR , AWB ,AGC , BLC •2.8-12 mm VF Lens , IR Range 40m , IP66 •Compatible with HDx / AHD , HDCVI , HDTVI , CVBS DVR •Metal Body		31,195,159
8	CP-VAC-T24FL4-T	2MP Full HD IR Bullet Camera - 40Mtr	2.4MP Full HD Bullet Camera- 40Mtr •1/2.9" , 2MP HQIS Pro Image Sensor •25 / 30 FPS @ 2MP •DWDR / Day & Night (ICR) , 2DNR , AWB ,AGC , BLC •2.8-12 mm VF Lens , IR Range 40m , IP66 •Compatible with HDx / AHD , HDCVI , HDTVI , CVBS DVR •Metal Body		31,195,159
9	CP-GPC-D24L2-S	2.4MP Full Color Guard+ Dome Camera - 20 Mtr	2.4MP Full HD Guard+ Dome Camera - 20 Mtr. •1/2.9" 2.4MP CMOS Image sensor 25/30fps@2.4MP •DWDR, 2D/3D-DNR, AWB, AGC, BLC •3.6mm lens •Support low illumination, warm light day night full color Illumination Range of 20 Mtr., IP66		33,628,824

ردیف	مدل	شرح	توضیحات	عکس	قیمت مصرف کننده (ریال)
10	CP-GPC-DA24PL2C-SE	2.4MP Full Color Guard+ Dome Camera - 20 Mtr	2.4MP Full-color Guard+ Dome Camera - 20Mtr. • 1/2.8" 2.4MP CMOS Image Sensor Max 30fps@2.4MP • DWDR, 2D-DNR, AWB, AGC, BLC • 3.6mm Fixed lens, IP67 • Illumination Range of 20 Mtrs, IP67 Support Full-color starlight CVI/CVBS/AHD/TVI switchable		33,628,824
11	CP-LSC-T24L3C-GP	2.4MP Full Color Guard+ Bullet Camera - 30 Mtr	2.4MP Full Color Guard+ Bullet Camera - 30 Mtr • 1/3" CMOS Sensor , • AHD/TVI/CVI: 2.4MP@30fps/25fps , • Warm light up to 30m , Metal+Plastic Body , IP67, • Built in Mic, • DWDR, Day/Night (ICR), 3D-NR, AWB, AGC • 3.6mm fixed lens		34,608,611
12	CP-LSC-T50ML5C	5MP IR Bullet Camera - 50Mtr	5MP IR Bullet Camera - 50Mtr. • 1/2.5" 5MP PS CMOS Image Sensor (1.016 centimeters • Max. 5MP (2592 x 1944)@20/12.5fps • DWDR, Day/Night, AGC, 2D DNR • 3.6mm Fixed Lens • IR Range of 50 Mtr., IP67 • Built-in Mic • Support OSD Menu • Metal Body • AHD/TVI: 5M@20fps/12.5fps • CVI: 4M/2M@30fps/25fps		41,719,969
13	CP-UVC-VB20L3-D	2 MP IR Dome Camera - 30Mtr	2.4MP IR Bullet Camera - 20Mtr. • 1/2.7" 2.4MP CMOS Image Sensor (0.9407 cm) • Max 25/30fps@2.4MP • DWDR, Day/Night (ICR), 2D-DNR, AWB, AGC, BLC, HLC • 3.6mm fixed lens • WDR • IR Range of 30 Mtrs., IP67 • OSD Menu, control over coaxial cable, 2D-DNR • HD, SD and Two Analog format Output switchable		42,700,659
14	CP-ENC-D21PL3C-GP	2MP Full-Color Guard+ Network Dome Camera - 30Mtr	2MP Full-Color Guard+ Network Dome Camera - 30Mtr. • 1/3" 2MP PS CMOS Image Sensor • 1920(H) x 1080(V) @30fps • H.265/H.264/JPEG/AVI/MJPEG • DWDR, BLC, HLC, White Balance • 3.6mm • Built in Mic • Illumination Distance of 30 Mtr. , PoE • Mobile Software: sMOB • CMS Software: SVMS Pro		57,793,897
15	CP-ENC-T21PL3C-GP	2MP Full-Color Guard+ Network Bullet Camera - 30Mtr	2MP Full-Color Guard+ Network Bullet Camera - 30Mtr. • 1/3" 2MP PS CMOS Image Sensor • 1920(H) x 1080(V) @30fps • H.265/H.264/JPEG/AVI/MJPEG • DWDR, BLC, HLC, White Balance • 3.6mm • Built in Mic • Illumination Distance of 30 Mtr. , PoE • Mobile Software: sMOB • CMS Software: SVMS Pro		62,610,055
16	CP-UNC-TA21L2-GP-V2	2MP Full-Color Guard+ Network Bullet Camera - 20Mtr	2MP Full-color Guard+ Network Bullet Camera • 1/2.8" 2Megapixel PS CMOS Image Sensor (7.112 centimeters) • Max. 2MP(1920 x 1080)@25/30fps • Smart H.265+ and Smart H.264+ dual-stream encoding DWDR, Day/Night (ICR), 3D-DNR, ROI, AWB, AGC, BLC, HLC • 3.6mm fixed lens • Support IP67, PoE • Built-in efficient LED illuminator, and the max. illumination distance is 20Mtr. • Mobile Software: iCMOB, gCMOB CMS Software: KVMS Pro		65,740,557
17	CP-LSC-T50L5C-GP	5MP Full color Bullet Camera 3.6mm, 50M IR, Mic	5MP IR Bullet Camera - 50Mtr. • 1/2.5" 5MP PS CMOS Image Sensor (1.016 centimeters • Max. 5MP (2592 x 1944)@20/12.5fps • DWDR, Day/Night, AGC, 2D DNR • 3.6mm Fixed Lens • IR Range of 50 Mtr., IP67 • Built-in Mic • Support OSD Menu • Metal Body • AHD/TVI: 5M@20fps/12.5fps • CVI: 4M/2M@30fps/25fps		66,562,314

ردیف	مدل	شرح	توضیحات	عکس	قیمت مصرف کننده (ریال)
18	CP-ENC-D51PL3C-GP	5MP Full-Color Guard+ Network Bullet Camera - 30Mtr	5MP Full-color Guard+ Network Dome Camera - 30Mtr. • 1/3" 5MP PS CMOS Image Sensor • 2880(H) x 1620(V)@30fps • H.265/H.264/JPEG • DWDR, BLC, 3D-NR, White Balance • 2.8mm fixed lens • Built in Mic, IP67 • Illumination Range of 30 Mtr., PoE • Mobile Software: sMOB • CMS Software: sVMS Pro		91,175,892
19	CP-ENC-T51PL3C-GP	5MP Full-Color Guard+ Network Bullet Camera - 30Mtr	5MP Full-color Guard+ Network Bullet Camera - 30Mtr. • 1/2.7" 5MP PS CMOS Image Sensor • 2880(H) x 1620(V)@30fps • H.265/H.264/JPEG • DWDR, BLC, 3D-NR, White Balance • 3.6mm fixed lens • Built in Mic • Illumination Range of 30 Mtr. IP66, PoE • Mobile Software: sMOB • CMS Software: sVMS Pro		91,175,892
20	CP-LSC-D50ML3C	5MP IR Dome Camera - 30Mtr.	5MP IR Dome Camera - 30Mtr. Metal is casing 1/2.5" 5MP PS CMOS Image Sensor (1.016 centimeters) • Max. 5MP (2592 x 1944)@20/12.5fps • DWDR, Day/Night, AGC, 2D DNR • 3.6mm Fixed Lens • IR Range of 30 Mtr., IP67 • Built-in Mic • Support OSD Menu • AHD/TVI: 5M@20fps/12.5fps • CVI: 4M/2M@30fps/25fps		41,719,969
21	CP-LSC-D50ML3C-GP	5MP Full Color Guard+ Dome Camera - 30 Mtr.	5MP Full-color Guard+ Bullet Camera - 30M. • 1/2.5" 5MP PS CMOS Image Sensor (1.016 centimeters) • Max. 5MP (2592 x 1944)@20/12.5fps • DWDR, Day/Night, 2D DNR, AWB, AGC • Built-in Mic • 3.6mm Fixed Lens • Warm Light Range of 30 Mtr., IP67 • Support OSD Menu • AHD/TVI: 5M@20fps/12.5fps • CVI: 4M/2M@30fps/25fps		66,246,254
22	CP-LNC-DC51ML3-D-L	5MP Dual Light Network Dome Camera - 30Mtr	5MP IR Dual light + Network Dome Camera - 30Mtr. • 1/2.8" 5MP PS CMOS Image Sensor • Max. 5MP (2592 x 1944)@30fps • H.265 and H.264 dual-stream encoding • WDR(120dB), Day/Night, ROI, BLC • 2.8mm fixed lens, IP67 • Warm Light Range of 30 Mtrs, PoE • Mobile Software: sMOB • CMS Software: sVMS Pro		106,670,376
23	CP-LNC-TC51ML4-VD-L	5MP Dual Light Network Bullet Camera - 30Mtr	5MP IR Dual light + Network Bullet Camera - 30Mtr. • 1/2.8" 5MP PS CMOS Image Sensor • Max. 5MP (2592 x 1944)@30fps • H.265 and H.264 dual-stream encoding • WDR(120dB), Day/Night, ROI, BLC • 3.6mm fixed lens, IP67 • Warm Light Range of 30 Mtrs, PoE • Mobile Software: sMOB • CMS Software: sVMS Pro		122,036,027
24	CP-LNC-D51L3-VMD-GP	5MP Full-Color Guard+ Network Dome Camera - 30Mtr	5MP Full-Color Guard+ Network Dome Camera - 30Mtr. • 1/2.8" 5MP PS CMOS Image Sensor • Max. 5MP (2592 x 1944)@30fps • H.265 and H.264 dual-stream encoding • WDR(120dB), Day/Night, ROI, BLC • 2.8mm fixed lens • Warm Light Range of 30 Mtrs, PoE • Mobile Software: sMOB • CMS Software: sVMS Pro		113,781,734
25	CP-LNC-T51PL3-VMD-GP	5MP Full-Color Guard+ Network Bullet Camera - 30Mtr	5MP Full-Color Guard+ Network Bullet Camera - 30Mtr. • 1/2.8" 5MP PS CMOS Image Sensor • Max. 5MP (2592 x 1944)@30fps • H.265 and H.264 dual-stream encoding • WDR(120dB), Day/Night, ROI, BLC • 3.6mm fixed lens • Warm Light Range of 30 Mtrs, PoE • Mobile Software: sMOB • CMS Software: sVMS Pro		113,781,734

ردیف	مدل	شرح	توضیحات	عکس	قیمت مصرف کننده (ریال)
26	CP-VNC-T41ZR5C-MD	4MP IP Bullet camera 2.8~12mm Motorized lens - 50Mtr.	4MP WDR Array Network Bullet Camera - 50Mtr. •1/3" 4Megapixel PS CMOS Image Sensor (0.8467 centimeter) •Max 25/30fps@4MP •Ultra 265, H.265, H.264, MJPEG triple-stream encoding •WDR(120dB), Day/Night (ICR), 2D/3D-DNR, 9:16 Corridor Mode, Digital Defog, ROI, AWB, AGC, BLC, HLC 2.8~12mm Motorized lens •Array Range of 50 Mtrs, •Micro SD Card, IP67, PoE •Support Instastream technology, save disk space and bandwidth upto 70% Built-in Mic •Mobile Software: Android, iOS CMS Software: IVMS		244,043,759
27	CP-UVR-0401K1-I3-V3	04Ch. 5M-N Digital Video Recorder,	4Ch. 5M-N Digital Video Recorder • Supports HDCVI/AHD/TVI/CVBS/IP video inputs. • Instastream/H.265 dual-stream video compression. • Max 6 channels IP camera inputs, each channel up to 6MP; Max 32 Mbps incoming bandwidth. • Up to 1 channels video stream (analog channel) Perimeter Protection. • Up to 4 channels video stream (analog channel) SMD Plus. • Up to 1 channels video stream (analog channel) human face recognition. • Support 1 SATA HDDs up to 6TB each, 2 USB Ports • 1 HDMI / 1 VGA simultaneous video output. • Mobile Software: iCMOB, gCMOB. • CMS Software: KVMS Pro.		110,557,918
28	CP-UVR-0401E1-IC2	4Ch. 1080N Digital Video Recorder	4Ch. 1080N Digital Video Recorder • Supports HDCVI/AHD/TVI/CVBS/IP video inputs • Max 5 channels IP camera inputs, each channel up to 2MP; Max 20Mbps Incoming Bandwidth • Supports Full-channel AI Instastream • Instastream/H.265 dual-stream video compression • Up to 4 channels video stream (analog channel) SMD Plus. • Support 1 SATA HDD up to 6TB, 2 USB Ports • 1 HDMI / 1 VGA Simultaneous Video Output • Mobile Software: iCMOB, gCMOB • CMS Software: KVMS Pro Lite		59,261,320
29	CP-LAR-0401E1	4Ch. 1080N Digital Video Recorder	4CH- DIGITAL VIDEO RECORDER - Embedded processor TVI/AHD/CVI/CVBS @ 2MP 1 HDMI / 1VGA Support (Max. resolution 1080P) output H265/H264 1080N/960P/720P/960H/D1 1 SATA, Up to 8TB capacity - ALL, Timing Video, Motion Detection, Tag search, Smart Event, Picture, Log		59,261,320
30	CP-UVR-0801E1-IC	8Ch. 1080N Digital Video Recorder	8Ch. 1080N Digital Video Recorder • Supports HDCVI/AHD/TVI/CVBS/IP video inputs - Max 10 channels IP camera inputs, each channel up to 6MP; Max 40Mbps Incoming Bandwidth • Supports Full-channel AI-Coding • Instastream/H.265 dual-stream video compression • Up to 4 channels video stream (analog channel) SMD Plus. • Support 1 SATA HDD up to 6TB, 2 USB Ports 1 •HDMI / 1 VGA Simultaneous Video Output - Mobile •Software: iCMOB, gCMOB •CMS Software: KVMS Pro		73,484,036
31	CP-LAR-0801E1	8Ch. 1080N Digital Video Recorder	8CH- DIGITAL VIDEO RECORDER •Embedded processor •TVI/AHD/CVI/CVBS @ 2MP •1 HDMI / 1VGA Support (Max. resolution 1080P) output H265/H264 •1080N/720P/960H/D1 •1 SATA, Up to 8TB capacity •ALL, Timing Video, Motion Detection, Tag search, Smart Event, Picture, Log		73,452,430
32	CP-LNR-4K3041	4Ch. Network Video Recorder	4CH- NETWORK VIDEO RECORDER •Industrial-grade embedded processor 80Mbps •1 HDMI (Max. resolution 1080P) output •H265/H264/H265+/H264+ •8MP/ 6MP/5MP/4MP/3MP/1080P/960P/720P/ 960H/D1 •1 SATA, Up to 8TB capacity •ALL, Timing Video, Motion Detection, Tag search, Smart Event, Picture, Log		82,514,333
33	CP-LNR-4K3091	9Ch. Network Video Recorder	9CH- NETWORK VIDEO RECORDER •Industrial-grade embedded processor 128Mbps •1 HDMI (Max. resolution 1080P) output •H265/H264/H265+/H264+ •8MP/ 6MP/5MP/4MP/3MP/1080P/960P/720P/ 960H/D1 •1 SATA, Up to 8TB capacity •ALL, Timing Video, Motion Detection, Tag search, Smart Event, Picture, Log		108,092,647

ردیف	مدل	شرح	توضیحات	عکس	قیمت مصرف کننده (ریال)
34	CP-UVR-0801K1-I3-V3	08Ch. 5M-N Digital Video Recorder,	4Ch. 5M-N Digital Video Recorder • Supports HDCVI/AHD/TVI/CVBS/IP video inputs. • Instastream/H.265 dual-stream video compression. • Max 12 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps incoming bandwidth. • Up to 1 channels video stream (analog channel) Perimeter Protection. • Up to 8 channels video stream (analog channel) SMD Plus. • Up to 1 channels video stream (analog channel) human face recognition. • Support 1 SATA HDDs up to 10TB each, 2 USB Ports • 1 HDMI / 1 VGA simultaneous video output. • Mobile Software: iCMOB, gCM		150,255,101
35	CP-UVR-0801K1-I3-V3	8Ch. Network Video Recorder with 8PoE Port	8Ch. Network Video Recorder with 8PoE Port •Support 8 channel IP camera input •Instastream/H.265/Smart H.264+/H.264 codec decoding Up to 8MP resolution preview and playback •Max 80Mbps Network Bandwidth •Support 1 SATA HDDs up to 8TB Each, 2 USB Ports (USB2.0) VGA/HDMI simultaneous video output, maximum resolution of HDMI is 1080P •Support Multi-brand network cameras ONVIF Version conformance •Support 8 PoE Ports Mobile Software: iCMOB, gCMOB CMS Software: KVMS Pro •Only for Middle East/ Africa/ EU Region		150,255,101
36	CP-LNR-4K3162	16Ch. AI Network Video Recorder	16Ch. AI Network Video Recorder •16 Channel IP video access •Instastream /H.265/Smart H.264+ /H.264/MJPEG - Max. decoding capability: 6 × 1080p@30fps. •Supports adaptive decoding •1-channel face detection and recognition (AI by NVR); 1-channel perimeter protection (AI by NVR); up to 10 face databases and 5,000 face images •AI by camera: Face detection and recognition, perimeter protection and SMD Support 2 SATA •HDDs up to 10TB Each, 2 USB Ports •Support Multi-brand network cameras Mobile •Software: iCMOB, gCMOB CMS Software: KVMS Pro		223,328,259
37	CP-UVR-0801L1-4KI3-V2	8Ch. 5MP Digital Video Recorder	8Ch. 5M-N Digital Video Recorder • Supports HDCVI/AHD/TVI/CVBS/IP video inputs. • Instastream/H.265 dual-stream video compression. • Max 12 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps incoming bandwidth. • Up to 1 channels video stream (analog channel) Perimeter Protection. • Up to 8 channels video stream (analog channel) SMD Plus. • Up to 1 channels video stream (analog channel) human face recognition. • Support 1 SATA HDDs up to 10TB each, 2 USB Ports • 1 HDMI / 1 VGA simultaneous video output. • Mobile Software: iCMOB, gCMOB. • CMS Software: KVMS Pro.		234,232,342
38	CP-UNR-4K4322-FI	32Ch. 4K Network Video Recorder	32Ch. AI Network Video Recorder •32 Channel IP video access •Instastream /H.265/Smart H.264+ /H.264/MJPEG •Max. decoding capability: 16 × 1080p@30fps. •Supports adaptive decoding •1-channel face detection and recognition (AI by NVR); 1-channel perimeter protection (AI by NVR); up to 10 face databases and 5,000 face images •AI by camera: Face detection and recognition, perimeter protection and SMD Support 2 SATA •HDDs up to 10TB Each, 2 USB Ports •Support Multi-brand network cameras Mobile •Software: iCMOB, gCMOB CMS Software: KVMS Pro		342,085,686
39	CP-UNR-4K5162-FI	16Ch. 4K AI Network Video Recorder	16Ch. 4K AI Network Video Recorder •Up to 16 channel IP camera input •Max. 384 Mbps incoming/recording/outgoing bandwidth Instastream/H.265/Smart H.264+/H.264/MJPEG codec decoding •AI by Recorder: 2-channel face detection or recognition/ 4-channel perimeter protection/ 8- channel SMD Plus. • AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting •Support 2 SATA HDDs up to 16TB Each, 2 USB Ports (1 USB 3.0) HDMI/ VGA simultaneous video output •Support Multi-brand network cameras Mobile •Software: iCMOB, gCMOB CMS Software: KVMS Pro		458,287,539
40	CP-LNR-4K3162	16Ch. 4K Network Video Recorder	16 CH 2SATA Network Video Recorder - Support Up to 12MP Resolution • H265/H264/H265+/H264+ Video Compression • Max Incoming Bandwidth 160Mbps • 2 SATA Port, Up to 10TB capacity • Support HDMI/VGA, 2 USB Ports •AI by Camera: Intrusion Detection, Tripwire, Loiter Detection, People Gather Detection, Motion detection based on human detection, Enter Area, Leave Area, Face Detection		223,328,259
41	CP-UVR-1601L1B-4KI3	16Ch. 4K-N/5MP Digital Video Recorder	16Ch. 4K-N/5MP Digital Video Recorder •Supports HDCVI/AHD/TVI/CVBS/IP video inputs •AI Instastream/ Instastream/ H.265 dual-stream video compression •Max 32 channels IP camera inputs, each channel up to 8MP; Max 128Mbps incoming bandwidth Up to 8 channels video stream (analog channel)Perimeter Protection •Up to 16 channels video stream (analog channel) SMD Plus •Up to 2 channels video stream (analog channel) human face recognition Support 1 SATA HDDs up to 16TB Each, 2 USB Ports •1 HDMI / 1 VGA simultaneous video output Mobile •Software: iCMOB, gCMOB •CMS Software: KVMS Pro		461,479,749

ردیف	مدل	شرح	توضیحات	عکس	قیمت مصرف کننده (ریال)
42	CP-UNR-4K5322-FI	32Ch. 4K AI Network Video Recorder	32Ch. 4K AI Network Video Recorder •Up to 32 channel IP camera input •Max. 384 Mbps incoming/recording/outgoing bandwidth Instastream/H.265/Smart H.264+/H.264/MJPEG codec decoding •AI by Recorder: 2-channel face detection or recognition/ 4-channel perimeter protection/ 8- channel SMD Plus. •AI by Camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting •Support 2 SATA HDDs up to 16TB Each, 2 USB Ports (1 USB 3.0) HDMI/ VGA simultaneous video output •Support Multi-brand network cameras Mobile •Software: iCMOB, gCMOB		506,202,292
43	CP-UNR-4K532R8-FI	32Ch. 4K AI Network Video Recorder	32Ch. 4K AI Network Video Recorder •Up to 32 channel IP camera input •Max. 384 Mbps incoming/recording/outgoing bandwidth Instastream/H.265/Smart H.264+/H.264/MJPEG codec decoding •AI by Recorder: 2-channel face detection or recognition/ 4-channel perimeter protection/ 8- channel SMD Plus. •Support 8 SATA HDDs up to 16TB Each, 4 USB Ports (2 USB 3.0) •AI by Camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting •Support RAID 0/1/5/6/10 Support Multi-brand network cameras •Mobile Software: iCMOB, gCMOB CMS Software: •KVMS Pro		986,519,239
44	CP-UNR-4K564R8-V2	64 Ch. 4K Network Video Recorder	64 Ch. 4K Network Video Recorder •Up to 64 channel IP camera input •Up to 12MP resolution preview and playback •Max 320Mbps incoming bandwidth •Instastream/H.265/Smart H.264+/H.264/MJPEG •Analytics By Camera: ANPR, People Counting, Tripwire, Intrusion, Heatmap, Missing Abandon Detection, Face Detection, Face Recognition •Support 8 SATA HDDs up to 16TB Each, 4 USB Ports (2 USB3.0), 1 eSATA port 2 HDMI / 2 VGA simultaneous video output •Support Multi-brand network cameras Support •RAID 0/1/5/10 •ONVIF Version 2.4 conformance Mobile Software: iCMOB, gCMOB CMS Software: KVMS Pro		1,076,356,239
45	CP-UNR-4K564R8-FI	64Ch. AI Network Video Recorder	64Ch. AI Network Video Recorder •Up to 64 channel IP camera input •Max. 384 Mbps incoming/recording/outgoing bandwidth •Instastream/H.265/Smart H.264+/H.264/MJPEG codec decoding •AI by recorder: 2-channel face detection or recognition/ 4-channel perimeter protection/ 8- channel SMD Plus. •Support 8 SATA HDDs up to 16TB Each, 4 USB Ports (2 USB 3.0) •AI by Camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting Support RAID 0/1/5/6/10 Support N+M cluster •Mobile Software: iCMOB, gCMOB CMS Software: KVMS Pro		1,155,335,211
46	CP-ANW-HPU8H2-N12	8 Port PoE + 2 Uplink Port PoE Switch	8 Port PoE + 2 Uplink Port PoE Switch •Networking standard: IEEE 802.3i 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3x Flow Control, IEEE 802.3af/at/bt Power over Ethernet •Support 6KV lightning protection, 8KV surge protection. •PoE Power Budget : 120W. Support bt 60W High Power (PoE Port 7~8).		102,042,349
47	CP-ANW-HP16G2F1-N30	16EP+2G+1SFP AI PoE Switch	CP-ANW-HP16G2F1-N30 16EP+2G+1SFP AI PoE Switch •Using CAT.5 network patch cords support power for the wireless AP and IP camera Networking standard: IEEE802.3af/at/bt •PoE Watchdog AI Function: Detection front-end PoE cameras and PD, Automatic detection, Automatic restart Upload port automatic flip (Auto MDI / MDIX) •FE ports can support 250 meters long distance transmission automatically 6KV lightning protection, 8KV surge protection, anti-reverse connection, over-current protection, over-voltage protection, over-temperature protection, Short circuit protection •The port Max power Output is 60 watts, it is convenient for high-power device Zero configuration feature power supply is automatically supplied to the adaptive equipment		243,366,486
48	CP-DNW-HPU24G2F1-30	27 Ports Switch with 24 PoE Ports & 2 Gigabit + 1 SFP Uplink Port	•Using CAT.5 network patch cords support power for the wireless AP/CPE and PTZ/IP camera •Networking standard: IEEE802.3af/at/bt •PoE Watchdog AI Function: Detection front-end PoE cameras and PD, Automatic detection, Automatic restart •Upload port automatic flip (Auto MDI / MDIX) 6KV lightning protection, 8KV surge protection, anti-reverse connection, over-current protection, over-voltage protection, over-temperature protection, Short circuit protection •Max. output power of the port is 60 watts, it is convenient for high-power device •Zero configuration feature power supply is automatically supplied to the adaptive equipment		294,613,418