

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
1 PSD81602-A360	8x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Eight 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 2x25fps@4096x1800+50/60fps@1080P Support 360-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking, Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out, 7/2 channel Alarm In/Out RS485, Micro SD memory, IP67, IK10		Call
2 PSD8802-A180	4x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Four 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 25fps@4096x1800+50/60fps@1080P Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking, Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out, 7/2 channel Alarm In/Out RS485, Micro SD memory, IP67, IK10		Call
3 SDT4E425-4F-GB-A-PV1	X-Spans 4MP+4MP 25x TiOC WizSense Network PTZ Camera Panorama: 1/2.8" 4Megapixel F1.0 CMOS Detail: 1/2.8"4Megapixel STARVIS™ CMOS 25x optical zoom, Max. 25/30fps@4M, IR distance up to 100 m Active deterrence, Auto tracking 3.0, Smart tracking, Perimeter protection, Smart dual light + Panorama: 0.001 lux@F1.0 (Color, 30 IRE); 0.0005 lux@F1.0 (B/W, 30 IRE); 0 lux (illuminator on); Detail: 0.005 lux@F1.6 (Color, 30 IRE); 0.0005 lux@F1.6 (B/W, 30 IRE); 0 lux (illuminator on) FoV Panorama: H: 101° Detail: H: 51.9°, Auto Focus Preset 300, Tour 8, Pattern 5, Scan 5 SMD 4.0, Quick Pick, Tripwire; intrusion; climbing fences; loitering detection; abandoned/missing object; fast moving; parking detection; people gathering; vehicle/human alarm classification; linking the detail camera to track objects Light Warning, Sound Warning 3 Streams, H.265+, WDR 120db, HLC, BLC, AWB, AGC, 3D DNR, Rol, EIS, Defog Micro SD 512GB, Audio I/O 1/1, Alarm I/O 2/1 12VDC, PoE+, TVS 6000 V lightning proof;IP66; surge protection; voltage transient protection		520,300,000
4 IPC-PFW3849S-A180-AS-PV	2x4MP TiOC Duo Splicing Fixed-focal Bullet WizSense Network Camera Dual 1/2.7" Progressive CMOS Sensor, 2.8mm Fixed Lens Outputs 180° wide angle splicing image, max. 8 MP (4096 × 1860)@20 fps H.265 codec, high compression rate, ultra-low bit rate, 3 Streams IR 25m, Warmlight 20m, 0.005 lux@F1.4 (Color, 30 IRE) 0.0005 lux@F1.4 (B/W, 30 IRE) 0 lux (illuminator on) WDR 120db, SSA, 3D NR, HLC, BLC, AGC, AWB, 3D DNR, Rol, Micro SD 256GB, Audio I/O 1/1, Alarm I/O 1/1, Dual Mic, Speaker, Two Way Talk EPTZ, SMD 4.0, arm & disarm option, Intrusion, tripwire, Quick Pick, Sound Warning, Light Warning(Red and Blue Light) 12VDC, IP67, Metal Case		215,300,000
5 PFW8800-A180	4x2MP Multi-Sensor Panoramic Network IR Bullet Camera Four 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x1800, 3.0mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/2 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+		Call
6 PFW8601-A180	3x2MP Multi-Sensor Panoramic Network IR Bullet Camera Three 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x832, 3.6mm fixed lens, Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+		Call
7 PDBW8800-A180	4x2MP Multi-Sensor Panoramic Network IR Dome Camera Four 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Max 25fps@4096x1800, 3.0mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+		Call

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
8 IPC-EBW8842-AS	8MP IR Fisheye WizMind Network Camera 8MP 1/1.7" CMOS image sensor, low luminance, and high definition image Min. Illumination 0.01 Lux@F2.0 (Color, 30 IRE), 0.001 Lux@F2.0 (B/W, 30 IRE), 0 Lux (Illuminator on) Focal Length 1.85mm, Field of View Horizontal: 185°; Vertical: 180° Outputs max. 8M (3280 × 2480) @25/30 fps Built-in IR LED, and the max. illumination distance is 10 m IVS: Intrusion, tripwire, heat map, people counting, Smart Search DWDR, HLC, BLC, AWB, AGC, 3D DNR, Rol, Defog, ICR, SMART H.264 +/-H.265+ Built-in Dual Array Mic and Speaker, Audio in/out 1/1, Alarm in/out 2/2, Micro SD 256GB 12V DC/PoE, IP67 and IK10 protection		470,600,000
9 ITC237-PW1B-IRZ	دوربین ANPR با قابلیت تشخیص پلاک، مناسب برای ورودی های پارکینگ 2 Megapixel Full HD WDR Access ANPR Camera -Embedded with LPR algorithm inside the camera -plate cutout, snapshot preview, recording -White list database, 1 ch relay out to control the barrier performance for outdoor applications- 1/2.8" 2Megapixel progressive scan CMOS H.265/H.264M/H.264H/H.264B dual-stream encoding 25/30fps@1080P(1920×1080), 2.7mm~12mm Motorize lens WDR(140dB),BLC,HLC,Day/Night(ICR),3DNR,AWB,AGC,BLC Mirco SD card 64GB, IR Distance 3~8m, IP67, IK10, PoE		263,600,000
10 IPCS831EP-ZE	1/2.5" 8 Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-stream encoding 15fps@4K(3840×2160), 25/30fps@3Mp(2304×1296) 2.7mm ~12mm motorized lens, Max. Aperture F1.6 WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card memory , 128 GB, 1/1 Audio In/Out, 2/1 Alarm In/Out Max. IR LEDs Length 50m , Smart IR, IP67, IK10, PoE (Tripwire Intrusion Object Abandoned/Missing Face)		198,100,000
11 IPC-HFW2849T-ZAS-IL	8MP Smart Dual Light Vari-focal Bullet WizSense Network Camera 8-MP 1/2.7" Progressive CMOS, max. 8MP@20 fps/4MP@25/30fps, 2.7-13.5mm Min. Illumination 0.008 lux@F1.5 (Color, 30 IRE) 0.0008 lux@F1.5 (B/W, 30 IRE) 0 lux (Illuminator on) WDR 120db, 3D DNR, HLC, BLC, AWB, AGC, ROI, SMART H.264+/H.265+, Smart Dual Light 60m SMD+, Intrusion, Tripwire, MSD256GB, Audio I/O 1/1, A;arm I/O 1/1, Built-in Mic IP67, IK10, 12 VDC/PoE, Metal		191,400,000
12 IPC-HFW2849T-AS-IL	8MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera 8-MP 1/2.7" Progressive CMOS image sensor, 8MP(3840×2160)@20fps, (2688×1520)@25/30fps Min. Illumination 0.008 Lux@F1.6 (Color, 30 IRE) 0.0008 Lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on) Illumination Distance up to 60 m (195.85 ft) (IR) up to 50 m (164.04 ft) (Warm light) Smart H.265+; Smart H.264+ high compression rate, ultra-low bit rate Intelligent monitoring: Intrusion, tripwire, SMD Plus Rol, WDR 120db, HLC, BLC, AWB, AGC, 3D DNR, Smart illumination Alarm in/out 1/1, Audio in/out 1/1, Built-in Mic, Micro SD 256GB 12 VDC/PoE, IP67, IK10, Metal Case		142,150,000
13 IPC-HFW2831T-ZAS-S2	8MP Lite IR Vari-focal Bullet Network Camera 8MP, 1/2.7" Progressive CMOS low illuminance 0.008 Lux@F1.5 high image definition 8MP@15fps & 4MP@25/30fps 2.7-13.5mm Motorized Lens SMART H.264+/H.265+, (MJPEG in Sub Stream) IVS Intrusion, Tripwire Micro SD 256GB, 1ch Audio I/O, 1ch Alarm I/O WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 4 IR LEDs 60m Distance, Onvif Profile S/G/T		158,050,000
14 HFW2831T-ZS-S2	8MP Lite IR Vari-focal Starlight Bullet Network Camera 1/2.7" progressive scan CMOS image sensor, low illuminance, high image definition Smart H.265/H.264 codec, MJPEG, high compression rate, ultra-low bit rate 8MP (3840 × 2160) @15 fps, 2688×1520 @25/30 fps WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Region of Interest, Voltage Detection 2.7 mm~13.5 mm Motorized fixed lens Max. IR LEDs Length 60m, Micro SD card memory , 256 GB IP67, PoE, Smart Detection (Tripwire Intrusion)		156,250,000
15 IPC-HFW2831TP-AS-S2	8MP Lite IR Fixed-focal Bullet Network Camera 8MP, 1/2.7" CMOS image sensor max. 8MP (3840 × 2160) @15 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps Smart H.265+/ Smart H.264+, H.265; H.264; H.264B; MJPEG (only supported by the sub stream) Built-in IR LED, max IR distance: 80m; 3.6mm Fixed Lenz Min. Illumination 0.009 Lux@F2.0 ONVIF (Profile S/Profile G/Profile T); CGI; Milestone; Genetec WDR(120db), 3D NR, HLC, BLC, AGC, AWB, Rol, Smart IR Intrusion, tripwire Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card 12V DC/POE power support supply, IP67, IK10		116,700,000

رقم	نموذج	مواصفات فنية	تصوير	سعر (ريال)
16	IPC-HFW2831S-S-S2	8MP Lite IR Fixed-focal Bullet Network Camera 1/2.7" Progressive CMOS image sensor, low illuminance, high image definition Illumination 0.009 Lux@F2.0 SMART H.264+/H.265+, MJPEG, high compression rate, ultra-low bit rate 8MP (3840 × 2160) @15 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps WDR (120 db), 3D DNR, HLC, BLC, AGC, AWB, RoI, Smart IR Intrusion, tripwire, SD Card 256GB, IP67, PoE		106,900,000
17	IPC-HFW1830SP-0360B-S6	8MP 8MP 1/2.7" CMOS Entry IR Fixed-focal Bullet Network Camera Outputs max. 8MP@15fps, supports 2688 × 1520 (2688 × 1520) @25/30 fps Illumination 0.004 Lux@F2.0 (B/W, 30 IRE) H.265+&H.264+ high compression rate, and ultra-low bit rate. WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Built-in MIC 3.6mm fixed lens, Built-in IR LED, and the max. illumination distance is 30 m. 12 V DC/PoE power supply, IP67		92,500,000
18	HF2531TP-ZS	1/2.7" 5Megapixel progressive CMOS 2.7~13.5mm Motorized lens 15fps@5M(2592×1944)&25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card 128GB, Max IR LEDs Length 60m, Smart IR IP67, PoE, Smart Detection (Tripwire Intrusion)		137,350,000
19	DH-IPC-HFW5449T1-ZE-LED	4MP 1/1.8" CMOS image sensor, Full-color Vari-focal Warm LED Bullet WizMind Network Camera Outputs max. 4MP (2688 × 1520) @30 fps, Focal Length 2.7 mm~12 mm Min. Illumination 0.0005 Lux@F1.0 , S/N Ratio > 56 dB Built-in warm illuminator, and the max. illumination distance : 70 m ROI, SMART H.264+/H.265+, flexible coding, WDR 140db , 3D NR, HLC, BLC IVS (Perimeter Protection) : Tripwire; intrusion; fast moving, loitering detection, people gathering; parking detection, Face Detection, People Counting, Intelligent Search Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card, built-in Mic and speaker 12V DC/PoE power supply, ePoE, IP67 protection, SMD 3.0		263,600,000
20	HF5442EP-ZE-0832	4MP Pro AI IR Vari-focal, WizMind 1/1.8" 4Megapixel progressive scan CMOS H.265,H.264,H.264B,H.264H, MJPEG triple-stream encoding Max 25/30fps@4Mp(2688×1520), 50/60fps@2Mp(1920 × 1080) WDR(140dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, EIS, Defog, Region of Interest, 8mm-32mm Motorized lenz, Max. IR LEDs Length 50m, Smart IR, Micro SD card memory , 128 GB Audio In/Out 1/1, Alarm In/Out 2/1 Smart Detection Tripwire, intrusion (Recognition of vehicle and people), Object Abandoned / Missing, fast moving, loitering detection, parking detection and people gathering Support Line crossing/Region/Queueing people counting; Support 4 accesses independent detection, 4 areas independent detection, Scene Change, Heatmap, IP67, IK10, PoE		223,600,000
21	IPC-HFW5241E-Z5E	2MP IR Vari-focal Bullet WizMind Network Camera 2MP 1/2.8" Progressive STARVIS™ CMOS low illuminance 0.0015 Lux@F1.3 high image definition 2MP@25/30fps 7-35mm Motorized Lens SMART H.264+/H.265+ IVS: Tripwire; intrusion; fast moving (with accurate classification of vehicle and human); loitering detection; people gathering; parking detection Face Detection with Face Attributes and Face Expression People Counting with Queue Management Micro SD card 256 GB, 1ch Audio I/O, 2/1 Alarm I/O WDR (120db), EIS, Defog, 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, IK10, 4 IR LEDs 120m Distance, Onvif Profile S/G/T		194,600,000
22	IPC-HFW5541E-ZE-S3	5MP IR Vari-focal Bullet WizMind Network Camera 5-MP (2960 × 1668) 1/2.7" CMOS image sensor, low luminance, and high definition image Super Low Illumination 0.0009 lux@F1.5(Color, 30 IRE) 0.0005 lux@F1.5(B/W, 30 IRE) 0 lux (Illuminator on 60m) 2.7 mm~13.5 mm Motorized Lens, Field of View H: 114°~32°; V: 58°~17°; D: 138°~36° Smart H.265+; Smart H.264+; AI Coding Deep learning algorithm, video metadata, smart sound detection, people counting, queue management, Heat Map, Smart Search face detection with 6 Face Attributes and 8 Face Expressions smart object detection: Smart abandoned object; smart missing object IVS: Intrusion, tripwire, fast moving, loitering, people gathering, parking detection SMD 3.0 (Less false alarm, longer detection distance) with detailed information about human body and vehicle features BLC, HLC, WDR 120db, Ai SSA, AWB, AGC, 3D DNR, RoI, EIS, Defog Built-in Mic, Audio I/O 1/1, Alarm I/O 2/1, Micro SD up to 512GB, ROM 4GB, RAM 1GB		248,400,000
23	DH-IPC-HFW4431TP-S-S4	4MP WDR IR Mini Bullet Network Camera 1/3" 4Megapixel progressive CMOS 3.6mm fixed lens 25/30fps@4Mp(2688×1520) H.265&H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Face detection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE		88,350,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
24	DH-IPC-HFW3849T1-AS-PV-S3	8MP Smart Dual Illumination Active Deterrence Fixed-focal Bullet WizSense Network Camera 1/2.8" CMOS image sensor, low illuminance, high image definition Outputs max. 8 MP (3840 × 2160)@25/30 fps Min. Illumination 0.004 lux@F1.0 (Color, 30 IRE), 0.0004 lux@F1.0 (B/W, 30 IRE), 0 lux (illuminator on) Built-in warm illuminator, and the max. illumination distance: 30 m Intrusion, tripwire (support the classification and accurate detection of vehicle and human) WDR 120db, 3D NR, HLC, BLC, digital watermarking, Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256G SD card; built-in dual MICs; 1-ch speaker 12 VDC/PoE power supply, IP67 protection, Sound and light alarm (red and blue lights) SMD 3.0, One-click arming/disarming through alarm input Full Metal Case		189,100,000
25	IPC-HFW3849T1-AS-PV-S4	8MP Smart Dual Light Active Deterrence Fixed-focal Bullet WizSense Network Camera 8-MP 1/2.8" CMOS image sensor, low luminance, and high definition image Outputs max. 8 MP (3840 × 2160)@25/30 fps, H.265 codec, high compression rate, ultra-low bit rate Min. Illumination 0.004 lux@F1.0 (Color, 30 IRE), 0.0004 lux@F1.0 (B/W, 30 IRE), 0 lux (illuminator on) Built-in warm light and IR LED; the max. IR illumination distance is 30 m and warm light distance is 30 m IVS: Intrusion, Tripwire, SMD 4.0, Quick Pick, Ai SSA, Ai Coding, WDR 120db, SSA, HLC, BLC, 3D DNR, Defog, AWB, AGC, Rol, ICR, Smart Illumination Dual Built-in Mic , Built-in Speaker, Audio in/out 1/1, Alarm Input 1 channel in: 5mA 3V~5 VDC, Alarm Output 1 channel out: 300mA 12 VDC ,Micro SD 256G, support two-way talk Power Supply 12V DC/PoE (802.3af), IP67 protection, One-tap arming/disarming through alarm input, Sound and light alarm (red and blue lights) Full Metal Case		190,450,000
26	DH-IPC-HFW3449EP-AS-LED-3.6	4MP Full-color WDR IR Mini Bullet Network Camera 1/2.7" 4Megapixel progressive CMOS 3.6mm fixed lens 25/30fps@4Mp(2688×1520) H.265/Smart H.265+/H.264/Smart H264+ triple-stream encoding IVS(Tripwire, Intrusion, Recognition of vehicle and people, SMD Plus) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE Full Metal Case		106,300,000
27	DH-IPC-HFW3449EP-AS-LED-2.8	4MP Full-color WDR IR Mini Bullet Network Camera 1/2.7" 4Megapixel progressive CMOS 2.8mm fixed lens 25/30fps@4Mp(2688×1520) H.265/Smart H.265+/H.264/Smart H264+ triple-stream encoding IVS(Tripwire, Intrusion, Recognition of vehicle and people, SMD Plus) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE Full Metal Case		106,300,000
28	HFW3441TP-ZS-27135	4MP IR Vari-focal Bullet WizSense Network Camera 1/3" 4Megapixel progressive CMOS Min. Illumination:0.005 Lux@F1.5 2.7 mm~13.5 mm Motorized lens 25/30fps@4Mp(2688×1520) SMART H.264+/H.265+ triple-stream encoding IVS(Tripwire; intrusion (Recognition of human and vehicle)) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Rol Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE Full Metal Case		149,050,000
29	IPC-HFW2849S-S-IL	8MP Smart Dual Light 2.8mm Fixed-focal Bullet WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps Min. Illumination 0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on) Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warmlight distance is 30m WDR 120db, BLC, HLC, AWB, AGC, Rol, 3D DNR, ICR, Smart Illumination IVS: Intrusion, Tripwire, SMD Plus, Smart Search Built-in Mic, Micro SD 256GB 12 VDC/PoE (802.3af), IP67 Protection, Full Metal Case		111,800,000
30	IPC-HFW2841T-ZS	8MP IR Vari-focal Bullet WizSense Network Camera 8-MP 1/2.7" Progressive CMOS image sensor 8MP@20fps,@25/30fps, 2.7-13.5mm Motorized Lens Smart H.265+; Smart H.264+ high compression rate, ultra-low bit rate Min. Illumination 0.008 lux@F1.5 (Color, 30 IRE) 0.0008 lux@F1.5 (B/W, 30 IRE) 0 lux (Illuminator on) Built-in IR LED, and the max. illumination distance is 60 m WDR 120db, BLC, HLC, AWB, AGC, Rol, 3D DNR, ICR, Smart Illumination Intelligent monitoring: Intrusion, tripwire, SMD Plus Built-in Mic, Micro SD 256GB, 12 VDC/PoE, IP67, IK10, Full Metal Case		178,750,000
31	IPC-HFW2549TL-S-PV	5MP Smart Dual Light Active Deterrence Fixed-focal Bullet WizSense Network Camera 5-MP 1/2.7" Progressive CMOS, max. 5MP@20fps/4MP@25/30fps, 3.6 mm: H: 91.9°; V: 48.7°; D: 107.7° Min. Illumination 0.006 lux@F1.0 (Color, 30 IRE) 0.0006 lux@F1.0 (B/W, 30 IRE) 0 lux (Illuminator on) WDR 120 db, BLC, HLC, 3D DNR, Rol, AWB, AGC, Smart Dual Light 30m SMD+, Intrusion, tripwire, Active Deterrence, MSD 256GB, Built-in Mic & Speaker, two-way talk, Sound and light alarm, One-tap arming/disarming IP67, 12 VDC/PoE, easy for installation, Metal Case		97,200,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
32 IPC-HFW2549T-AS-IL	Full-Color Dual Light 5MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera 5-MP 1/2.7" Progressive CMOS image sensor 5MP(2960 × 1668)@25/30 fps Smart H.265+; Smart H.264+ high compression rate, ultra-low bit rate Focal Length 2.7 mm–13.5 mm Min. Illumination 0.007 lux@F1.6 (Color, 30 IRE) 0.0007 lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on) Built-in warm light and IR LED, the max. IR light distance is 60 m and max. warm light is 50 m WDR, Rol, HLC, BLC, AWB, AGC, 3D DNR, Smart illumination Intelligent monitoring: Intrusion, tripwire, SMD Plus Alarm in/out 1/1, Audio in/out 1/1, Built-in Mic, Micro SD 256GB 12 VDC/PoE, IP67, IK10, Metal Case		124,200,000
33 IPC-HFW2541T-AS-S2	STARLIGHT WizSense 5MP IR Fixed-focal Bullet WizSense Network Camera 3.6mm Lens, 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments Built-in IR LED, and the max. illumination distance is 80 m Min. Illumination, 0.007 Lux@F1.6 (Color, 30 IRE), 0.0007 Lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on) WDR 120db, HLC, BLC, AWB, AGC, 3D DNR, Auto ICR Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human), SMD Plus Alarm: 1 in, 1 out; audio: 1 in, 1 out; Supports max. 256 G Micro SD card; built in MIC 12 VDC/PoE power supply, easy for installation, IP67, Metal Case		115,300,000
34 IPC-HFW2449S-S-LED	Full-Color 4MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps H.265 codec, high compression rate, ultra-low bit rate Min. Illumination :0.005 lux@F1.0 Built-in warm light/IR LED, the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Supports max. 256 G Micro SD card, built in MIC 12 VDC/PoE power supply, easy for installation, IP67 protection, SMD Plus.Full Metal Case		79,400,000
35 DH-IPC-HFW2449S-S-IL	Full-Color Dual Light 4MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps H.265 codec, high compression rate, ultra-low bit rate Min. Illumination : 0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on) Built-in warm light/IR LED, the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Supports max. 256 G Micro SD card, built in MIC 12 VDC/PoE power supply, easy for installation, IP67 protection, SMD Plus. Full Metal Case		79,400,000
36 IPC-HFW2441S-S	STARLIGHT WizSense 4MP IR Fixed-focal Bullet WizSense Network Camera 4-MP 1/2.9" Progressive CMOS image sensor, Outputs 4MP (2688 × 1520)@20 fps, and supports 2560 × 1440@25/30 fps Min. Illumination 0.006 Lux@F1.6(Color,30IRE) 0.0006 Lux@F1.6(B/W,30IRE) 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, and the max. illumination distance is 30m Rol, SMART H.264 +/H.265+, WDR 120db, 3D NR, HLC, BLC, AWB, AGC, 3D DNR Intelligent monitoring: Intrusion, tripwire, SMD Micro SD card 256GB, built-in MIC, 12 VDC/PoE, IP67, Metal Case		69,000,000
37 DH-IPC-HFW2441T-ZS	STARLIGHT WizSense 4MP IR Vari-focal Bullet WizSense Network Camera Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 ,(2560 × 1440)@25/30 fps Min. Illumination, 0.008 lux@F1.5 (Color, 30 IRE), 0.0008 lux@F1.5 (B/W, 30 IRE), 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate, Focal Length 2.7 mm–13.5 mm Built-in IR LED, and the max. illumination distance is 60 m ROI, SMART H.264+/H.265+, flexible coding, WDR 120db, 3D NR, HLC, BLC Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Alarm: 1 in, 1 out (Only - ZAS supports), audio: 1 in, 1 out (Only - ZAS supports), 256G SD card, built in MIC 12 VDC/PoE power supply, easy for installation, IP67, IK10 (optional) protection, SMD Plus		133,900,000
38 IPC-HFW2439SP-SA-LED-0360B-S2	Full-Color 4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps, 3.6mm Fixed lens SMART H.264+/H.265+, IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/G/T		73,900,000
39 HFW2431TP-AS-S2	STARLIGHT 4MP Lite IR Fixed-focal Bullet Network Camera,1/3" CMOS image sensor Outputs max. 4MP (2688 × 1520) @20 fps, and supports 2560x1440 (2560 × 1440) @25/30 fps Built-in IR LED, max IR distance: 80 m, Intelligent detection: Intrusion, tripwire H.265; H.264; H.264B; MJPEG(only supported WDR(120 dB), 3D NR, HLC, BLC, digital watermarking Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card 12V DC/POE , IP67 protection, IK10 protection (optional)		90,450,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
40	HF2431TP-ZS-S2 	4MP WDR IR Bullet Network Camera 1/3" 4MP image sensor SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.5, 2.7-13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, max IR distance:60 m, Smart IR, IP67, PoE		117,300,000
41	IPC-HFW1431S1-S4-S5	4MP Entry IR Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.03 Lux @ F2.0 high image definition 4MP@25/30fps 3.6mm fixed lens, Smart H.265+/H.264+ WDR(120db), Rol, BLC, HLC, 3D DNR, AWB, AGC, Day/Night Auto ICR, Smart Illumination 12V, PoE, IP67, 1 IR LEDs 30m Distance, ONVIF (Profile S/Profile G/Profile T)		50,400,000
42	HF2431SP-0360B-S4	4MP Entry IR Fixed-focal Bullet Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.03 Lux@F2.0, 3.6 Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30 m, Smart IR, IP67, PoE		59,350,000
43	HF23541EP-AS  	5MP IR Fixed focal Bullet WizSense Network Camera 1/2.7" CMOS image sensor,Outputs max. 5MP (2592 × 1944) @20 fps H.265 codecSMART H.264+/H.265+ WDR(120db), 3D DNR, HLC, BLC, digital watermarking, Min Illumination 0.0005 Lux@F1.6 (B/W, 30IRE) 12V DC/POE IP67 SMD Plus Supports max. 256 G Micro SD card, built-in Mic		Call
44	IPC-HFW3549T1P-AS-PV  	5-MP 1/2.7" CMOS image sensor, low luminance, Smart Dual Illumination Min. Illumination : 0.003 lux@F1.0 (Color, 30 IRE) / 0.0003 lux@F1.0 (B/W, 30 IRE) / 0 lux (illuminator on) Lens Fixed-focal 3.6 mm , 15.6 m Recognize & 7.8 m Identify Illumination Distance : 30 m (2 IR LED) / 30 m (2 warm light) AI H.265, AI H.264 , Smart H.265+ , Smart H.264+ , Built-in MIC Main stream: 2880 × 1620 or 2960 × 1668 @20fps / 2688 × 1520 @(30 fps) WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol(4 years), Smart Illumination, Defog, Scence Self-adaption Storage : FTP, SFTP, Micro SD card (support max. 256 G), NAS ROM : 128MB, RAM : 512MB, S/N Ratio > 56db , Sound and Light Alarm, Active Deterrence, IVS (Tripwire, intrusion), SMD 4.0, Smart Search, Quick Pick, AI SSA Audio In/out : 1/1 , Alarm in/out : 1/1, RJ-45 (10/100 Base-T) , 3.3 W (12 VDC); 4.4 W (PoE), IP67		159,000,000
45	HF23549EP-AS-LED-0360B 	5MP Full-color Fixed-focal Warm LED Bullet WizSense Network Camera 5MP, 1/2.7" CMOS image sensor low illuminance 0.003 Lux@F1.0 5MP@20 fps, 4MP@25/30 fps, 3.6mm Fixed lens SMART H.264+/H.265+, IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, Built-in warm light, max. illumination distance: 30 m, Onvif Profile S/G/T, Full Metal Case		117,300,000
46	IPC-HFW3541TP-ZS-27135  	5MP IR Vari-focal Bullet WizSense Network Camera 5MP, 1/2.7" Progressive CMOS 0.005 Lux@F1.5 (Color, 30IRE), 0.0005 Lux@F1.5 (B/W, 30IRE), 0 Lux (Illuminator on) high image definition 5MP@20fps 2.7-13.5mm Motorized Lens SMART H.264+/H.265+ 3 Streams IVS Intrusion, Tripwire, Accurate Human/Vehicle Classification, SMD Plus Micro SD 256GB WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 4 IR LEDs 60m Distance, Onvif Profile S/G/T		177,700,000
47	IPC-HFW2531TP-AS-S2 	5MP Lite IR Fixed-focal Bullet Network Camera 5MP, 1/2.7" Progressive CMOS low illuminance 0.008 Lux@F1.6 high image definition 5MP@20fps, 3.6mm fixed Lens SMART H.264+/H.265+, IVS Intrusion/Tripwire 1ch Alarm I/O, 1ch Audio I/O, Micro SD 256GB WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, IK10, IR LED 80m Distance, Onvif Profile S/G/T		103,700,000
48	HF2431SP-S-S2 	4MP WDR IR Bullet Network Camera 1/3" 4MP image sensor SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.6, 3.6mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, max IR distance: 30 m, Smart IR, IP67, PoE		67,800,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
49	Full-color 2MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, 0.0002 lux@F1.6 (B/W, 30 IRE) Outputs max. 2 MP (1920 × 1080)@25/30 fps, Fixed Lens 3.6mm Smart H.265+, Smart H.264+, H.264H, H.265, H.264, H.264B Built-in warm light/IR LED : 30m/30m ROI, WDR, 3D NR, HLC, BLC, digital watermarking SMD Plus, Intrusion, tripwire (two functions supported : detection of vehicle and human) Supports max. 256 G Micro SD card, built in MIC. 12 VDC/PoE power supply, easy for installation, IP67 STARLIGHT WizSense		65,600,000
50	Full-color 2MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, 0.0002 lux@F1.6 (B/W, 30 IRE) Outputs max. 2 MP (1920 × 1080)@25/30 fps, Fixed Lens 3.6mm Smart H.265+, Smart H.264+, H.264H, H.265, H.264, H.264B Built-in warm light/IR LED : 30m/30m ROI, WDR, 3D NR, HLC, BLC, digital watermarking SMD Plus, Intrusion, tripwire (two functions supported : detection of vehicle and human) Supports max. 256 G Micro SD card, built in MIC. 12 VDC/PoE power supply, easy for installation, IP67 STARLIGHT WizSense		65,600,000
51	2MP WDR IR Bullet Network Camera, starlight 1/2.8" 2Megapixel progressive CMOS Min. Illumination:0.002 Lux@F1.6 Outputs max. 2MP (1920 × 1080) @25/30 fps, 3.6mm Fixed lens SMART H.264/H.265 dual-stream encoding, IVS(Tripwire, intrusion) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Roi Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE STARLIGHT		49,700,000
52	2MP IR Bullet Network Camera 1/2.7" CMOS image sensor, low illuminance, high image definition H.265+/H.265/H.264+/H.264 Double-stream encoding 25/30fps@1080P(1920×1080) DWD, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI 3.6mm, Max. IR LEDs Length 30m, Smart IR Micro SD card memory 128 GB, IP67, PoE, AVI(Tripwire Intrusion) STARLIGHT		47,950,000
53	2MP Lite Full-color Fixed-focal Bullet Network Camera 1/2.8" CMOS image sensor, Outputs max. 2MP (1920 × 1080) @25/30 fps ROI, SMART H.264+/H.265+, flexible coding, Min Illumination 0.0017 Lux@F1.0 Intelligent detection: Intrusion, tripwire WDR(120db), 3D NR, HLC, BLC, digital watermarking Supports max. 256 GB Micro SD card and built-in Mic, 12V DC/PoE, IP67 Full-color		59,900,000
54	2MP Lite IR Vari-focal Bullet Network Camera 2MP, 1/2.8" Progressive CMOS, low illuminance 0.002 Lux@F1.5 high image definition 2MP@25/30fps, 2.7-13.5mm Motorized Lens, SMART H.264+/H.265+ IVS Intrusion, Tripwire, Micro SD card 256 GB WDR(120db), Roi, BLC, HLC, 3D DNR, AWB, AGC, Day/Night Auto ICR, Smart Illumination 12V, PoE, IP67, IK10, 4 IR LEDs 60m Distance, Onvif Profile S/G/T STARLIGHT		103,700,000
55	Dual Light 8MP Entry Smart Dual Light Fixed-focal Bullet Network Camera 8-MP 1/2.7" Progressive CMOS sensor, 8MP@20 fps, and 4MP@25/30 fps, 3.6mm Fixed Lens, HfV 100° Built-in Multi-core Light, IR 30m warmlight 30m, 0.008 lux@F1.6 (Color, 30 IRE); 0.0008 lux@F1.6 (B/W, 30 IRE); 0 lux (Illuminator on) Human Detection, 2 Streams, H.265+, Smart Codec, Smart Dual Light, Built-in Mic DWD, HLC, BLC, 3D DNR, Roi, AGC, AWB 12VDC, IP67, Metal Case, easy for installation STARLIGHT Full-color		96,400,000
56	Dual Light 6MP Entry Smart Dual Light Fixed-focal Bullet Network Camera 1/2.7" Progressive CMOS sensor, max. 6MP@20 fps, and 4MP@25/30 fps, 3.6mm Fixed Lens, HfV 91° Built-in Multi-core Light, IR 30m warmlight 30m, 0.007 lux@F1.6 (Color, 30 IRE); 0.0007 lux@F1.6 (B/W, 30 IRE); 0 lux (Illuminator on) DWD, HLC, BLC, 3D DNR, Roi, AGC, AWB Human Detection, 2 Streams, H.265+, Smart Codec, Smart Dual Light, Built-in Mic 12VDC, IP67, Metal Case, easy for installation STARLIGHT Full-color		68,400,000
57	5MP 1/2.7" CMOS image sensor Outputs max. 5MP (2880 × 1620) @20 fps, Fixed-focal 3.6mm min illumination 0.003 Lux@F2.0 (B/W, 30 IRE) H.265 codec, SMART H.264 +/H.265+, Built-in IR LED, and the max. illumination distance is 30 m DWD, 3D NR, HLC, BLC, digital watermarking Built-in MIC, IP67, POE STARLIGHT		63,500,000
58	Dual Light 4MP Entry Full-color Fixed-focal Bullet Network Camera -MP 1/2.9" Progressive CMOS sensor, max. 4MP@25/30 fps, 3.6mm Fixed Lens, HfV 95° IR 40m, Warmlight 30m, 0.006 lux@F1.6 WDR 120db, HLC, BLC, 3D DNR, Roi, AGC, AWB human detection, 2 Streams, H.265+, Smart Codec, Smart Dual Light, Built-in Mic 12 VDC/PoE, Metal + plastic, IP67 STARLIGHT Full-color		61,900,000
59	4MP Entry Full-color Fixed-focal Bullet Network Camera 4-MP 1/3" Progressive CMOS image sensor, Outputs max. 4 MP (2560 × 1440)@25/30 fps Min. Illumination 0.008 lux@F1.6, Illumination Distance 15 m (49.21 ft) (warm light) SMART H.264+/H.265+, Roi, WDR 120db, BLC, HLC, AWB, AGC, 3D DNR, Smart Illumination Built-in Mic, 12 VDC/PoE, Metal + plastic, IP67 Full-color		58,800,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
60	NEW DH-IPC-HFW1239TC1-LED-S6 STARLIGHT Full-color 2 MP Entry Full-color Fixed-focal Bullet Network Camera 2-MP 1/2.8" Progressive CMOS, max. 2 MP (1920 × 1080)@25/30 fps warm light 30m, 0.005 lux@F1.6, 3.6 mm: H: 87°; V: 44°; D: 105° DWDR, 3D NR, HLC, BLC, ROI, AWB, AGC, SMART H.264+/H.265+ human detection, Full-color IP67, 12 VDC/PoE, easy for installation, Metal+Plastic		45,750,000
61	DH-IPC-HFW1239TL1-A-IL STARLIGHT Full-color 2MP Smart Dual Light Fixed-focal Bullet Network Camera 2-MP 1/2.8" Progressive CMOS sensor, max. 2MP@30 fps Built-in multi-core light, IR 30m Warmlight 30m, 0.005 lux@F1.6 (Color,30 IRE) DWDR, HLC, BLC, AGC, AWB, 3D DNR, Smart Dual Light human detection, 2 Streams, H.265+, Smart Codec, Smart Dual Light, Built-in Mic 12 VDC/PoE, Metal + plastic, IP67		47,250,000
62	IPC-HFW1239S1-A-LED-S5 Full-color 2MP Entry Full-color Fixed-focal Bullet Network Camera 2-MP 1/2.8" Progressive CMOS sensor, max. 2MP@25/30 fps, 2.8mm Fixed Lens, HfOV 107° H.265 codec, high compression rate, ultra-low bit rate, 0.005 lux@F1.6, Warmlight 15m DWDR, 3D DNR, HLC, BLC, AWB, AGC, ROI Built-in MIC IP67, 12 VDC/PoE, Metal+Plastic		44,900,000
63	DH-IPC-HFW1239S1-LED-S5 STARLIGHT Full-color 2MP Lite Full-color Fixed-focal Bullet Network Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.005 Lux @F1.6 high image definition 2MP@25/30fps 3.6mm fixed lens SMART H.264+/H.265+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 15m Distance, Onvif Profile S/T		43,900,000
64	HFW1230T1P-ZS 2MP Entry, 1/2.8" CMOS image sensor, low luminance, and high definition image Outputs max. 2MP (1920 × 1080)@25/30 fps. Min. Illumination : 0.008 Lux@F1.7 (Color, 30 IRE), 0.0008 Lux@F1.7 (B/W, 30 IRE) Motorized vari-focal, 2.8 mm–12 mm, IR Distance 50 m(2 IR) Smart H.265+, Smart H.264+, H.265 codec, high compression rate, ultra-low bit rate. DWDR, 3D DNR, HLC, BLC, AWB, AGC, ROI(4 years), Smart Illumination, S/N Ratio > 56 dB 1 Port RJ-45 (10/100 Base-T), 12V DC/PoE (802.3af), IP67, Humidity ≤95%		82,800,000
65	HFW1230S1P-0360B-S5 2MP Entry IR Fixed-Focal Bullet Network Camera 1/2.8" CMOS image sensor, low illuminance Fixed Lens 3.6mm, F2.0, Horizontal: 84° Outputs max. 2MP (1920 × 1080) @25/30 fps Smart H.265+, Smart H.264+, H.265, H.264, H.264B ONVIF (Profile S/Profile T) Built-in efficient IR illuminator, and the max. illumination distance is 30 m ROI, DWDR, 3D NR, HLC, BLC, digital watermarking 2V DC/PoE power supply, IP67		40,900,000
66	HFW1230SP-S4-S5 2MP Entry IR Fixed-focal Bullet Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 × 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0 3.6 Fixed lens DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30m, Smart IR IP67, PoE		43,100,000
67	IPC-HDBW5541E-ZE-S3 Super STARLIGHT 5MP IR Vari-focal Vandal-proof Dome WizMind Network Camera 5-MP (2960 × 1668) 1/2.7" CMOS image sensor, low luminance, and high definition image Super Low Illumination 0.0009 lux@F1.5(Color, 30 IRE) 0.0005 lux@F1.5(B/W, 30 IRE) 0 lux (Illuminator on 40m) 2.7 mm–13.5 mm Motorized Lens, Field of View H: 114°–32°; V: 58°–17°; D: 138°–36° Smart H.265+; Smart H.264+; AI Coding Deep learning algorithm, video metadata, smart sound detection, people counting, queue management, Heat Map, Smart Search face detection with 6 Face Attributes and 8 Face Expressions smart object detection: Smart abandoned object; smart missing object IVS: Intrusion, tripwire, fast moving, loitering, people gathering, parking detection SMD 3.0 (Less false alarm, longer detection distance) with detailed information about human body and vehicle features BLC, HLC, WDR 120db, AI SSA, AWB, AGC, 3D DNR, ROI, EIS, Defog Built-in Mic, Audio I/O 1/1, Alarm I/O 2/1, Micro SD up to 512GB, ROM 4GB, RAM 1GB IP67 and IK10 protection Wiz Mind ACUPICK		247,050,000
68	HDW4431EMP-AS-S4 4MP IR Eyeball Network Camera 1/3" 4Megapixel progressive CMOS 2.8mm fixed lens 25/30fps@4Mp(2688×1520) H.265&H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Face detection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Built-in Mic Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, PoE		76,650,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
69	IPC-HDBW3541E-S-S2	5MP IR Fixed-focal Dome WizSense Network Camera 5-MP (2960 × 1668) @20fps 1/2.7" CMOS image sensor, excellent low luminance performance and high definition of images 0.005 lux@F1.4 (Color, 30 IRE), 0.0005 lux@F1.4 (B/W, 30 IRE), 0 lux (Illuminator on 50m) 2.8 mm: Horizontal: 111°; Vertical: 58°; Diagonal: 132° Smart H.265+, Smart H.264+, AI Coding IVS: Tripwire, Intrusion, SMD 4.0, Smart Search, Scene Changing, Audio Detection BLC, HLC, WDR 120db, AI SSA, AWB, AGC, 3D DNR, ROI, Defog, AFSA Built-in Mic, Micro SD up to 256GB, ROM 128MB, RAM 512MB IP67, IK10 protection, Easy Installation		110,600,000
70	HDBW3441EP-AS	4MP IR Fixed focal Dome WizSense Network Camera 1/3" CMOS image sensor Outputs max. 4MP (2688 × 1520)@30 fps H.265 codec, SMART H.264+/H.265+ WDR(120db), 3D DNR, HLC, BLC, digital watermarking Supports max. 256 G Micro SD card, 12V DC/POE, IP67, IK10, SMD Plus Min Illumination 0.0005 Lux@F1.6 (B/W, 30IRE) Audio Input 1 channel (RCA port), Audio Output 1 channel (RCA port) Alarm Input 1 channel in, Alarm Output 1 channel out		91,000,000
71	HDW3441TMP-AS-0280B	4MP IR Fixed focal Eyeball WizSense Network Camera 1/3" 4Megapixel progressive CMOS Min. Illumination: 0.005 Lux@F1.6 2.8mm Motorized lens 25/30fps@4Mp(2688×1520) SMART H.264+/H.265+ triple-stream encoding IVS(Tripwire; intrusion (Recognition of human and vehicle)) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Built-in Mic, Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, PoE		86,300,000
72	HDBW2831EP-S-S2	1/2.7" 8Megapixel progressive CMOS Min. Illumination: 0.009 Lux@F2.0 3.6mm Fixed Lens max. 8MP (3840 × 2160) @15 fps, 2688×1520 (2688 × 1520) @25/30 fps SMART H.264+/H.265+, flexible coding IVS(Tripwire; intrusion), Abnormality detection: Motion detection, video tampering WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Micro SD memory 256GB Built-in IR LED Max.Length 30m, IP67, PoE		111,000,000
73	HDBW2531RP-ZAS	1/2.7" 5Megapixel progressive CMOS 2.7~13.5mm Motorized lens 20fps@5M(2592×1944)&25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 1/1 Audio in/out, 1/1 Alarm in/out Micro SD card 128GB Max IR LEDs Length 30m, Smart IR IP67, IK10, PoE		137,250,000
74	IPC-HDBW2531E-S-S2	5MP Lite IR Fixed-focal Dome Network Camera 5MP, 1/2.7" Progressive CMOS Min. Illumination 0.008 Lux @ F1.6 Max 5MP@20fps SMART H.264+/H.265+ IVS: Intrusion, tripwire Micro SD card 256GB WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance: 30m, 12V DC, PoE, IP67, IK10		69,000,000
75	IPC-HDW2831TP-AS-S2	8MP Lite IR Fixed-focal Eyeball Network Camera 1/2.7" CMOS image sensor Outputs max. 8MP (3840 × 2160) @15 fps Min Illumination 0.009 Lux@F2.0 Built-in IR LED, max IR distance: 30 m SMART H.264+/H.265+ WDR, 3D NR, HLC, BLC, digital watermarking Supports max. 256 GB Micro SD card, built-in MIC 12V DC/PoE, IP67		111,700,000
76	IPC-HDW2449T-S-LED	4MP Full-color Fixed-focal Eyeball Wizsense Network Camera 4-MP 1/2.9" Progressive CMOS image sensor, 4MP(2688× 1520)@20fps, (2560×1440)@25/30fps Min. Illumination 0.005 lux@F1.0, Built-in warm light, max. illumination distance 30m Smart H.265+; Smart H.264+ high compression rate, ultra-low bit rate ROI, WDR 120db, HLC, BLC, AGC, AWB, 3D DNR, Smart illumination Intelligent monitoring: Intrusion, tripwire, SMD Plus Built-in Mic, Micro SD 256GB 12 VDC/PoE, IP67, Metal+Plastic Case		79,100,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
77 DH-IPC-HDW2449T-S-IL	4MP Smart Dual Illumination Fixed-focal Eyeball WizSense Network Camera Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps Min. Illumination : 0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate Built-in warm light/IR LED, the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding, WDR, 3D NR, HLC, BLC, digital watermarking Intrusion, tripwire (support the classification and accurate detection of vehicle and human Supports max. 256 G Micro SD card; built in MIC, 12 VDC/PoE power supply, easy for installation, IP67 protection,SMD Plus		81,300,000
78 IPC-HDW2439TP-AS-LED-0360B	4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps 3.6mm Fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 2 Warmlight LED 30m Distance, Onvif Profile S/G/T		75,400,000
79 IPC-HDW2439TP-AS-LED-0280B-S2	4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps 2.8mm Fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 2 Warmlight LED 30m Distance, Onvif Profile S/G/T		75,400,000
80 DH-IPC-HDBW2441E-S	4MP 1/2.9" CMOS image sensor, IR Fixed-focal Dome WizSense Network Camera Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2566 × 1440@25/30 fps Min. Illumination 0.008 lux@F1.6 (Color,30IRE), 0.0008 lux@F1.6 (B/W,30IRE), 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, and the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding, , WDR 120db, 3D NR, HLC, BLC Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Supports max. 256 G Micro SD card; built in MIC 12 VDC/PoE power supply, easy for installation, IP67, IK10 protection, SMD Plus		74,650,000
81 DH-IPC-HDBW2441R-ZS	4MP IR Vari-focal Dome WizSense Network Camera, 4-MP 1/2.9" CMOS image sensor Outputs max. 4 MP (2688 × 1520)@20 fps and supports 2560 × 1440 , (2560 × 1440)@25/30 fps Min. Illumination 0.008 lux@F1.5 (Color, 30 IRE) , 0.0008 lux@F1.5 (B/W, 30 IRE) , 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, and the max. illumination distance : 40 m, ROI, SMART H.264+/H.265+ WDR 120db, 3D NR, HLC, BLC, Focal Length 2.7 mm–13.5 mm Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS supports); 256G SD card; built in MIC 12 VDC/PoE power supply, easy for installation, IP67 and IK10 protection, SMD Plus		130,800,000
82 IPC-HDW2441T-S	4MP IR Fixed-focal Eyeball WizSense Network Camera 4-MP 1/2.9" Progressive CMOS image sensor, Output 4MP (2688 × 1520)@20 fps, 2560 × 1440@25/30 fps Min. Illumination 0.006 lux@F1.6 (Color, 30IRE) 0.0006 lux@F1.6 (B/W, 30IRE) 0 lux (Illuminator on) Smart H.265+; Smart H.264+, high compression rate, ultra-low bit rate Built-in IR LED, and the max. illumination distance is 30 m WDR 120db, 3D NR, HLC, BLC, ROI, AWB, AGC, 3D DNR Intelligent monitoring: Intrusion, tripwire, SMD Plus Built-in Mic, Micro SD 256GB, IP67, 12 VDC/PoE, Metal+Plastic		70,350,000
83 HDBW2431RP-ZS-27135-S2	4MP WDR IR Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.5 2.7–13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB 1/1 Audio in/out, 1/1 Alarm in/out max IR distance:40 m, Smart IR IP67, IK10, PoE		115,300,000
84 HDBW2431RP-ZAS-S2	4MP WDR IR Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.5 2.7–13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB 1/1 Audio in/out, 1/1 Alarm in/out max IR distance:40 m, Smart IR IP67, IK10, PoE		116,400,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
85	HDBW2431EP-S-0360B-S2	4MP IR Mini Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux @ F1.6 3.6 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB max IR distance:30 m, Smart IR IP67, IK10, PoE		65,400,000
86	HDBW2431EP-S-0280B-S2	4MP IR Mini Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux @ F1.6 2.6 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB max IR distance:30 m, Smart IR IP67, IK10, PoE		65,400,000
87	HDW2431TP-AS-0280B-S2	4MP Lite IR Fixed-focal Eyeball Network Camera 1/3" CMOS image sensor, Outputs 4MP (2560 × 1440)@25/30 fps H.265 coding, SMART H.264+/H.265+, Fixed Lens 2.8mm Min. Illumination 0.008 Lux @ F1.6 WDR(120db), 3D NR, HLC, BLC, digital watermarking, Intelligent detection: Intrusion, tripwire Max. 256 GB SD card and built-in Mic ,12V DC/POEIP67		69,000,000
88	HDW2431TMP-AS-0280B-S2	4MP WDR IR Eyeball Network Camera, Starlight 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.6 2.8 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, Built in Mic max IR distance:30 m, Smart IR IP67, PoE		70,150,000
89	IPC-HDW1639T-A-IL	6MP Entry Smart Dual Light Fixed-focal Eyeball Network Camera 1/2.7" Progressive CMOSsensor, max. 6MP@20 fps, and 4MP@25/30 fps, 2.8mm Fixed Lens, HFoV 110° Built-in Multi-core Light, IR 30m warmlight 30m, 0.007 lux@F1.6 (Color, 30 IRE); 0.0007 lux@F1.6 (B/W, 30 IRE); 0 lux (Illuminator on) DWDR, HLC, BLC, 3D DNR, Rol, AGC, AWB Human Detection, 2 Streams, H.265+, Smart Codec, Smart Dual Light, Built-in Mic 12VDC, IP67, Metal Case, easy for installation		68,400,000
90	HDBW1431EP-0280B-S4	4MP Entry IR Fixed-focal Dome 1/3" CMOS image sensor Network, low illuminance Min. Illumination : 0.03 Lux @ F2.0 ,Illumination Distance : 30 m(3 IR LED), S/N Ratio > 56db Lens Fixed-focal 2.8 mm , Horizontal: 93° / Vertical: 53° / Diagonal: 111° Smart H.265+, H.265, Smart H.264+, H.264 Main Stream: 2688 × 1520 (20 fps) , high compression rate, ultra-low bit rate WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol(4 years), Smart Illumination Storage(FTP, SFTP, NAS) , ROM : 128MB, RAM : 512MB 12V DC/POE (802.3af), Power Consumption < 5.5W, 1 port RJ-45 (10/100 Base-T) ,IP67, IK10		59,850,000
91	HDW1431T1P-A-0360B-S4	4MP Entry IR Fixed-focal Eyeball Network Camera 1/3"4Megapixel progressive CMOS, Fixed-focal 3.6mm 20fps@4.1M(2688×1520) & 25fps@4M(2560×1440) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), Image flip, 3D DNR, HLC, BLC, digital watermar Support ROI,Built-in MIC Max. IR LEDs Length 30m, IP67, PoE		60,500,000
92	HDW1431T1P-0280B-S4-S5	4MP Entry IR Fixed-focal Eyeball Network Camera 1/3"4Megapixel progressive CMOS 20fps@4.1M(2688×1520) & 25fps@4M(2560×1440) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Support ROI Max. IR LEDs Length 30m, IP67, PoE		54,250,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
93 DH-IPC-HDW2249TP-S-IL-0280B	2MP Smart Dual Illumination Fixed-focal Eyeball WizSense Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance Min. Illumination : 0.0002 lux@F1.6 (B/W, 30 IRE) , Fixed Lens 2.8 mm Outputs max. 2 MP (1920 × 1080)@25/30 fps Smart Codec : Smart H.265+, Smart H.264+, H.264H, H.265, H.264, H.264B SMD Plus, Intrusion, tripwire (accurate detection of vehicle and human). Supports max. 256G Micro SD card, built in MIC. ROI, WDR, 3D NR, HLC, BLC, digital watermarking Built-in warm light/IR LED : 30m/30m 12 VDC/PoE power supply, easy for installation, IP67		65,400,000
94 HDW2231TMP-AS-S2	2MP WDR IR Eyeball Network Camera, Starlight 1/2.8" 2Megapixel progressive CMOS Min. Illumination:0.002 Lux@F1.6 Outputs max. 2MP (1920 × 1080) @25/30 fps 2.8mm Fixed lens SMART H.264/H.265 dual-stream encoding IVS(Tripwire, intrusion) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, RoI Built-in Mic, Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE		55,800,000
95 IPC-HDW2231TP-AS-0280B-S2	2MP Lite IR Fixed-focal Eyeball Network Starlight Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.002 Lux @F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T		55,050,000
96 IPC-HDW2230T-AS-S2	2MP IR Eyeball Network Camera 2MP, 1/2.7" Progressive CMOS low illuminance 0.005 Lux @ F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens SMART H.264+/H.265+ IVS Intrusion, Tripwire Micro SD 256GB, Built-in Mic DWDR, 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T		47,850,000
97 IPC-HDBW2230E-S-S2	2MP Lite IR Fixed-focal Dome Network Camera 2MP, 1/2.7" Progressive CMOS low illuminance 0.005' Lux @F1.6 high image definition 2MP@25/30fps 2.8mm Fixed Lens SMART H.264+/H.265+ IVS Tripwire; intrusion Micro SD 256GB DWDR, 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 3 IR LEDs 30m Distance, Onvif Profile S/G/T		47,600,000
98 HDW1530TP-0280B-S6	5MP Entry IR Fixed-focal Eyeball Network Cam 1/2.7" CMOS image sensor low illuminance 0.003 Lux @F2 Outputs max. 5MP (2880 × 1620) @20 H.265 code, SMART H.264 +/H.265 DWDR, 3D NR, HLC, BLC, digital watermarking Built-in MIC, 12 V DC/PoE power supply		64,700,000
99 IPC-HDW1439V-A-IL	NEW 4MP Entry Smart Dual Light Fixed-focal Eyeball Network Camera 4-MP 1/2.9" Progressive CMOS, max. 4 MP (2560 × 1440)@25/30 fps, 2.8 mm: H: 94°; V: 52°; D: 111° Min. Illumination 0.006 lux@F1.6 (Color, 30 IRE) 0.0006 lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on) Human Detection, Smart Dual Light 30m, Built in Mic, easy for installation WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, ROI, SMART H.264 +/H.265+ IP67, 12 VDC/PoE, Metal+plastic		62,900,000
100 DH-IPC-HDW1239T1P-A-IL-S6	NEW 2MP Entry Smart Dual Light Fixed-focal Eyeball Network Camera 2-MP 1/2.8" Progressive CMOS, max. 2MP@25/30fps, 2.8 mm: H: 103°; V: 55°; D: 123° Min. Illumination 0.005 lux@F1.6 (Color, 30 IRE); 0.0005 lux@F1.6 (B/W, 30 IRE); 0 lux (Illuminator on) DWDR, 3D NR, HLC, BLC, AWB, AGC, ROI, SMART H.264+/H.265+ Human Detection, Smart Dual Light 30m, Built-in Mic IP67, 12 VDC/PoE, Metal + Plastic		47,950,000
101 DH-IPC-HDW1239T1-A-LED-S5	2MP Lite Full-color Fixed-focal Eyeball Network Camera Outputs max. 2MP (1920 × 1080) @25/30 fps H.265 codec, high compression rate, ultra-low bit rate Min. Illumination : 0.005 Lux @F1.6, Built-in LEDs, max LED distance: 15 m, built in MIC ROI, SMART H.264/H.265, flexible coding, applicable to various Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, 12V DC/PoE power support, IP67 protection		47,850,000

رقم	نموذج	مواصفات فنية	تصوير	سعر (ريال)
102	DH-IPC-HDW1239T1-LED-0360B-S5	2 MP Entry Full-color Fixed-focal Bullet Network Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.005 Lux @F1.6 high image definition 2MP@25/30fps 3.6mm fixed lens Smart H.265+/Smart H.264+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/T		42,200,000
103	DH-IPC-HDW1239T1P-LED-0280B-S5	2 MP Entry Full-color Fixed-focal Bullet Network Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.005 Lux @F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens Smart H.265+/Smart H.264+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/T		42,200,000
104	DH-IPC-HDW1230T1-A-S5	2MP Entry IR Fixed-Focal Eyeball Network Camera Outputs max. 2MP (1920 × 1080) @25/30 fps H.265 codec, high compression rate, ultra-low bit rate, Min. Illumination : 0.01 Lux @F2.0 Built-in efficient IR illuminator, and the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various, built in MIC Rotation mode, DWDR, 3D NR, HLC, BLC, S/N Ratio 56 dB, digital watermarking 12V DC/PoE power supply, IP67 protection		46,000,000
105	HDW1230T1P-0280B-S5	2MP Entry IR Fixed-Focal Eyeball Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 × 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0, 2.8 Fixed lens DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI, EIS max IR distance:30 m, Smart IR, IP67, PoE		38,300,000
106	HDBW1230EP-0360B-S2	1/2.7" 2Megapixel progressive scan CMOS, 3.6mm fixed lens H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m, IP67, IK10, PoE		43,100,000
107	DH-SD29204T-GN	1/2.7" 2MP CMOS Sensor, 2.7mm ~ 11mm , 4x Optical Zoom H.264+/H.264 Encoding Max. 25/30fps@1080P, 25/30/50/60fps@720P WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 100°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Built-in Mic, IR Distance up to 30m, POE, (Tripwire Intrusion Scene Change Face Abandoned-Missing Object)		115,650,000
108	DH-SD1A203T-GN	1/2.8" 2MP STARVIS™ CMOS (Starlight) H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 25/30fps@1080P, 2.7mm ~ 8.1mm , 3x Optical Zoom WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max Pan: 80° /s; Tilt: 40° /s speed Pan: 0° ~ 355°; Tilt: 5° ~ 90° rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern, Support Defog, IR Distance up to 15m, IP 66, support POE (Tripwire Intrusion Abandoned Missing Face Detection)		118,000,000
109	SD3A205-GNP-PV	2MP Starlight IR AI WizSense Network PTZ Camera H.265; H.264B; H.264M; H.264H; MJPEG; MJPEG (Sub Stream); H.265+; H.264+ Focal Length 2.7 mm~13.5 mm, Optical Zoom 5x Tripwire and intrusion, Deep-learning-based perimeter protectionm SMD Plus IR distance up to 30m Starlight technology Up to 300 presets DWDR, HLC, BLC, AGC, AWB, 2D/3D DNR, Day/Night Auto (ICR), ROI, Defog Built-in Mic, Built-in Speaker, Two Way Audio ONVIF Profile S&G&T; CGI IP66; TVS 2000V lightning proof; surge protection; voltage transient protection		153,900,000
110	DH-SD6CE230U-HNI	1/2.8" 2MP STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P 4.5mm~135mm Powerful 30x optical zoom Max 200°/s pan speed, 360° endless pan rotation WDR(120db), Day/Night(ICR), Ultra DNR, BLC, HLC Auto-tracking,Tripwire, Intrusion,Abandoned Missing, Face Detection, Heat Map), Support Defog, ROI, EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Alarm 7/2 in/out, Audio 1/1 in/out, 1*Video output RS485, IR Distance up to 200m, PoE+, IP67, IK10		542,000,000

رقم المنتج	مواصفات فنية	تصوير	سعر (ريال)
111 DH-SD6CE245XA-HNR	2MP 45x Starlight IR WizSense Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Minimum Illumination:Color(0.005Lux@F1.6), B/W(0.0005Lux@F1.6) Max. 50/60fps@1080P, 3.95mm~177.7mm Focal Length 45x optical zoom WDR(120dB), Day/Night(ICR), 2D/3D DNR, BLC, HLC, AGC, AWB Auto-tracking, Perimeter protection, Face detection, SMD Plus Tripwire and intrusion, alarm triggering by target types (human and vehicle) Support Defog, ROI Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 1*Video output, Rs485 7/2 Alarm in/out, 1/1 Audio in/out IR Distance up to 250m, PoE+, IP67, IK10		765,150,000
112 DH-SD6CE245U-HNI	2MP 45x Starlight IR PTZ Network Camera 1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Minimum Illumination:Color(0.005Lux@F1.6), B/W(0.0005Lux@F1.6) Max. 50/60fps@1080P, 3.95mm~177.7mm Focal Length 45x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, BLC, HLC, AGC, AWB Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map) Support Defog, ROI, EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 1*Video output, Rs485 7/2 Alarm in/out, 1/1 Audio in/out IR Distance up to 250m, PoE+, IP67, IK10		Call
113 SD5A245XA-HNR	2MP 45x Starlight IR WizSense Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS H.265; H.265+; H.264+; H.264; MJPEG (Sub Stream) Max. 50/60 fps@1080P Pan/Tilt Range Pan: 0°~360°; Tilt: -15°~+90° Manual Control Speed Pan: 0.1°/s~240°/s; Tilt: 0.1°/s~120°/s WDR(120db), HLC, BLC, 2D/3D DNR, ROI, EIS, Defog, AWB, AGC, Privacy Masking, Day/Night Auto Auto Tracking, SMD Plus, Intrusion, Tripwire, Object Abandoned/Missing, Face Detection Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Alarm I/O 2/1, Audio I/O 1/1, Supports Two Way Talk Focal Length 3.95 mm~177.7 mm, Min. Illumination Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0 Lux (IR on) IR distance up to 150 m, 45x optical zoom ONVIF Profile S&G&T, DC 24V/2.5A ± 25%; PoE+ (802.3at), Operating Temperature -40°C to +70°C IP67; IK10; TVS 6000V lightning protection; surge protection; voltage transient protection		749,200,000
114 DH-SD5A232XB-HNR	2MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS 32x optical zoom,Max. 50/60 fps@2M Min Illumination Color: 0.005 lux@F1.6,Focal Length 4.8 mm~154 mm Smart H.265+; H.265; Smart H.264+; H.264B Face detection ,tracking and perimeter protection,SMD PLUS IR distance up to 150 m,PoE+, IP67, IK10 WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC		649,200,000
115 DH-SD5A232XA-HNR	1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 50/60fps@1080P, 4.9mm~156mm 32x optical zoom Max 400°/s pan speed, 360° endless pan rotation WDR(120db), Day/Night(ICR), Ultra DNR(2D/3D), BLC, HLC Support Defog, ROI, Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Alarm 2/1 in/out, Audio 1/1 in/out IR Distance up to 150m, PoE+, IP67, IK10		649,200,000
116 DH-SD49425ZB-HNR	4MP 25x Starlight IR WizSense Network PTZ Camera, Image Sensor: 1/2.8" STARVIS™ CMOS 1/2.8" 4Megapixel CMOS, Powerful 25x optical zoom, ROM: 4GB, RAM: 1GB Starlight technology, Max.25/30fps@4M, Illuminator Number: 4 Focal Length: 4.8 mm~120 mm, Field of View: H: 60.0°~2.5°; V: 30.8°~2.2°; D: 66.7°~2.9° Min. Illumination: Color: 0.005Lux@F1.6, B/W: 0.0005Lux@F1.6: 0Lux@F1.6 (IR light on) Illuminator On/Off Control: Zoom Prio/Manual/SmartIR Perimeter protection, Face Detection, Smart Capture, SMD PLUS, IVS: Object Abandoned/Missing Support PoE+, IR distance up to 100m, BLC, WDR 120db, HLC, AGC, ANR, ROI, Electronic Defog Pan: 0.1°~200°/s, Tilt: 0.1°~120°/s, Presets: 300, Tour: 8 (up to 32 presets per tour), Pattern: 5, Scan: 5 IP66, DC 12V/3A, PoE+ (802.3at) Audio Input: 1, Audio Output: 1, Alarm I/O: 2/1		426,100,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
117 SD49425XB-HNR	4MP 25x Starlight IR WizSense Network PTZ Camera 1/2.8" STARVIS™ Progressive CMOS H.265+/H.265/H.264+/H.264/MJPEG (sub stream) Max.25/30fps@4M, 960P, 720P 4.8mm~120mm 25x optical zoom Max 240°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest) False Alarm Avoidance for Animals, Leaves, Bright Light Support Defog and EIS Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+ STARLIGHT WizSense		426,100,000
118 SD49225XA-HNR-S3	2MP 25x Starlight IR WizSense Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS , 25x optical zoom, Min Illumination Color: 0.005 lux@F1.6 Max. 25/30 fps@1080p IR distance up to 100 m , Perimeter protection, Face detection, SMD Plus, IP66 Pan: 0° to 360° endless, Tilt: -15° to +90°, auto flip 180° , Pan: 200°/s; Tilt: 100°/s Smart H.265+; H.265; Smart H.264+; H.264B; H.264M; H.264H; MJPEG (Sub Stream) Tripwire and intrusion. Support alarm triggering by target types (human and vehicle) WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC STARLIGHT WizSense		350,700,000
119 SD49225XA-HNR	2MP 25x Starlight IR PTZ AI Network Camera 1/2.8" STARVIS™ CMOS H.265+/H.265/H.264+/H.264/MJPEG (sub stream) Max. 1~60fps@1080P, 960P, 720P 4.8mm~120mm 25x optical zoom Max 240°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest) False Alarm Avoidance for Animals, Leaves, Bright Light Support Defog and EIS Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+ STARLIGHT WizSense		350,700,000
120 SD49225DB-HNY	2MP 25x Starlight IR Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom - Focal Length 4.8 mm~120 mm Max. 25/30 fps@1080p Min. Illumination Color: 0.005 lux@F1.6 B/W: 0.0005 lux@F1.6 0 lux (IR light on) Illumination Distance 100 m (328.08 ft) (IR) Max. Aperture F1.6~F3.5 Smart IR - 4 IR - S/N Ratio ≥ 55 dB IVS (Perimeter Protection) : Tripwire , intrusion / SMD Plus / Face Detection / Motion Detection Smart H.265+; H.265; Smart H.264+; H.264B; H.264M; MJPEG (Sub Stream) WDR 120db, Day/Night Auto (ICR)/Color/B/W, HLC, BLC, AWB, AGC, 2D DNR, 3D DNR, RoI, EIS, Defog Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Alarm in/out 2/1, Audio in/out 1/1, 12 VDC/3 A, PoE+, IP66, FTP/ Micro SD card (512 GB)/ NAS STARLIGHT WizSense		350,700,000
121 SD49225ZB-HNR	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom - Focal Length 4.8 mm~120 mm Max. 25/30 fps@1080p - Min. Illumination Color: 0.005 lux@F1.6 / B/W: 0.0005 lux / 0 lux (IR light on) IVS (Perimeter Protection) : Tripwire , intrusion / SMD Plus / Face Detection / Motion Detection Smart H.265+; H.265; Smart H.264+ WDR(120dB), DNR(2D/3D), BLC, HLC, AWB, AGC , RoI , Electronic Defog IR distance up to 100 m - Smart IR - 4 IR - S/N Ratio ≥ 55 dB Presets 300 / Tour 8 (up to 32 presets per tour) / Pattern 5 / Scan 50 Alarm I/O : 2/1 - IP66 - Power Supply 12 VDC, 3 A - PoE+ Storage : FTP/ Micro SD card (512 GB)/ NAS STARLIGHT		350,700,000
122 SD49425GB-HNR	4MP 25x Starlight IR Network PTZ Camera 1/2.8" STARVIS™ CMOS 25x optical zoom, Focal Length 5 mm~125 mm Starlight technology, Min. Illumination Color: 0.005 lux@F1.6 B/W: 0.0005 lux@F1.6 0 lux@F1.6 (IR light on) Max. 25/30fps@4M. IR distance up to 100 m Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Perimeter protection, Face detection, SMD 4.0, Acupick IP66, Audio I/O 1/1, Alarm I/O 2/1 STARLIGHT ACUPICK		426,100,000

رقم	نموذج	مواصفات فنية	تصوير	سعر (ريال)
123	SD59430U-HNI	1/3" CMOS Sensor H.265+/H.265/H.264+/H.264 Encoding, Ultra-low bit rate Max. 25/30fps@4M(2592×1520) & 50/60fps @1080P resolution WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus 4.5mm ~ 135.0mm , 30x Optical Zoom Max 400°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Micro SD card memory , 64 GB Audio In/Out, Alarm In/Out, IP66, POE+ IR Distance up to 100m(AC24V)/ 80m(DC12V) Smart Detection (Tripwire Intrusion Scene Change Face Anandoned-Missing Object)		557,900,000
124	SD5A432XB-HNR	4MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+, H.264+, H.265, H.264, MJPEG(Sub Stream) 3 Stream, Max. 25/30fps@4M Min. Illumination Color: 0.005 Lux@F1.35, B/W: 0.0005 Lux@F1.6, 0 Lux (IR on) 4.8 mm–154 mm Powerful 32x optical zoom, Max. Aperture F1.35–F4.4 Support human, motor vehicle and non-motor vehicle image capture Tripwire and intrusion. Support alarm triggering by target types (human and vehicle) Support filtering false alarms caused by animals, rustling leaves, bright lights, etc. Pan: 0° to 360° endless , Tilt: –15° to +90°, auto flip 180° , Pan: 0.1°–300°/s , Tilt: 0.1°–200°/s WDR(120), EIS, Defog, Rol,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Alarm I/O : 2/1 , Audio I/O : 1/1, PoE+, IP67; IK10; TVS 6000 V		701,350,000
125	DH-SD5A432GB-HNR	4MP 32x Starlight IR WizSense Network PTZ Camera Image Sensor 1/2.8" CMOS, Max. Resolution 2560 (H) × 1440 (V) Electronic Shutter Speed 1/1 s–1/30,000 s, Min. Illumination, Color: 0.005 lux@F1.6, B/W: 0.0005 lux@F1.6 Illumination Distance 150 m(IR), Focal Length 4.8 mm–154 mm Manual Control Speed Pan: 0.1°/s–300°/s, Tilt: 0.1°/s–200°/s Preset 300, Tour 8 (up to 32 presets per tour), Pattern 5, Scan 5 Perimeter Protection, Face Detection, Auto Tracking, Quick Pick, SMD BLC, WDR 120 db, WB, AGC, ANR, Rol, EIS, Defog Electronic, S/N Ratio ≥55 dB Storage : FTP, Micro SD card (512 GB); NAS, Alarm I/O 2/1, Audio I/O 1/1 Power Supply 24 VDC, 2.5 A (± 25%), Operating Temperature –40 °C to +70 °C		733,200,000
126	SD5A432XA-HNR	4MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+, H.264+, H.265, H.264, MJPEG(Sub Stream) 3 Stream, Max. 25/30fps@4M Min. Illumination Color: 0.005 Lux@F1.35, B/W: 0.0005 Lux@F1.35, 0 Lux (IR on) 4.9 mm–156 mm Powerful 32x optical zoom, Max. Aperture F1.35–F4.4 Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan: 0°–360° endless rotation WDR(120), EIS, Defog, Rol,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR Deep Learning, Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm Filtering Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Micro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile S&G&T IR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10, 6000V lightning proof; surge protection; voltage transient protection		682,500,000
127	SD5A445GB-HNR	4MP 45x Starlight IR Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.264H; H.264B; Smart H.265+; H.264; H.265; MJPEG(Sub Stream); Smart H.264+ Min. Illumination Color: 0.005 lux@F1.6 B/W: 0.0005 lux@F1.6 0 Lux (IR light on) 3.95 mm–177.75 mm 45x optical zoom Starlight technology IR distance up to 150 m WDR(120), EIS, Defog, Rol,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR Perimeter protection, Face detection, SMD 4.0, Quick Pick, Auto-tracking 3.0 Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Alarm in/out 2/1, Audio in/out 1/1, IP67, IK10, TVS 6000V lightning proof; surge protection; voltage transient protection		876,750,000
128	SD5A445XA-HNR-1T	4MP 45x Starlight IR DHOP Network PTZ Camera - Max. 25/30 fps@4MP 1/2.8" 4Megapixel STARVIS™ CMOS - Progressive CMOS - ROM : 4GB - RAM : 1GB 1T computing power for enhanced performance - Flash : 350 M - Memory : 300 M Compression H.265/H.265+/H.264+/H.264/MJPEG(Sub Stream) Min. Illumination Color: 0.005 Lux@F1.6 / B/W: 0.0005 Lux@F1.6 / 0 Lux (IR light on) Starlight technology - Illumination Distance : 150 m (492.13 ft) - Illuminator Number : 4 Focal Length 3.95 mm–177.7 mm - Max. Aperture F1.6–F4.95 - Field of View H: 70.3°–1.8°; V: 37°–1° Pan: 0°–360°; Tilt: –15° +90° / Manual Control Speed : Pan: 0.1°/s–300°/s; Tilt: 0.1°/s–200°/s Preset Speed : Pan: 400°/s; Tilt: 300°/s - Presets : 300 - Tour 8 (up to 32 presets per tour) - Pattern : 5 WDR(120), HLC, BLC, AWB, AGC, 2D DNR, 3D DNR, ROI, EIS, Electronic Defog Alarm I/O 2/1 - Audio I/O 1 (Line in; bare wire)/1 (Line out; bare wire) - 1 RJ-45 Port 10/100Base-T DC 24 V/2.5 A ± 25% - PoE+ (802.3at), 11 W / 20 W (IR light on) IP67, IK10		852,850,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
129	SD5A445XA-HNR	4MP 45x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+/H.265+/H.264+/H.264/MJPEG(Sub Stream) 3 Streams, Max. 25/30fps@4M Min. Illumination Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0Lux (IR light on) 3.95 mm~177.7 mm Powerful 45x optical zoom Max. Aperture F1.6~F4.95 Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan: 0°~360° endless rotation WDR(120), EIS, Defog, Rol, 2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR Deep Learning, Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm Filtering Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Micro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile S&G&T IR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10, 6000V lightning proof; surge protection		852,850,000
130	SD6CE445XA-HNR	4MP 45x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+/H.265+/H.264+/H.264/MJPEG(Sub Stream) Max. 25/30fps@4MP Minimum Illumination Color: 0.005 Lux@F1.6; B/W: 0.0005 Lux@F1.6; 0 Lux@F1.6 (IR on) 3.95 mm~177.75 mm Powerful 45x optical zoom Max. Aperture F1.6~F4.95 Pan/Tilt Range Pan: 0°~360° endless; Tilt: -20°~90°, auto flip 180° Preset Speed Pan: 300° /s ; Tilt: 200° /s WDR 120db, BLC, HLC, Auto ICR, AWB, AGC, 2D/3D DNR, Rol, EIS, Defog Deep-learning-based auto tracking and perimeter protection Face detection, SMD Plus, Tripwire, Intrusion. Human/Vehicle/Motor-non Motor Vehicle Detection Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Micro SD card (256G), 1/1 Audio I/O, 7/2 Alarm I/O, ONVIF Profile S&G&T IR distance up to 250m, DC 24 V/2.5 A, PoE+, IP67, IK10		892,650,000
131	DHI-NVR1104HS-S3/H (V2.0)	4 Channel IPC Input, 4K Lite H.265 NVR 1/4 Live & Playback Smart H.265+/Smart H.264+/H.265/H.264 Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60Mbps for forwarding. Up to 8MP Resolution for Preview & Playback Decoding Capacity : 1-ch@8MP(30FPS) or 1-ch@5MP(30FPS) or 2-ch@4MP(30FPS) or 2-ch@3MP(30FPS) or 4-ch@1080P(30FPS) Video Output 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P 1 SATA 2.0 port, up to 8TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G)		45,500,000
132	NVR2104HS-P-I	4 Channel Compact 1U 4PoE WizSense Network Video Recorder, New 4.0 user interface H.264+/H.265/Smart H.264+/Smart H.265+/MJPEG, H.265 auto switch 1 VGA/1 HDMI simultaneous video output, HDMI 4K, non-simultaneous video output is also supported on 1080p 1-channel face detection and recognition (AI by NVR); or 2-channel perimeter detection (AI by NVR); or 4-channel SMD (AI by NVR); up to 10 face databases and 5,000 face images Max. decoding capability: 4x1080P@30fps. Supports adaptive decoding Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding Resolution 12M/8M/5M/4M/3M/2M/720P/D1 AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps AI enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps 4 PoE Ports, 1 SATA port, up to 8 TB, 1 front USB 2.0 port, 1 rear USB 2.0 port, 1 RJ-45 port (10/100 Mbps), 4 RJ-45 ports with PoE power supply (10/100 Mbps)		95,650,000
133	NVR2104HS-4KS2	4 channel IP camera input H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support		51,850,000
134	NVR2104HS-P-4KS2	4 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, 4PoE Port, P2P support		67,900,000
135	DHI-NVR1108HS-S3/H	8 Channel IPC Input, 4K Lite H.265 NVR 1/4/8/9 Live & Playback Smart H.265+/Smart H.264+/H.265/H.264 Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding. Up to 8MP Resolution for Preview & Playback Decoding Capacity : 1-ch@8MP(30FPS) or 1-ch@5MP(30FPS) or 2-ch@4MP(30FPS) or 2-ch@3MP(30FPS) or 4-ch@1080P(30FPS) Video Output 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P 1 SATA 2.0 port, up to 8TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G)		55,700,000

رقم	نموذج	مميزات تقنية	تصوير	سعر (ريال)
136	NVR2108HS-4KS3	NEW 12MP AI 8CH Compact 1U 1HDD Lite Network Video Recorder Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding capability: 6 × 1080p@30 fps Max. 80/80/60 Mbps incoming/recording/outgoing bandwidth Supports IPC up to 12MP AI by Recorder supports 4-channel SMD AI by Camera supports perimeter protection and SMD Supports one-click arming and disarming 1 HDMI, 1 VGA, Audio I/O 1/1(two way talk only), 1 SATA up to 20TB LAN 10/100, 12 VDC, 1.5 A		76,800,000
137	NVR2108HS-4KS2	4K 8 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support		63,800,000
138	NVR2108HS-8P-4KS2	4K 8 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, 8Port PoE, P2P support		90,250,000
139	NVR2108HS-S3	8 Channel Lite Series, Compact 1U 1HDD Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264 decoding format Max. decoding capability: 6 × 1080p@30 fps. Supports adaptive decoding AI by camera: perimeter protection, and SMD Plus Multi-channel Playback Up to 8 channels, HDD interface 1 SATA port, up to 16 TB Audio Input/Out : 1/1 , Network Port 1 × RJ-45, 10/100 Mbps Power Supply 12 VDC, 1.5 A		74,250,000
140	NVR2108HS-I2	WizSense AI 8 Channel Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Max. decoding capability: 6 × 1080p@30 fps. Supports adaptive decoding 1-channel face detection and recognition (AI by NVR) 1-channel perimeter protection (AI by NVR), 4-channel SMD Plus (AI by NVR) AI by camera: Face detection and recognition, perimeter protection, and SMD Plus HDD 1 SATA port, up to 10 TB, RCA Input 1, RCA Output 1 Power Supply 12 VDC, 1.5 A, Operating Temperature -10 °C to +55 °C		92,500,000
141	NVR2108HS-I	WizSense 12MP AI 8 Channel 12MP WizSense NVR 1/4/8 Live & Playback Smart H.265+/H.264+/MJPEG Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding AI Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps AI Enabled : 1ch 8MP@30fps or 1ch 5MP@30fps or 2ch 4MP@30fps or 4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition AI by NVR up to 5000 Face Library or 2ch Perimeter AI By NVR or 4ch SMD Plus AI by NVR, Human/Vehicle Classification 1 SATA II port, up to 8TB 1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)		92,500,000
142	NVR4108HS-4KS2	4K 8 channel IP camera input 1/4/8/9 channel Live Preview, 8CH Playback H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support		74,950,000
143	DHI-NVR2216-4KS2	4K 16 Channel 4K Lite H.265 NVR 1/4 Live & Playback Dual-core embedded processor, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth, Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output 2 SATA III Ports, up to 6TB capacity for each, Total 12TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (1000Mbps), P2P Support		98,900,000
144	NVR2116HS-I	WizSense 12MP AI 16 Channel 12MP WizSense NVR 1/4/9/16 Live & Playback Smart H.265+/H.264+/MJPEG Network Bandwidth 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwarding AI Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps AI Enabled: 1ch 8MP@30fps/1ch 5MP@30fps/2ch 4MP@30fps/4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition AI by NVR up to 5000 Face Library or 2ch Perimeter AI By NVR or 4ch SMD Plus AI by NVR, Human/Vehicle Classification 1 SATA II port, up to 8TB 1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)		116,500,000

قېتىم (روپال)	تصویر	مشخصات فنی	مدل ردیف
114,850,000		16 Channel Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Network Bandwidth: AI off: Access: 144 Mbps; Storage: 144 Mbps; Forward: 72 Mbps AI on: Access: 72 Mbps; Storage: 72 Mbps; Forward: 36 Mbps Resolution: 12MP; 8MP; 5MP; 4MP; 3MP; 2MP; 720p; D1 Decoding Capability: AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps AI enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps 1 × VGA, 1 × HDMI (simultaneous) 4K Output 1-channel face detection and recognition (AI by NVR); 1-channel perimeter protection (AI by NVR); up to 10 face databases and 5,000 face images; 4-channel SMD Plus (AI by NVR); AI by camera: Face detection and recognition, perimeter protection, and SMD Plus 1 SATA II port, up to 10TB 1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)	145 NVR2116HS-I2 12MP WizSense AI
148,700,000		16 Channel 12MP WizSense NVR 1/4/9/16 Live & Playback Smart H.265+/H.264+/MJPEG Network Bandwidth 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwarding AI Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps AI Enabled: 1ch 8MP@30fps/1ch 5MP@30fps/2ch 4MP@30fps/4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition AI by NVR up to 5000 Face Library or 2ch Perimeter AI By NVR or 4ch SMD Plus AI by NVR و Human/Vehicle Classification 2 SATA 2.0 port, up to 8TB each, Total 16TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)	146 DHI-NVR2216-I 12MP WizSense AI
148,700,000		16 Channel 1U 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Max. decoding capability: 6 × 1080p@30 fps. Supports adaptive decoding AI by NVR: 1-channel face detection and recognition; 1-channel perimeter protection; up to 10 face databases and 5,000 face images; 4-channel SMD Plus AI by camera: Face detection and recognition, perimeter protection, and SMD Plus 2 SATA each up to 10TB, 2 USB, 1 HDMI, 1 VGA, 1 LAN 1000Mbps, Audio in/out 1/1, Onvif (S, T, G)	147 DHI-NVR2216-I2
110,200,000		16 Channel Compact 1U 4K&H.265 Lite Network Video Recorder Smart H.265+/Smart H.264+/H.265/H.264; H.265 auto switch Max 80Mbps Incoming Bandwidth Up to 8MP Resolution for Preview and Playback 8-channel decoding@1080p (30 fps) AI by Camera: Perimeter protection; SMD Plus; people counting; heat map target classification (human, vehicle) HDMI(4K)/VGA simultaneous video output 1 SATA III port, up to 10 TB, 1 front USB 2.0 port, 1 rear USB 3.0 port Audio I/O 1/1 for Two Way Talk Only 100 Mbps Network Card, P2P support	148 NVR4116HS-4KS2 4K AI
110,200,000		16 channel IP camera input, 16 channel Live Preview Smart H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback 16-ch@720P decoding capacity Support SMD Plus by Camera HDMI(4K)/VGA simultaneous video output Support 1 SATA HDD up to 8TB, 2 USB2.0 100 Mbps Network Card, P2P support	149 NVR4116HS-4KS2/L 4K
110,200,000		16CH Compact 1U 1HDD Lite Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30 fps Max. 160/160/80 Mbps incoming/recording/outgoing bandwidth Supports IP cameras with a resolution up to 12 MP AI by Recorder supports 4-channel SMD Plus AI by Camera supports face detection and recognition, perimeter protection, SMD Plus, people counting, stereo analysis and heat map Supports EPTZ, and one-click arming and disarming 1 SATA port up to 20 TB, 1 HDMI, 1 VGA Simultaneous/Heterogeneous, Audio I/O 1/1, Alarm I/O 2/1, 1000Mb LAN, ONVIF 22.12(Profile T; Profile S; Profile G)	150 NVR4116HS-4KS3 4K AI
148,700,000		16 channel IP camera input, 16 channel Live Preview Smart H.265+/H.264+ codec decoding Max160Mbps incoming bandwidth Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding 8-ch@1080P decoding capability HDMI(4K)/VGA simultaneous video output AI by Camera: Face detection with Face Attributes, perimeter protection, IVS, people counting, heat map, and SMD Support 2 SATA HDD up to 10TB, 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, P2P support, ONVIF(profile T/S/G)	151 NVR4216-4KS2/L 4K UPGRADED

رقم	نموذج	مواصفات تقنية	تصوير	السعر (ريال)
152	NVR4216-16P-4KS2/L	16 channel IP camera input, 16 channel Live Preview Smart H.265+/H.264+ codec decoding Max160Mbps incoming bandwidth Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding 8-ch@1080P decoding capability HDMI(4K)/VGA simultaneous video output AI by Camera: Face detection with Face Attributes, perimeter protection, IVS, people counting, heat map, and SMD Support 2 SATA HDD up to 10TB, 2 USB Ports (1 × front USB2.0, 1 × back USB2.0) 4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, 16 Port PoE, ONVIF(profile T/S/G)		240,500,000
153	NVR4216-4KS3	16CH 1U 2HDDs Lite Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats Max. 160/160Mbps incoming/recording bandwidth Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30 fps HDMI(4K)/VGA simultaneous video output AI by Recorder supports 4-channel SMD Plus AI by Camera supports face detection(6CHs) and recognition(6CHs), perimeter protection(6CHs), SMD Plus(6CHs), people counting, stereo analysis and heat map Supports IP cameras with a resolution up to 12MP 2 SATA ports. Each disk up to 20TB, Audio in/out 1/1 for Two Way Talk, Alarm in/out 4/2, USB 2 Ports, LAN 1*1000, P2P support, ONVIF(profile T/S/G)		148,700,000
154	NVR4232-EI	32CH 1U 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled) Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding HDMI(4K)/VGA simultaneous & Independent video output AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus AI by Camera: Face detection(8CHs) and recognition(8CHs), perimeter protection(8CHs); SMD Plus(8CHs); people counting; stereo analysis; heat map Supports IP cameras with a resolution up to 16MP 2 SATA ports, up to 16TB, Audio in/out 1/1 for Two Way Talk, Alarm in/out 4/2, USB 2 Ports, LAN 1*1000, P2P support, ONVIF(profile T/S/G)		212,400,000
155	NVR4232-4KS2/L	32 Channel 1U 2HDDs Network Video Recorder Smart H.265+/H.264+ codec decoding Max160Mbps incoming bandwidth Max. decoding capability: 8 × 1080p@30 fps HDMI(4K)/VGA simultaneous video output AI by Camera: Face detection with attributes, perimeter protection, IVS, people counting, heat map, and SMD, Human & Vehicle Classification 2 SATA III ports, up to 10 TB each port, 1 × front USB2.0; 1 × back USB2.0 4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, P2P support, ONVIF(profile T/S/G)		175,450,000
156	NVR4232-4KS2	32 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output 1*1000Mbps Network Card, P2P support		172,500,000
157	NVR4432-4KS2/I	32 Channel 1.5U 4HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Access, storage or forwarding at 256 Mbps, Max. decoding capability: 10 × 1080p@30 fps Face detection; face recognition; perimeter protection,SMD Plus Multi-channel Playback Up to 16 channel The maximum HDD capacity 4 SATA ports, up to 10 TB Alarm Input 16,Alarm Output 4 2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet port		317,400,000
158	NVR4232-4KS3	32CH 1U 2HDDs Lite Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats Max. 160Mbps incoming bandwidth Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30 fps HDMI(4K)/VGA simultaneous video output AI by Recorder supports 4-channel SMD Plus AI by Camera supports face detection(6CHs) and recognition(6CHs), perimeter protection(6CHs), SMD Plus(6CHs), people counting, stereo analysis and heat map Supports IP cameras with a resolution up to 12 MP 2 SATA ports. Each disk up to 20TB, Audio in/out 1/1 for Two Way Talk, Alarm in/out 4/2, USB 2 Ports, LAN 1*1000, P2P support, ONVIF(profile T/S/G)		178,650,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
159	NVR4432-EI	32CH 1.5U 4HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled) Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding 1 HDMI, 1 VGA, 4K, Simultaneous/heterogeneous AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; ANPR; people counting; stereo analysis; heat map Supports IP cameras with a resolution up to 16MP 4 SATA ports, up to 16 TB each, Audio I/O 1/1, Alarm I/O 16/4, 3 USB Ports, 2 1000Mb LAN ONVIF 22.06(Profile T; Profile S; Profile G)		357,450,000
160	DHI-NVR5232-4KS2(V2.0)	32Channel 1U 4K & H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 1*HDMI(4K)/1*VGA simultaneous video output 2*SATA HDDs(10 TB for each HDD), 2 USB(1 USB3.0,1 USB2.0) 1*1000 Mbps Network Card, RS232, RS485,4/2 Alarm In/out , P2P Support		310,950,000
161	NVR5232-EI	32 Channels 1U 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps Max. 384 Mbps incoming/recording/outgoing bandwidth 16ch AcuPick, N+M Clustering, Face Detection, Face Recognition, Face Attributes, Face Expression, SMD Plus, Perimeter Protection, Metadata, ANPR, Stereo Analysis, Heatmap, People Counting AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting Audio in/out 1/1, Alarm in/out 4/2, 2 SATA each up to 16TB, RS232, RS485, 2 USB 2, 1 USB 3, 1 HDMI, 1 VGA, 1 LAN		346,050,000
162	NVR5432-EI	32 Channels 1.5U 4HDD WizSense Network Video Recorder Industrial-grade processor - Embedded Linux OS Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Max. 384 Mbps incoming/recording/outgoing bandwidth AI by recorder: 2ch face detection and recognition, 4ch perimeter protection, and 8ch SMD Plus AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting Network Port 2 (10/100/1000 Mbps Ethernet port, RJ-45) 4 SATA ports, up to 16 TB - Security baseline 2.3 - Supports 4K display - Alarm In/Out : 16ch/6ch		478,200,000
163	NVR5432-4KS2(V2.0)	32Channel 1.5U 4K & H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0) Support 1 e-SATA, 2*1000 Mbps Network Card RS232, RS485,16/6 Alarm In/out , P2P Support		406,600,000
164	NVR5832-EI	32 Channels 2U 8HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Max. 384 Mbps incoming/recording/outgoing bandwidth Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps Support AcuPick with Max. 16-Channel, Support N+M cluster AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. AI by camera: Face detection(16CHs) and recognition(16CHs), perimeter protection(16CHs), SMD Plus(16CHs), metadata(8CHs), ANPR(8CHs), stereo analysis, heat map, and people counting Audio in/out 1/2 for Two way talk only, Alarm in/out 16/8, USB*3, HDMI*2, VGA*2, LAN*2*1000, eSATA*1, 8 SATA Ports each up to 20TB, RS-232, RS-485, P2P Support, Onvif (S/T/G)		733,200,000
165	NVR5832-4KS2	32 channel IPC input, 32 Channel Live Preview H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview&playback Max 16ch@1080P 4ch@4K H.265 H.264 Playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB, 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card, RS232, 16 Alarm In , 6 Relay Output, P2P Support, Raid 0/1/5/6/10		526,100,000
166	DHI-NVR5464-4KS2(V2.0)	64Channel 1.5U 4K&H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0) Support 1 e-SATA, 2*1000 Mbps Network Card, RS232, RS485,16/6 Alarm In/out , P2P Support		478,200,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
167	NVR5464-EI	64 Channels 2U 8HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Industrial-grade processor - Embedded Linux Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps Support AcuPick with Max. 16-Channel - Support N+M cluster - Support Raid0/1/5/6/10 Max. 384 Mbps incoming/recording/outgoing bandwidth AI by recorder: 2-ch face detection and recognition, 4-ch perimeter protection, and 8-ch SMD Plus AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting Security baseline 2.3 - Alarm In/Out : 16/6 - 4 SATA ports, each disk up to 20 TB HDMI:2 - VGA:2 - USB:4 - RS485:2 - RS232:1		604,450,000
168	NVR5864-EI	64 Channels 2U 8HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Industrial-grade processor - Embedded Linux Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps Support AcuPick with Max. 16-Channel - Support N+M cluster - Support Raid0/1/5/6/10 Max. 384 Mbps incoming/recording/outgoing bandwidth AI by recorder: 2-ch face detection and recognition, 4-ch perimeter protection, and 8-ch SMD Plus AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting Security baseline 2.3 - Alarm In/Out : 16/8 - 8 SATA ports, each disk up to 20 TB HDMI:2 - VGA:2 - USB:4 - RS485:2 - RS232:1		843,400,000
169	NVR5864H-XI	64CH 2U 8HDDs WizMind Network Video Recorder Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG Max. decoding capability: 32 × 1080p@30 fps Max. 512/512/512 Mbps incoming/recording/outgoing bandwidth Supports IPC up to 32 MP, AcuPick with up to 36 channels, EPTZ, and one-click arming and disarming AI by Recorder supports 8-channel face detection and recognition, up to 20 face databases and 200,000 face images; 8-channel metadata; 24-channel perimeter protection; 32-channel SMD Plus AI by Camera supports face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting RAID 0/1/5/6/10, N+M cluster, and ISCSI, HDD hot swapping 2 VGA, 2 HDMI, Audio I/O 1/1, Alarm I/O 16/8, 1 E-SATA, 8 SATA each up to 20TB total 160TB, 2x LAN 1000, USB:4 - RS485:2 - RS232:1		1,182,000,000
170	DHI-NVR5864-4KS2(V2.0)	64 Channel 2U 4K & H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 8*SATA HDDs(10 TB for each HDD), 4 USB(2 USB3.0,2 USB2.0) 1*e-SATA, 2*1000 Mbps Network Card, RS232, RS485,16/6 Alarm In/out , P2P Support		701,350,000
171	NVR608-32-4KS2	Intel Dual-core Processor, 32 channel IPC input, 32 Channel Live Preview (1st Screen:1/4/8/9/16/25/36,2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding, Max 384Mbps incoming bandwidth Up to 12Mp resolution preview&playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB,1 eSATA Port Support Raid 0/1/5/6/10, 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card, RS232 , RS485, 16 Alarm In , 8 Relay Output		597,850,000
172	NVR608-64-4KS2	Intel Quad-core Processor 64 channel IPC input, 32 Channel Live Preview (1st Screen:1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16), H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview & playback 2HDMI/VGA simultaneous video output 8 SATA III ports, up to 10 TB for a single HDD,1 eSATA Port Support Raid 0/1/5/6/10 Support Smart Tracking and Intelligent Video 4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card RS232 , RS485, 16 Alarm In , 8 Relay Output		1,036,100,000
173	DHI-NVR608H-32-XI	32 Channels 2U 8HDDs WizMind Network Video Recorder Industrial-grade processor AI disabled: 1024 Mbps incoming, 1024 Mbps recording and 800 Mbps outgoing AI enabled: 512 Mbps incoming, 512 Mbps recording and 400 Mbps outgoing Resolution 32 MP; 24 MP; 16 MP; 12 MP; 8 MP; 5 MP; 4 MP; 1080p; 720p; D1 Supports N+M cluster Support Raid0/1/5/6/10 & HDD hot swapping AI by recorder: 4ch face detection and recognition; 8ch metadata; 24ch perimeter protection; 32ch SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, and people counting 2-channel VGA, 4-channel HDMI video output with Simultaneous & Independent Video Mode HDMI1 and HDMI2 is 4K, max. resolution of HDMI3 is 8K, max. resolution of HDMI4 is 1080p Support Smart H.265+; H.265; Smart H.264+; H.264; MPEG4; MJPEG Audio I/O 1/2, Alarm I/O 16/8, HDD 8 SATA Ports 16TB Each, 1 e-SATA Port, 4 USB Ports, 2 Network Ports 10/100/1000		1,068,000,000

رقم المنتج	نموذج	مواصفات تقنية	الصورة	السعر (ريال)
174	DHI-NVR608H-64-XI	64 Channels 2U 8HDDs WizMind Network Video Recorder Industrial-grade processor AI disabled: 1024 Mbps incoming, 1024 Mbps recording and 800 Mbps outgoing AI enabled: 512 Mbps incoming, 512 Mbps recording and 400 Mbps outgoing Resolution 32 MP; 24 MP; 16 MP; 12 MP; 8 MP; 5 MP; 4 MP; 1080p; 720p; D1 Supports N+M cluster Support Raid0/1/5/6/10 & HDD hot swapping AI by recorder: 4ch face detection and recognition; 8ch metadata; 24ch perimeter protection; 32ch SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, and people counting 64ch - metadata, ANPR 32ch 2-channel VGA, 4-channel HDMI video output with Simultaneous & Independent Video Mode HDMI1 and HDMI2 is 4K, max. resolution of HDMI3 is 8K, max. resolution of HDMI4 is 1080p Support Smart H.265+; H.265; Smart H.264+; H.264; MPEG4; MJPEG Audio I/O 1/2, Alarm I/O 16/8, HDD 8 SATA Ports 16TB Each, 1 e-SATA Port, 4 USB Ports, 2 Network Ports 10/100/1000	  	1,514,300,000
175	NVR608H-128-XI	128 Channels 2U 8HDDs WizMind Network Video Recorder Industrial-grade processor AI disabled: 1024 Mbps incoming, 1024 Mbps recording and 800 Mbps outgoing AI enabled: 512 Mbps incoming, 512 Mbps recording and 400 Mbps outgoing Resolution 32 MP; 24 MP; 16 MP; 12 MP; 8 MP; 5 MP; 4 MP; 1080p; 720p; D1 Supports N+M cluster Support Raid0/1/5/6/10 & HDD hot swapping AI by recorder: 4ch face detection and recognition; 8ch metadata; 24ch perimeter protection; 32ch SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, and people counting 64ch - metadata, ANPR 32ch 2-channel VGA, 4-channel HDMI video output with Simultaneous & Independent Video Mode HDMI1 and HDMI2 is 4K, max. resolution of HDMI3 is 8K, max. resolution of HDMI4 is 1080p Support Smart H.265+; H.265; Smart H.264+; H.264; MPEG4; MJPEG Audio I/O 1/2, Alarm I/O 16/8, HDD 8 SATA Ports 16TB Each, 1 e-SATA Port, 4 USB Ports, 2 Network Ports 10/100/1000	  	2,120,000,000
176	DHI-NVR608-128-4KS2	128 Channel 2U Ultra 4K H.265 Network Video Recorder (1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview & playback 2HDMI(different Source)/VGA simultaneous video output Support 8 SATA (8TB for each HDD),1 eSATA Port Support Raid 0/1/5/10 Support Smart Tracking and Intelligent Video 4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card RS232 , RS485, 16/8 Alarm In/Output	 	1,211,400,000
177	ESS1508C	2U standard 19-inch rack case Connect master device via eSATA or USB 1 eSATA port transmission speed up to 3Gbps 1 USB 3.0 port data transmission higher than normal Powerful R / W performance: read >64MB/s, write >64MB/s ESS1508C: Max support Internal 8 SATA HDD up to 48TB Recommended with DVR, NVR connection		184,950,000
178	PFS3006-4ET-36	6-Port Fast Ethernet Switch with 4-Port PoE 4 PoE ports with 10/100 Mbps Base-TX 2 uplink ports with 10/100Mbps Base-TX Port1-4 ≤30W, whole PoE budget ≤36W Support 802.3af and 802.3at standards Operating Temperature: -10°C to +55°C Support 250 m long distance PoE transmission Support PoE watchdog Switching Capacity 1.2 Gbps, Packet Forwarding Rate 0.89 Mpps, MAC Table Size 2K, Jumbo Frame 2048 byte Standards IEEE 802.3, IEEE 802.3u, IEEE 802.3X ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 6kV Differential mode: 4kV		36,100,000
179	PFS3106-4ET-60 (V2.0)	4-Port PoE Switch (Unmanaged) 4 × RJ-45 10/100 Mbps (PoE) 1 × RJ-45 10/100/1000 Mbps (Uplink) 1 × SFP 100/1000 Mbps (Uplink) Intelligent PoE, Hi-PoE 60W (Orange Port), PoE watchdog, 250 m long distance PoE transmission Wide operating temperature: -30°C to +65°C (-22°F to +149°F) Switching Capacity 6.80 Gbps, Packet Forwarding Rate 3.57 Mpps, Packet Buffer Memory 1 Mbit, MAC Table Size 8K Communication Standard IEEE802.3; IEEE802.3u; IEEE802.3X; IEEE 802.3ab; IEEE 802.3z PoE Standard IEEE802.3af; IEEE802.3at; Hi-PoE, 250 m long distance PoE transmission Statics Protection Air discharge:15kV Contact discharge:8kV, Thunder-proof Common mode:4kV Differential mode:2kV	 	65,500,000
180	PFS3010-8ET-65	10-Port Fast Ethernet Switch with 8-Port PoE Port 1-8: 8 × RJ-45 10/100 Mbps (PoE) Port 9-10: uplink with 10/100 Mbps Support 802.3af and 802.3at standards Support 250 m long distance PoE transmission Support PoE watchdog Port1-8 ≤30W, whole PoE budget ≤65W Switching Capacity 2.0 Gbps, Packet Forwarding Rate 1.49 Mpps, MAC Table Size 2K, Jumbo Frame 2048 byte ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 6kV Differential mode: 4kV		51,400,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
181 PFS3110-8ET-96 (V2.0)	10-Port Unmanaged Desktop Switch with 8 Port PoE Port 1~8: 8 × RJ-45 10/100 Mbps (PoE) Port 9: 1 × RJ-45 10/100/1000 Mbps (uplink) Port 10: 1 × SFP 1000 Mbps (uplink) Communication Standard IEEE802.3/IEEE802.3u/IEEE802.3X/IEEE 802.3ab/IEEE 802.3z PoE Standard IEEE802.3af/ IEEE802.3at/ Hi-PoE/ IEEE802.3bt Port 1-2 ≤ 90 W, Port 3-8 ≤ 30W, totals 96 W Intelligent PoE, BT 90W, Long distance PoE, PoE watchdog, Wide working temperature Lightning Protection Air discharge:8kV Contact discharge:6kV, ESD Protection Common mode:4kV Differential mode:2kV		95,000,000
182 PFS3218-16ET-135	Layer 2 PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 16 × RJ45 10/100 Mbps Port 1~2≤60W, Port 3~16≤30W, totals≤135W IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z PoE Standard IEEE802.3af, IEEE802.3at, Hi-PoE Intelligent PoE, PD Alive(PoE Watchdog), Long Distance PoE Transmission, Smooth Transmission Wide Working Temperature: -10 to 55°C (14°F to 131°F), VLAN Port Isolation Switching Capacity 7.2 Gbps, Packet Forwarding Rate 5.3568 Mpps, Packet Buffer Memory 4 Mbit, MAC Table Size 8K ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 4kV Differential mode: 2kV		162,750,000
183 PFS3226-24ET-240	Layer 2 PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 24 × RJ45 10/100Mbps Intelligent PoE, PD Alive(PoE Watchdog), Long Distance PoE Transmission, Smooth Transmission Wide Working Temperature: -10 to 55°C (14°F to 131°F), VLAN Port Isolation Port1/2 support Hi-PoE (60W), PoE+, PoE Port 1-2≤60W, Port 3-24≤30W, totals≤240W IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z PoE Standard IEEE802.3af, IEEE802.3at, Hi-PoE Switching Capacity 8.8Gbps, Packet Forwarding Rate 6.5472 Mpps MAC Table Size 8K ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 4kV Differential mode: 2kV		208,800,000
184 PFT1300	PoE Extender 1*10/100 Base-T PoE power receiving port 1*10/100 Base-T PoE power supply port, supply power for the next extender 1*10/100 Base-T PoE power supply port, supply power for IPC Support passive PoE cascade power supply and Ethernet data exchange Support IEEE 802.3af/at standard power supply IP Camera able to cascade level 2 PoE Extender, connect to 3 IPC (power consumption <=8W), max transmission distance 300m		10,750,000
185 PFM700	*1 Channel HDMI Transmission Signal *1080P/1080i/720P/576P/576i/480P/480i Resolution Output Signal , *60M (max)Transmission Distance *Input voltage DC5V *Use single UTP (CAT-5E and CAT-6) real-time transmit 1-ch HD video, signal:support HDMI 1.3		30,550,000
186 NKB1000	Keyboard to Control : Dahua High Speed Dome (all models) Dahua Standalone DVR , Dahua Network High Speed Dome Network Video Server, Connection : RS485, RS422, USB, RS232 & Network Three Dimensional Joystick Control of PTZ Functions Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control, On-Screen Menu & User Operation Procedure Tips Connect to SmartPSS via USB		195,000,000